

Potassium hydroxide 0.5 mol/l in methanol

according to Regulation (EC) No 1907/2006

Revision date: 10.03.2025

Product code: 05069

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Potassium hydroxide 0.5 mol/l in methanol

UFI:

061F-S0H9-W00K-WKC7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	•	REC Day or Night Within USA and Canada: anada: +1 703-741-5970 (collect calls

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

Danger

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling methanol

potassium hydroxide

Signal word:



according to Regulation (EC) No 1907/2006

	Potassium hydroxide 0.5 mol/l in methanol	
Revision date: 10.03.2025	Product code: 05069	Page 2 of 14
Pictograms:		
Hazard statements		
H225 H290 H301+H311+H331 H314 H370	Highly flammable liquid and vapour. May be corrosive to metals. Toxic if swallowed, in contact with skin or if inhaled. Causes severe skin burns and eye damage. Causes damage to organs.	
Precautionary statemer	nts	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P240 P280	Ground and bond container and receiving equipment. Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	
P301+P330+P331 P302+P352 P304+P340 P305+P351+P338	 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water and soap. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. 	
P308+P311 P403+P233	IF exposed or concerned: Call a POISON CENTER/doctor. Store in a well-ventilated place. Keep container tightly closed.	

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No 1272/2008)					
67-56-1	methanol					
	200-659-6	603-001-00-X	01-2119433307-44			
	Flam. Liq. 2, Acute Tox. 3, Ac	cute Tox. 3, Acute Tox. 3, STOT	SE 1; H225 H331 H311 H301 H370			
1310-58-3	potassium hydroxide			1 - < 5 %		
	215-181-3	019-002-00-8	01-2119487136-33			
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H290 H302 H314 H318					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Quantity	
	Specific Conc. Limits, M-factors and ATE		
67-56-1	200-659-6	85 - < 90 %	
	inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10		
1310-58-3	215-181-3	potassium hydroxide	1 - < 5 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 3 of 14

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.

After contact with eyes

After eye contact: Rinse immediately carefully and thoroughly with eye-bath or water. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

After ingestion

Provide fresh air. Do not allow a neutralisation agent to be drunk. Call a physician immediately. Notes for the doctor : Methanol

4.2. Most important symptoms and effects, both acute and delayed

corrosive, Irritant, Dizziness, Dizziness Anaesthetic state, Agitation, Spasms Inebriation, Vomiting, Headache Impairment of vision, Dyspnoea, Cough Repeated exposure may cause skin dryness or cracking. Risk of serious damage to eyes. Circulatory collapse, Corneal opacity.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor : Methanol

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2) Foam Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture


Combustible liquids

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide, Carbon monoxide

Beware of reignition.





according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 4 of 14

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Wear full chemical protective clothing.

In case of fire and/or explosion do not breathe fumes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Take action to prevent static discharges. Corrosive to metals.

Conosive to metals.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 5 of 14

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid exposure - obtain special instructions before use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Unsuitable container/equipment material: Aluminium, tin, zinc

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances. national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

storage temperature +15°C - +25°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
67-56-1	Methyl alcohol	200	260		TWA (8 h)	
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 6 of 14

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

DNEL/DMEL values

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
67-56-1	methanol					
Consumer DN	EL, acute	inhalation	systemic	50 mg/m³		
Worker DNEL,	long-term	inhalation	systemic	260 mg/m³		
Worker DNEL,	acute	inhalation	systemic	260 mg/m³		
Worker DNEL,	long-term	inhalation	local	260 mg/m³		
Worker DNEL,	acute	inhalation	local	260 mg/m³		
Worker DNEL,	long-term	dermal	systemic	40 mg/kg bw/day		
Worker DNEL,	acute	dermal	systemic	40 mg/kg bw/day		
Consumer DN	EL, long-term	inhalation	systemic	50 mg/m³		
Consumer DN	EL, long-term	inhalation	local	50 mg/m³		
Consumer DN	EL, acute	inhalation	local	50 mg/m³		
Consumer DN	EL, long-term	dermal	systemic	8 mg/kg bw/day		
Consumer DN	EL, acute	dermal	systemic	8 mg/kg bw/day		
Consumer DN	EL, long-term	oral	systemic	8 mg/kg bw/day		
Consumer DN	EL, acute	oral	systemic	8 mg/kg bw/day		
1310-58-3	1310-58-3 potassium hydroxide					
Worker DNEL,	long-term	inhalation	local	1 mg/m³		
Consumer DN	EL, long-term	inhalation	local	1 mg/m³		

PNEC values

CAS No	Substance			
Environmen	Environmental compartment			
67-56-1	methanol			
Freshwater 2				
Freshwater	1540 mg/l			
Marine wate	r	2,08 mg/l		
Freshwater	sediment	77 mg/kg		
Marine sedi	7,7 mg/kg			
Micro-organ	isms in sewage treatment plants (STP)	100 mg/l		
Soil		100 mg/kg		

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 7 of 14

Eye/face protection

goggles

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Recommended glove articles KCL 897 Butoject® Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Recommended glove articles KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols. The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Methanol	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and		~64 °C
boiling range:		
Flammability:		not applicable
Lower explosion limits:		5,5 vol. %



according to Regulation (EC) No 1907/2006

Potassium h	ydroxide 0.5 mol/l in methanol	
Revision date: 10.03.2025	Product code: 05069	Page 8 of 14
Upper explosion limits:	44 vol. %	
Flash point:	~11 °C	
Auto-ignition temperature:	455 °C	
Decomposition temperature:	not determined	
pH-Value:	alkaline	
Viscosity / kinematic:	not determined	
Water solubility:	Soluble in: Water	
Solubility in other solvents		
not determined		
Dissolution rate:	No data available	
Partition coefficient n-octanol/water:	not determined	
Dispersion stability: Vapour pressure:	No data available No data available	
Vapour pressure:	No data available	
Density:	0,8442 g/cm ³	
Relative density:	No data available	
Bulk density:	No data available	
Relative vapour density:	not determined	
Particle characteristics:	No data available	
9.2. Other information		
Information with regard to physical hazard classes Explosive properties Vapours can form explosive mixtures with air.	s	
Sustaining combustion:	Sustaining combustion	
Self-ignition temperature		
Solid:	not applicable	
Gas: Oxidizing properties	not applicable	
not determined		
Other safety characteristics		
Evaporation rate:	not determined	
Solvent separation test:	not determined	
Solvent content:	No data available	
Solid content:	not determined	
Sublimation point:	No data available	
Softening point:	No data available	
Pour point:	No data available	
No data available:		
Viscosity / dynamic:	No data available	
Flow time:	not determined	
Further Information		
May be corrosive to metals.		
SECTION 10: Stability and reactivity		

10.1. Reactivity

Highly flammable. Vapours can form explosive mixtures with air. May be corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 9 of 14

Oxidising agent, Hydrogen peroxide, Acid halides Reducing agent, Acid, Alkaline earth metal, Alkali metals

Risk of explosion with: Oxidizing agents, perchloric acid, perchlorates, salts of oxyhalogenic acids, chromium(VI) oxide, halogen oxides, nitrogen oxides, nonmetallic oxides, chromosulfuric acid, chlorates, hydrides, zinc diethyl, halogens, powdered magnesium, hydrogen peroxide, Nitric acid, sulphuric acid, permanganic acid, sodium hypochlorite Exothermic reaction with: acid halides, Acid anhydrides, Reducing agents, acids, Bromine, Chlorine, Chloroform, magnesium, tetrachloromethane, CYANURIC CHLORIDE Risk of ignition or formation of inflammable gases or vapours with: Fluorine, Oxides of phosphorus, Raney-nickel Generates dangerous gases or fumes in contact with: Alkaline earth metals, Alkali metals

10.4. Conditions to avoid

Vapours can form explosive mixtures with air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles Glass metals (including their alloys)

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects). Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract. Resorption (oral) Resorption (by inhalation) Resorption (dermal)

ATEmix calculated

ATE (oral) 115,4 mg/kg; ATE (dermal) 354,4 mg/kg; ATE (inhalation vapour) 3,540 mg/l; ATE (inhalation dust/mist) 0,5910 mg/l



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 10 of 14

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
67-56-1	methanol						
	oral	LD50 mg/kg	6000	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t	
	dermal	ATE mg/kg	300				
	inhalation (4 h) vapour	LC50 mg/l	128,2	Rat	Study report (1980)	Study performed according to internal co	
	inhalation dust/mist	ATE	0,5 mg/l				
1310-58-3	potassium hydroxide						
	oral	LD50 mg/kg	333	Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425	

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage. Serious eye damage/eye irritation: Causes serious eye damage.

Corneal opacity.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol) eyes Liver and kidney damage Irreversible damage to the optic nerve.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

corrosive, Irritant, Dizziness, Dizziness Anaesthetic state, Agitation, Spasms Inebriation, Vomiting, Headache Impairment of vision, Dyspnoea, Cough



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 11 of 14

Repeated exposure may cause skin dryness or cracking. Risk of serious damage to eyes. Circulatory collapse, Corneal opacity.

Further information

Do not empty into drains. Discharge into the environment must be avoided. The substance has delayed effects. Other dangerous properties cannot be excluded.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
67-56-1	methanol							
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975	
	Acute algae toxicity	ErC50 22000 mg/l	ca.	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11	
	Fish toxicity	NOEC mg/l	446,7	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR	
	Crustacea toxicity	NOEC	208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-56-1	methanol	-0,77
BCF		

CAS No	Chemical name	BCF	Species	Source
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the mixture itself.



Potassium hydroxide 0.5 mol/l in methanol

according to Regulation (EC) No 1907/2006

Revision date: 10.03.2025

Product code: 05069

Page 12 of 14

Further information

Do not allow to enter into surface water or drains. Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not allow to enter into surface water or drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste. Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

Land transport (ADK/KID)	
14.1. UN number or ID number:	UN 3286
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol,
	potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	ll
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	368
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 3286
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol,
	potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	ll
Hazard label:	3+6.1+8
Classification code:	FTC
Special Provisions:	274 802
Limited quantity:	1 L
Excepted quantity:	E2
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 3286
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol,
	potassium hydroxide)
14.3. Transport hazard class(es):	3
14.4. Packing group:	ll
Hazard label:	3+6.1/8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol			
Revision date: 10.03.2025	Product code: 05069	Page 13 of 14	
EmS:	F-E, S-C		
Air transport (ICAO-TI/IATA-DGR)			
14.1. UN number or ID number:	UN 3286		
14.2. UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (methanol,		
	potassium hydroxide)		
14.3. Transport hazard class(es):	3		
14.4. Packing group:			
Hazard label:	3+6.1 8		
Limited quantity Passenger:	0.5 L		
Passenger LQ:	Y340		
Excepted quantity: IATA-packing instructions - Passenger:	E2 352		
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	302 1 L		
IATA-nax. quality - Tassenger. IATA-packing instructions - Cargo:	363		
IATA-max. quantity - Cargo:	5 L		
14.5. Environmental hazards	02		
ENVIRONMENTALLY HAZARDOUS:	Νο		
	INU		
14.6. Special precautions for user Warning: Combustible liquid. Toxic.			
14.7. Maritime transport in bulk according to	MO instruments		
) MO Instruments		
not applicable			
SECTION 15: Regulatory information			
15.1. Safety, health and environmental regul	ations/legislation specific for the substance or mixture		
EU regulatory information			
Restrictions on use (REACH, annex XVII):			
Entry 3, Entry 40, Entry 69, Entry 75			
Information according to Directive	H2 ACUTE TOXIC		
2012/18/EU (SEVESO III):			
Additional information:	P5c		
National regulatory information			
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juve work protection guideline' (94/33/EC). Observe employment restriction under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.		
Water hazard class (D):	2 - obviously hazardous to water		
Skin resorption/Sensitization:	Permeates easily through outer skin and causes poisoning.		

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9.



according to Regulation (EC) No 1907/2006

Potassium hydroxide 0.5 mol/l in methanol

Revision date: 10.03.2025

Product code: 05069

Page 14 of 14

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals Flam. Lig: Flammable liquid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage STOT SE: Specific target organ toxicity - single exposure ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration. 50% LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H311	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Corr. 1B; H314	
Eye Dam. 1; H318	Calculation method
STOT SE 1; H370	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H301+H311+H331	Toxic if swallowed, in contact with skin or if inhaled.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H370	Causes damage to organs (eyes, central nervous system).
H370	Causes damage to organs.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)