



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H**

Revision date: 26.06.2024

Product code: 05244

Page 2 of 13

**Pictograms:**



**Hazard statements**

- H290 May be corrosive to metals.
- H314 Causes severe skin burns and eye damage.
- H410 Very toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7664-93-9	sulphuric acid			90 - < 95 %
	231-639-5	016-020-00-8	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318			
10294-26-5	disilver(1+) sulphate			1 - < 5 %
	233-653-7			
	Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H318 H400 H410			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
7664-93-9	231-639-5	sulphuric acid	90 - < 95 %
	oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15		
10294-26-5	233-653-7	disilver(1+) sulphate	1 - < 5 %
	oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=1000 Aquatic Chronic 1; H410: M=100		

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H

Revision date: 26.06.2024

Product code: 05244

Page 3 of 13

#### 4.1. Description of first aid measures

##### **General information**

First aider: Pay attention to self-protection!

##### **After inhalation**

Provide fresh air.

Call a physician immediately.

##### **After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

##### **After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

##### **After ingestion**

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

#### 4.2. Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes.

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Gastric perforation

Nausea

Abdominal pain

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

##### **Unsuitable extinguishing media**

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Sulphur oxides

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Avoid contact with skin, eyes and clothes.

##### **Additional information**

Use water spray jet to protect personnel and to cool endangered containers.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H

Revision date: 26.06.2024

Product code: 05244

Page 4 of 13

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Corrosive to metals.

#### For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

No special fire protection measures are necessary.

#### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take

a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe

vapour/aerosol.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H**

Revision date: 26.06.2024

Product code: 05244

Page 5 of 13

**Further information on handling**

- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.
- Take off immediately all contaminated clothing and wash it before reuse.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

- Keep container tightly closed.
- Unsuitable container/equipment material: Metal
- Protect against: Light

**Further information on storage conditions**

- Corrosive to metals.
- storage temperature: +15°C - +25°C

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
7664-93-9	Sulphuric acid	-	0.05		TWA (8 h)	

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
7664-93-9	sulphuric acid			
	Worker DNEL, long-term	inhalation	local	0,05 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	local	0,1 mg/m <sup>3</sup>

**PNEC values**

CAS No	Substance	Environmental compartment	Value
7664-93-9	sulphuric acid		
	Freshwater		0,003 mg/l
	Marine water		0 mg/l
	Freshwater sediment		0,002 mg/kg
	Marine sediment		0,002 mg/kg
	Micro-organisms in sewage treatment plants (STP)		8,8 mg/l
10294-26-5	disilver(1+) sulphate		
	Freshwater		0,00004 mg/l
	Marine water		0,00086 mg/l
	Freshwater sediment		438,13 mg/kg
	Marine sediment		438,13 mg/kg
	Micro-organisms in sewage treatment plants (STP)		0,025 mg/l
	Soil		0,794 mg/kg

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H

Revision date: 26.06.2024

Product code: 05244

Page 6 of 13

#### 8.2. Exposure controls

##### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

Suitable eye protection:

goggles

Face protection shield

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®

Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm

Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

##### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

##### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:

Liquid

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H**

Revision date: 26.06.2024

Product code: 05244

Page 7 of 13

Colour:	colourless	
Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		X
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		0
Viscosity / kinematic:		No data available
Water solubility:		very soluble (Heat)
Solubility in other solvents		No data available
No data available		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		No data available
Vapour pressure:		No data available
Density:		1,8952 g/cm <sup>3</sup>
Bulk density:		No data available
Relative vapour density:		No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	No data available
Gas:	No data available
Oxidizing properties	
No data available	

**Other safety characteristics**

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

**Further Information**

Corrosive to metals.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Corrosive to metals.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H**

Revision date: 26.06.2024

Product code: 05244

Page 8 of 13

**10.2. Chemical stability**

Protect against: Light

**10.3. Possibility of hazardous reactions**

Violent reaction with:  
Water, Alkali metals, Ammonia  
aldehydes, Alkaline earth metal, Acids  
Alkali (lye), Metal,  
Phosphorus oxides, Combustible substance  
Solvent, Aniline, permanganates, e.g. potassium permanganate  
Peroxides, Amines, Carbide  
peroxides, for example hydrogen peroxide , Nitriles

**10.4. Conditions to avoid**

No data available

**10.5. Incompatible materials**

Metal  
Cellulose

**10.6. Hazardous decomposition products**

In case of fire may be liberated:  
SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.  
If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).  
Irritation to respiratory tract (Cough, Dyspnoea)

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7664-93-9	sulphuric acid				
	oral	LD50 mg/kg 2140	Rat	Am Ind Hyg Assoc J. 1969 Sep-Oct; 30(5):	The study was performed as part of a ser
10294-26-5	disilver(1+) sulphate				
	oral	LD50 mg/kg > 2000	Rat	Study report (1993)	OECD Guideline 401

**Irritation and corrosivity**

Skin corrosion/irritation: Causes severe skin burns and eye damage.  
Serious eye damage/eye irritation: Causes serious eye damage.  
Risk of serious damage to eyes.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H

Revision date: 26.06.2024

Product code: 05244

Page 9 of 13

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

#### Practical experience

There are no data available on the mixture itself.

#### 11.2. Information on other hazards

##### Other information

There are no data available on the mixture itself.

##### Further information

Risk of serious damage to eyes.

Causes burns.

Irritant

Cough

Dyspnoea

Vomiting

Gastric perforation

Nausea

Abdominal pain

## SECTION 12: Ecological information

### 12.1. Toxicity

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H**

Revision date: 26.06.2024

Product code: 05244

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
7664-93-9	sulphuric acid					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2009)	OECD Guideline 202
	Fish toxicity	NOEC 0,025 mg/l	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977	Groups of sexually mature flagfish
10294-26-5	disilver(1+) sulphate					
	Acute fish toxicity	LC50 0,0012 mg/l	96 h	Pimephales promelas	Environmental Toxicology and Chemistry 2	A guideline was not specified. The test
	Acute crustacea toxicity	EC50 0,00022 mg/l	48 h	Daphnia magna	Environmental Toxicology and Chemistry 2	48-hour static renewal toxicity tests. A
	Fish toxicity	NOEC > 0,00125 mg/l	73 d	Oncorhynchus mykiss	Environmental Toxicology and Chemistry 2	other: ASTM 1241-98
	Algae toxicity	NOEC 0,0012 mg/l	14 d	Champia parvula	in Bishop WE, Cardwell RD Heidolph BB (E	The toxicity tests lasted 11 days for th
	Crustacea toxicity	NOEC 0,001 mg/l	7 d	Ceriodaphnia reticulata	Publication (1986)	other: 7 day semi-static chronic toxicit

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**BCF**

CAS No	Chemical name	BCF	Species	Source
10294-26-5	disilver(1+) sulphate	70	Cyprinus carpio	Water, Air and Soil

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H**

Revision date: 26.06.2024

Product code: 05244

Page 11 of 13

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not mix with other wastes.  
Do not allow to enter into surface water or drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 3264
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid, disilver(1+) sulphate)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 3264
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid, disilver(1+) sulphate)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 3264
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid, disilver(1+) sulphate)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 3264
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid, disilver(1+) sulphate)
<b>14.3. Transport hazard class(es):</b>	8

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H**

Revision date: 26.06.2024

Product code: 05244

Page 12 of 13

<b>14.4. Packing group:</b>	II	
Hazard label:	8	
Special Provisions:	A3 A803	
Limited quantity Passenger:	0.5 L	
Passenger LQ:	Y840	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		851
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		855
IATA-max. quantity - Cargo:		30 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	disilver(1+) sulphate

**14.6. Special precautions for user**

Warning: strongly corrosive.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 3 - highly hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,12.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Silver sulfate sulfuric acid 80 g Ag<sub>2</sub>SO<sub>4</sub>/l in H<sub>2</sub>SO<sub>4</sub> 96 % for COD determination DIN 38409:1981, DEV H**

Revision date: 26.06.2024

Product code: 05244

Page 13 of 13

**Abbreviations and acronyms**

- Met. Corr: Substance or mixture corrosive to metals
- Skin Corr: Skin corrosion
- Eye Dam: Eye damage
- Aquatic Acute: Acute aquatic hazard
- Aquatic Chronic: Chronic aquatic hazard
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service
- LC50: Lethal concentration, 50%
- LD50: Lethal dose, 50%

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

**Relevant H and EUH statements (number and full text)**

- H290 May be corrosive to metals.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*