

according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 1 of 12

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Petroleum benzine 50/70 °C pure

EC No: 265-151-9

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

## Further Information

This product is a mixture. REACH Registration Number see section 3.

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Repr. 2; H361f STOT SE 3; H336 STOT RE 2; H373 Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

# 2.2. Label elements

## Regulation (EC) No 1272/2008

## Hazard components for labelling

Naphtha (petroleum), hydrotreated light

n-hexane

Signal word: Danger



according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 2 of 12

## Pictograms:









#### **Hazard statements**

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

## **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P403+P235 Store in a well-ventilated place. Keep cool.

#### 2.3. Other hazards

No data available

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No	1272/2008)		
64742-49-0	Naphtha (petroleum), hydrotreated light			75 - < 80 %
	265-151-9	649-328-00-1	01-2119474679-18	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
110-54-3	n-hexane			25 - < 30 %
	203-777-6	203-777-6 601-037-00-0 01-2119480412-44		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc. L	pecific Conc. Limits, M-factors and ATE			
110-54-3	203-777-6	n-hexane	25 - < 30 %		
	inhalation: LC50 = 73860 mg/l (vapours); dermal: LD50 = > 2000 mg/kg STOT RE 2; H373: >= 5 - 100				

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).



according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 3 of 12

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

### **General information**

No data available

#### After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Vapours may cause drowsiness and dizziness.

Gastrointestinal complaints

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Carbon dioxide (CO2)

Foam

Extinguishing powder

Water spray jet

## Unsuitable extinguishing media

Full water jet

# 5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO2) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

## 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

## Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.



according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 4 of 12

Use water spray jet to protect personnel and to cool endangered containers.

#### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

## For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

**Emergency procedures** 

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

### For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

## 6.3. Methods and material for containment and cleaning up

## For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

## For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

## Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Avoid exposure - obtain special instructions before use.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation. Do not breathe vapour.



according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 5 of 12

### Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

## Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints on joint storage

national regulations

### Further information on storage conditions

Keep container tightly closed and dry.

Keep cool. Protect from sunlight.

### 7.3. Specific end use(s)

Laboratory chemicals

### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
110-54-3	n-Hexane	20	72		TWA (8 h)	

## **Biological limit values**

CAS No	Substance	Parameter	Value	Test material	Sampling time
110-54-3	Hexane	2,5-Hexanedion	0.4 mg/L		End of shift at end of workweek

## **DNEL/DMEL values**

CAS No	Substance					
DNEL type		Exposure route	Effect	Value		
110-54-3	n-hexane					
Worker DNEL,	long-term	dermal	systemic	11 mg/kg bw/day		
Consumer DNEL, long-term		inhalation	systemic	16 mg/m³		
Consumer DNEL, long-term		dermal	systemic	5,3 mg/kg bw/day		
Consumer DNEL, long-term		oral	systemic	4 mg/kg bw/day		
Worker DNEL, long-term		inhalation	systemic	75 mg/m³		

### 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection



according to Regulation (EC) No 1907/2006

## Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 6 of 12

equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

#### Eye/face protection

goggles

Face protection umbrella

## Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®
Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 730 Camatril® Velours Suitable material: NBR (Nitrile rubber) 0,4 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

# **Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: like: Gasoline

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

50-70 °C

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

7,5 vol. %

Flash point:

Auto-ignition temperature:

No data available



according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 7 of 12

Decomposition temperature:

pH-Value:

No data available

No data available

Viscosity / kinematic:

No data available

Water solubility:

No data available

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

Vapour pressure:

No data available

Vapour pressure:

No data available

Density:

0,66 g/cm³

Bulk density:

No data available

Relative vapour density:

No data available

### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

### Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available Solvent content: No data available Solid content: No data available Sublimation point: No data available No data available Softening point: Pour point: No data available No data available Viscosity / dynamic: No data available Flow time: No data available

#### **Further Information**

No data available

## **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

Vapours may form explosive mixtures with air.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Oxidising agent

## 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## 10.5. Incompatible materials

Plastic articles

Rubber articles



according to Regulation (EC) No 1907/2006

## Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 8 of 12

### 10.6. Hazardous decomposition products

**SECTION 5: Firefighting measures** 

#### **Further information**

No data available

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### ATFmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
110-54-3	n-hexane							
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1982)			
	inhalation (4 h) vapour	LC50 mg/l	73860		Industrial Medicine, Vol. 39, No. 5, May	OECD Guideline 403		

#### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

## Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging fertility. (n-hexane)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum), hydrotreated light; n-hexane)

Organs affected: central nervous system

# STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (n-hexane)

## **Aspiration hazard**

May be fatal if swallowed and enters airways.

## Specific effects in experiment on an animal

No data available

## Additional information on tests

No data available

## **Practical experience**

No data available

# 11.2. Information on other hazards

#### Other information

Avoid exposure - obtain special instructions before use.

#### **Further information**

Irritant



according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 9 of 12

Vapours may cause drowsiness and dizziness.

Gastrointestinal complaints

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
110-54-3	n-hexane						
	Acute algae toxicity	ErC50 mg/l	9,285	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50 mg/l	21,85	48 h	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Fish toxicity	NOEC	2,8 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	4,888	21 d	Daphnia magna	CONCAWE, Brussels, Belgium (2009)	The aquatic toxicity was estimated by a

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
110-54-3	n-hexane	4

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
110-54-3	n-hexane	501,187	Pimephales promelas	QSAR in Environmenta

## 12.4. Mobility in soil

There are no data available on the mixture itself.

## 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

#### **Further information**

No data available

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

## **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.



according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 10 of 12

Send to a physico-chemical treatment facility under observation of official regulations.

### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number or ID number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 3 Classification code: F1 Special Provisions: 640D Limited quantity: 1 I Excepted quantity: F2 Transport category: 2 Hazard No: 33 Tunnel restriction code: D/E

### Inland waterways transport (ADN)

14.1. UN number or ID number: UN 3295

**14.2. UN proper shipping name:** HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Classification code:F1Special Provisions:640DLimited quantity:1 LExcepted quantity:E2

## Marine transport (IMDG)

14.1. UN number or ID number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-E. S-D

#### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3295

14.2. UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3Special Provisions:A3 A324Limited quantity Passenger:1 LPassenger LQ:Y341Excepted quantity:E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364



according to Regulation (EC) No 1907/2006

Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 11 of 12

IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: n-hexane

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive

E2 Hazardous to the Aquatic Environment

2012/18/EU (SEVESO III):

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

### **SECTION 16: Other information**

## Changes

This data sheet contains changes from the previous version in section(s): 12.

# Abbreviations and acronyms

Flam. Liq: Flammable liquid Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

## Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Repr. 2; H361f	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

# Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Print date: 29.01.2025



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Petroleum benzine 50/70 °C pure

Revision date: 29.01.2025 Product code: 07080 Page 12 of 12

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)