

Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%)for viscosity determination according to DIN 53727

Revision date: 06.02.2024

Product code: 07257

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%) for viscosity determination according to DIN 53727

REACH Registration Number:	01-2119458838-20-XXXX
CAS No:	7664-93-9
Index No:	016-020-00-8
EC No:	231-639-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	
1.4. Emergency telephone	For Hazardous Materials [or Danger	ous Goods] Incidents Spill, Leak, Fire,
number:	Exposure, or Accident Call CHEMT	REC Day or Night Within USA and Canada:
	1-800-424-9300 Outside USA and C	Canada: +1 703-741-5970 (collect calls
	accepted)	

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Met. Corr. 1; H290 Skin Corr. 1A; H314 Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Signal word: Pictograms: Danger





Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%) for viscosity determination according to **DIN 53727** Revision date: 06.02.2024 Product code: 07257 Page 2 of 11 Hazard statements H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. **Precautionary statements** P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 IF exposed or concerned: Immediately call a POISON CENTER/doctor. P310

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula:	H2SO4
Molecular weight:	98,08 g/mol

Relevant ingredients

CAS No	Chemical name				
	EC No				
	Classification (GB CLP Regulation)				
7664-93-9	sulphuric acid				
	231-639-5 016-020-00-8 01-2119458838-20-XXXX				
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc. L	cific Conc. Limits, M-factors and ATE				
7664-93-9	231-639-5	sulphuric acid	95 - < 100 %			
	oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15					

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

Provide fresh air. Call a physician immediately.

After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. Call a physician immediately.



Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%)for viscosity determination according to DIN 53727

Revision date: 06.02.2024

Product code: 07257

Page 3 of 11

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

4.2. Most important symptoms and effects, both acute and delayed

Risk of serious damage to eyes. Causes burns. Irritant Cough Dyspnoea Vomiting Gastric perforation Nausea Abdominal pain

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids Hazardous combustion products In case of fire may be liberated: Sulphur oxides

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Avoid contact with skin, eyes and clothes.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes and clothes. Remove persons to safety. Emergency procedures



Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%)for viscosity determination according to DIN 53727

Revision date: 06.02.2024

Product code: 07257

Page 4 of 11

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers). Collect in closed and suitable containers for disposal. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Use personal protection equipment. Use extractor hood (laboratory). Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Unsuitable container/equipment material: Metal

Hints on joint storage

national regulations



Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%)for viscosity determination according to

Revision date: 06.02.2024

DIN 53727

Product code: 07257

Page 5 of 11

Further information on storage conditions

Corrosive to metals.

The product develops hydrogen in an aqueous solution in contact with metals.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
7664-93-9	Sulphuric acid (mist)	-	0.05		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	-					
DNEL type		Exposure route	Effect	Value			
7664-93-9	sulphuric acid						
Worker DNEL, long-term inhalation local 0,05 mg/m ³							
Worker DNEL, acute inhalation local 0,1 mg/m³							

PNEC values

CAS No	Substance				
Environmental compartment Value					
7664-93-9 sulphuric acid					
Freshwater 0,003 mg/l					
Marine water 0 mg/l					
Freshwater sediment 0,002 m					
Marine sedime	0,002 mg/kg				
Micro-organisms in sewage treatment plants (STP) 8,8 mg/l					

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles Face protection shield

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Suitable examples are gloves of KCL GmbH, D-36124 Eichenzell, e-mail: vertrieb@kcl.de with the following



Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%) for viscosity determination according to

DIN 53727

Revision date: 06.02.2024

Product code: 07257

Page 6 of 11

specification (test according to EN 374):

By long-term hand contact Trade name/designation KCL 890 Vitoject® Recommended material: FKM (fluoro rubber) 0,7 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Trade name/designation KCL 720 Camapren® Recommended material: CR (polychloroprene, chloroprene rubber) 0,65 mm Wearing time with occasional contact (splashes): > 60 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing. Wash hands before breaks and after work.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation Filtering device with filter or ventilator filtering device of type: ABEK

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid	
Odour:	odourless	
Melting point/freezing point:	ououness	-20 °C
Boiling point or initial boiling point and		-20°C 335 °C
boiling range:		333 8
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		x
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value (at 20 °C):		0
Viscosity / kinematic:		No data available
Water solubility:		very soluble (Heat)
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:		No data available
Vapour pressure:		0,0001 hPa
(at 20 °C)		
Vapour pressure:		0,004 hPa
(at 50 °C)		



Revision date: 06.02.2024	DIN 53727 Product code: 07257	Page 7 of 11
Revision date: 00.02.2024		i age / 0i i i
Density:	~1,84 g/cm³	
Bulk density:	No data available	
Relative vapour density:	3,4	
9.2. Other information		
Information with regard to physical ha	azard classes	
Explosive properties		
No data available		
Sustaining combustion:	No data available	
Self-ignition temperature		
Solid:	No data available	
Gas:	No data available	
Oxidizing properties No data available		
Other safety characteristics		
Evaporation rate:	No data available	
Solvent separation test:	No data available	
Solvent content:	No data available	
Solid content:	No data available No data available	
Sublimation point: Softening point:	No data available	
Pour point:	No data available	
No data available:		
Viscosity / dynamic:	24 mPa⋅s	
(at 20 °C)		
Flow time:	No data available	
Further Information		
No data available		

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals. Oxidising agent, strong

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Violent reaction with: Water, Alkali metals, Ammonia aldehydes, Alkaline earth metal, Acids Alkali (lye), Metal, Phosphorus oxides, Combustible substance Solvent, Aniline, permanganates, e.g. potassium permanganate Peroxides, Amines, Carbide peroxides, for example hydrogen peroxide , Nitriles

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Metal

The product develops hydrogen in an aqueous solution in contact with metals. Cellulose



Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%) for viscosity determination according to

DIN 53727

Revision date: 06.02.2024

Product code: 07257

Page 8 of 11

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Irritation to respiratory tract (Cough, Dyspnoea)

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

Other dangerous properties can not be excluded.

CAS No	Chemical name									
	Exposure route Dose Species Source Method									
7664-93-9	sulphuric acid									
	oral	LD50 mg/kg	2140		1969 Sep-Oct; 30(5):	The study was performed as part of a ser				

Irritation and corrosivity

Causes severe skin burns and eye damage. Causes serious eye damage. Risk of serious damage to eyes.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Other information No data available

Further information

Risk of serious damage to eyes. Causes burns. Irritant



Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%) for viscosity determination according to

Revision date: 06.02.2024

DIN 53727 Product code: 07257

Page 9 of 11

Cough Dyspnoea Vomiting Gastric perforation Nausea Abdominal pain

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name								
	Aquatic toxicity	Dose	Dose		Species	Source	Method		
7664-93-9	sulphuric acid								
	Acute algae toxicity	ErC50 mg/l	> 100		Desmodesmus subspicatus	Study report (2009)	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2009)	OECD Guideline 202		
	Fish toxicity	NOEC mg/l	0,025	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977	Groups of sexually mature flagfish		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of UK REACH.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment. Harmful effect due to pH shift. Forms corrosive mixtures with water even if diluted.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not mix with other wastes.

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information



Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%)for viscosity determination according to DIN 53727			
Revision date: 06.02.2024	Product co	ode: 07257	Page 10 of 11
Land transport (ADR/RID) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label: Classification code: Limited quantity: Excepted quantity: Transport category: Hazard No:	UN 1830 SULPHURIC ACID 8 II 8 C1 1 L E2 2 80		
Tunnel restriction code:	E		
Inland waterways transport (ADN) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u> <u>14.3. Transport hazard class(es):</u> <u>14.4. Packing group:</u> Hazard label: Classification code: Limited quantity: Excepted quantity:	UN 1830 Sulphuric acid 8 II 8 C1 1 L E2		
Marine transport (IMDG)	E2		
14.1. UN number or ID number: 14.2. UN proper shipping name: 14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: Special Provisions: Limited quantity: Excepted quantity: EmS:	UN 1830 Sulphuric acid 8 II 8 - 1 L E2 F-A, S-B		
Air transport (ICAO-TI/IATA-DGR) <u>14.1. UN number or ID number:</u> <u>14.2. UN proper shipping name:</u>	UN 1830 SULPHURIC ACID		
14.3. Transport hazard class(es):14.4. Packing group:Hazard label:Limited quantity Passenger:Passenger LQ:Excepted quantity:IATA-packing instructions - Passenger:IATA-max. quantity - Passenger:IATA-packing instructions - Cargo:IATA-max. quantity - Cargo:	8 II 8 0.5 L Y840 E2	851 1 L 855 30 L	
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS: <u>14.6. Special precautions for user</u> Warning: strongly corrosive. <u>14.7. Maritime transport in bulk according t</u> not applicable	No o IMO instruments		



Sulphuric acid 96.00 % (Accuracy: 95.90% - 96.10%) for viscosity determination according to

Revision date: 06.02.2024

DIN 53727

Product code: 07257

Page 11 of 11

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

Acquisition, introduction, possession or use of this product by the general public is restricted by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions:

Water hazard class (D):

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9.

Abbreviations and acronyms

Met. Corr: Corrosive to metals Skin Corr: Skin corrosion Eye Dam: Eye damage ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration. 50% LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

- H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H318
 - Causes serious eye damage.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users