

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Vorlagelösung für die Chloridtitration

UFI: XHDX-T0VR-6006-UJA5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemical

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290
Flam. Liq. 2; H225
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetone

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 2 of 13

Hazard statements

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P390	Absorb spillage to prevent material damage.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-64-1	acetone			45 - < 50 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
7697-37-2	nitric acid			1 - < 5 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A, Eye Dam. 1; H272 H290 H331 H314 H318 EUH071			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-64-1	200-662-2	acetone	45 - < 50 %
		dermal: LD50 = > 7426 mg/kg; oral: LD50 = 5800 mg/kg	
7697-37-2	231-714-2	nitric acid	1 - < 5 %
		inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 3 of 13

After inhalation

Provide fresh air.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant, Dizziness, Anaesthetic state
Vomiting, Headache, Dizziness
Gastrointestinal complaints, Corneal opacity.
Has degreasing effect on the skin.
Repeated exposure may cause skin dryness or cracking.
May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂).
Foam.
Extinguishing powder

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquid.
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Hazardous combustion products
In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide
Beware of reignition.

5.3. Advice for firefighters

Remove persons to safety. Do not inhale explosion and combustion gases.
Avoid contact with skin, eyes and clothes.
In case of fire: Wear self-contained breathing apparatus.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Additional information

Danger of bursting container.
Use water spray jet to protect personnel and to cool endangered containers.
Suppress gases/vapours/mists with water spray jet.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 4 of 13

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 5 of 13

Advice on general occupational hygiene

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Keep away from food, drink and animal feedingstuffs.

Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

storage temperature: +5°C - +30°C

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

Protect against: Light

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-64-1	acetone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m ³
Worker DNEL, acute		inhalation	local	2420 mg/m ³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m ³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
67-64-1	acetone	
Freshwater		10,6 mg/l
Freshwater (intermittent releases)		21 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe vapour/aerosol.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 7 of 13

carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	fruity	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		55 °C
Flammability:		not applicable
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		-5 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		No data available
Water solubility:		very soluble
Solubility in other solvents		No data available
Vapour pressure:		No data available
Density:		0,9403 g/cm ³
Bulk density:		No data available
Relative vapour density:		No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours can form explosive mixtures with air.

Sustaining combustion:

Sustaining combustion

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	0
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Flow time:	No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 8 of 13

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.
Vapours can form explosive mixtures with air.

10.2. Chemical stability

Protect against:
Light
Air

10.3. Possibility of hazardous reactions

Ignition hazard:
Fluorine, Oxidising agent, strong; chromium trioxide
Reducing agent, strong; Nitric acid
Danger of explosion:
Chloroform, peroxides, for example hydrogen peroxide
Exothermic reaction with:
Bromine, Alkali metals
Hydrogen halide, Sulphur dichloride

10.4. Conditions to avoid

Heat
Light
Air

10.5. Incompatible materials

Rubber articles
Plastic articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.
Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone				
	oral	LD50 5800 mg/kg	Rat	J Toxicol Environ Health 15: 609-621 (19)	Undiluted acetone applied to female rats
	dermal	LD50 > 7426 mg/kg	Rabbit	Toxicol Appl Pharmacol 7: 559-565. (1965)	other: Code of federal regulations: 21 C
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.
 Serious eye damage/eye irritation: Causes serious eye irritation.
 Has degreasing effect on the skin.
 Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.
 Carcinogenicity: Based on available data, the classification criteria are not met.
 Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Other information

There are no data available on the mixture itself.

Further information

Irritant, Dizziness, Anaesthetic state
 Vomiting, Headache, Dizziness
 Gastrointestinal complaints, Corneal opacity.
 Has degreasing effect on the skin.
 Repeated exposure may cause skin dryness or cracking.
 May cause drowsiness or dizziness.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone					
	Acute fish toxicity	LC50 mg/l	8120	96 h	Pimephales promelas	Publication (1984) OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia pulex	Publication (1978) The toxicity of acetone towards daphnids
	Crustacea toxicity	NOEC mg/l	2212	28 d	Daphnia magna	Arch Environm Contam Toxicol 12: 305-310 Study conducted comparable to OECD 211 w
	Acute bacteria toxicity	EC50 mg/l ()	61150	0,5 h	activated sludge of a predominantly domestic sewage	Water Res 26: 887-892 (1992) ISO 8192
7697-37-2	nitric acid					
	Acute fish toxicity	LC50 mg/l	1559	96 h	Topeka shiner	Environmental Toxicology and Chemistry, other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009) Growth tests estimated the test chemical
	Algae toxicity	NOEC mg/l	> 419	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977) Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50 mg/l ()	> 1000	3 h	Activated sludge	Study report (2008) OECD Guideline 209

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone	-0,23

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone	3		Unpublished calculat

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 11 of 13

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (acetone, nitric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (acetone, nitric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (acetone, Nitric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (acetone, Nitric acid)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Special Provisions:	A3
Limited quantity Passenger:	0.5 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 12 of 13

Passenger LQ:	Y340	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		352
IATA-max. quantity - Passenger:		1 L
IATA-packing instructions - Cargo:		363
IATA-max. quantity - Cargo:		5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Additional information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 9,12,15.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Vorlagelösung für die Chloridtitration

Revision date: 06.03.2025

Product code: 10617

Page 13 of 13

Abbreviations and acronyms

Ox. Liq: Oxidising liquid
 Met. Corr: Substance or mixture corrosive to metals
 Flam. Liq: Flammable liquid
 Acute Tox: Acute toxicity
 Skin Corr: Skin corrosion
 Skin Irrit: Skin irritation
 Eye Dam: Eye damage
 Eye Irrit: Eye irritation
 STOT SE: Specific target organ toxicity - single exposure
 ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
 H272 May intensify fire; oxidiser.
 H290 May be corrosive to metals.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.
 EUH071 Corrosive to the respiratory tract.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)