

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l**

Revision date: 26.06.2024

Product code: 10770

Page 1 of 13

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l

UFI: CPTX-80GG-100W-2SG1

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet**

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

**1.4. Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

**Further Information**

This product is a mixture. REACH Registration Number see section 3.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Met. Corr. 1; H290

Skin Irrit. 2; H315

Eye Irrit. 2; H319

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Signal word:** Warning**Pictograms:****Hazard statements**

H290 May be corrosive to metals.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l**

Revision date: 26.06.2024

Product code: 10770

Page 2 of 13

**Precautionary statements**

- P280 Wear protective gloves and eye protection/face protection.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Chemical characterization**

Mixtures in aqueous solution

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7647-01-0	Hydrochloric acid			5 - < 10 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Skin Corr. 1B, STOT SE 3; H314 H335			
7697-37-2	nitric acid			1 - < 5 %
	231-714-2	007-030-00-3	01-2119487297-23	
	Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071			
7446-08-4	selenium dioxide			< 1 %
	231-194-7	034-002-00-8		
	Acute Tox. 3, Acute Tox. 3, STOT RE 2, Aquatic Acute 1, Aquatic Chronic 1; H331 H301 H373 H400 H410			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
7647-01-0	231-595-7	Hydrochloric acid	5 - < 10 %
	Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100		
7697-37-2	231-714-2	nitric acid	1 - < 5 %
	inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20		
7446-08-4	231-194-7	selenium dioxide	< 1 %
	inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: LD50 = 68,1 mg/kg		

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l

Revision date: 26.06.2024

Product code: 10770

Page 3 of 13

#### After inhalation

Provide fresh air.  
Call a doctor if you feel unwell.

#### After contact with skin

Wash immediately with: Water  
Take off immediately all contaminated clothing and wash it before reuse.  
In case of skin irritation, consult a physician.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.  
Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Rinse mouth immediately and drink plenty of water.  
Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage  
Cough  
Dyspnoea

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

#### Unsuitable extinguishing media

no restriction

### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids  
Hazardous combustion products  
In case of fire may be liberated:  
Hydrochloric gas

### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.  
Avoid contact with skin, eyes and clothes.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Use water spray jet to protect personnel and to cool endangered containers.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Corrosive to metals.

#### For non-emergency personnel

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Consult an expert

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l

Revision date: 26.06.2024

Product code: 10770

Page 4 of 13

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

##### For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Usual measures for fire prevention.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

#### Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed.

Provide adequate ventilation as well as local exhaust at critical locations.

Keep in a cool place.

#### Further information on storage conditions

Unsuitable container/equipment material: Metal  
storage temperature: +2°C - +25°C.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l**

Revision date: 26.06.2024

Product code: 10770

Page 5 of 13

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	
7697-37-2	Nitric acid	1	2.6		STEL (15 min)	

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
7647-01-0	Hydrochloric acid			
	Worker DNEL, long-term	inhalation	local	8 mg/m <sup>3</sup>
	Worker DNEL, acute	inhalation	local	15 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	local	8 mg/m <sup>3</sup>
	Consumer DNEL, acute	inhalation	local	15 mg/m <sup>3</sup>
7446-08-4	selenium dioxide			
	Worker DNEL, long-term	inhalation	systemic	0,07 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	9,8 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,021 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	6,02 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,00602 mg/kg bw/day

**PNEC values**

CAS No	Substance	Value
	Environmental compartment	
7446-08-4	selenium dioxide	
	Freshwater	0,00374 mg/l
	Freshwater (intermittent releases)	0,0077 mg/l
	Marine water	0,0028 mg/l
	Freshwater sediment	11,48 mg/kg
	Marine sediment	8,68 mg/kg
	Secondary poisoning	1,4 mg/kg
	Micro-organisms in sewage treatment plants (STP)	10 mg/l
	Soil	0,06 mg/kg

**8.2. Exposure controls**

**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l**

Revision date: 26.06.2024

Product code: 10770

Page 6 of 13

gas/fumes/vapour/spray.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Suitable eye protection:  
Face protection shield  
goggles.

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 741 Dermatril® L  
Recommended material: NBR (Nitrile rubber) 0,11 mm  
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 741 Dermatril® L  
Recommended material: NBR (Nitrile rubber) 0,11 mm  
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Wear suitable protective clothing.  
Protective clothing acid-resistant

**Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation  
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	stinging	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		not applicable

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l

Revision date: 26.06.2024

Product code: 10770

Page 7 of 13

Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	X
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value (at 20 °C):	<1
Viscosity / kinematic:	No data available
Water solubility:	easily soluble
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density (at 20 °C):	1,052 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	No data available

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

No data available

##### Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

0

Solid content:

0

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

##### Further Information

Corrosive to metals

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Corrosive to metals.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

### 10.3. Possibility of hazardous reactions

Exothermic reaction with: Amines, permanganates, e.g. potassium permanganate, aldehydes

Ignition hazard: Carbide, Fluorine

Possibility of hazardous reactions: Aluminium, Formaldehyde, Metal, Alkali (lye)

Danger of explosion: Alkali metals, Sulphuric acid, concentrated

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l

Revision date: 26.06.2024

Product code: 10770

Page 8 of 13

#### 10.4. Conditions to avoid

Heat

#### 10.5. Incompatible materials

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

#### Further information

No data available

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

##### Acute toxicity

Based on available data, the classification criteria are not met.

Pulmonary oedema

##### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7697-37-2	nitric acid				
	inhalation vapour	ATE 2,65 mg/l			
7446-08-4	selenium dioxide				
	oral	LD50 68,1 mg/kg	Rat	Indian Journal of Pharmacology 23(3):153	Method not specified GLP compliance: not
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			

##### Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

##### Sensitising effects

Based on available data, the classification criteria are not met.

##### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

##### STOT-single exposure

Based on available data, the classification criteria are not met.

##### STOT-repeated exposure

Based on available data, the classification criteria are not met.

##### Aspiration hazard

Based on available data, the classification criteria are not met.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l

Revision date: 26.06.2024

Product code: 10770

Page 9 of 13

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.

#### Additional information on tests

There are no data available on the mixture itself.

#### Practical experience

There are no data available on the mixture itself.

#### 11.2. Information on other hazards

##### Other information

There are no data available on the mixture itself.

##### Further information

Irritant — skin irritation and eye damage

Cough

Dyspnoea

### SECTION 12: Ecological information

#### 12.1. Toxicity

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l**

Revision date: 26.06.2024

Product code: 10770

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
7647-01-0	Hydrochloric acid					
	Acute fish toxicity	LC50	862 mg/l	96 h	Leuciscus idus	
7697-37-2	nitric acid					
	Acute fish toxicity	LC50	1559 mg/l	96 h	Topeka shiner	Environmental Toxicology and Chemistry, other: ASTM E729-26
	Fish toxicity	NOEC	268 mg/l	30 d	juvenile Topeka shiner and with juvenile Fathead m	Study report (2009) Growth tests estimated the test chemical
	Algae toxicity	NOEC	> 419 mg/l	10 d	several benthic diatoms; see results	Marine Biology 43:307-315 (1977) Ten cultures of benthic diatoms were iso
	Acute bacteria toxicity	EC50	> 1000 mg/l ( )	3 h	Activated sludge	Study report (2008) OECD Guideline 209
7446-08-4	selenium dioxide					
	Acute fish toxicity	LC50	3,3 mg/l	96 h	Morone saxatilis	Publication (1992) other: ASTM methods for acute testing
	Acute algae toxicity	ErC50	44,24 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1992) OECD Guideline 201
	Acute crustacea toxicity	EC50	0,55 mg/l	48 h	Daphnia magna	Environmental Toxicology and Chemistry 1 other: EPA-660/3-75-009: Methods for Acu
	Fish toxicity	NOEC	0,01 mg/l	258 d	Lepomis macrochirus	Environmental Toxicology and Chemistry 1 Year long study investigating the effect
	Algae toxicity	NOEC	0,995 mg/l	10 d	Anabaena flos-aquae	Archives of Environmental Contamination 10-d experiment on the toxicity of selen
	Crustacea toxicity	NOEC	0,07 mg/l	28 d	Daphnia magna	Department of Entomology, Fisheries and OECD Guideline 211
	Acute bacteria toxicity	EC50	> 3200 mg/l ( )	3 h	activated sludge of a predominantly domestic sewage	Study report (2012) OECD Guideline 209

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**BCF**

CAS No	Chemical name	BCF	Species	Source
7446-08-4	selenium dioxide	755	periphyton	Environmental Pollut

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

**Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l**

Revision date: 26.06.2024

Product code: 10770

Page 11 of 13

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Discharge into the environment must be avoided.

**Further information**

Do not empty into drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1789
<b>14.2. UN proper shipping name:</b>	HYDROCHLORIC ACID
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C1
Special Provisions:	520
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1789
<b>14.2. UN proper shipping name:</b>	HYDROCHLORIC ACID
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Classification code:	C1
Special Provisions:	520
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1789
<b>14.2. UN proper shipping name:</b>	HYDROCHLORIC ACID
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l

Revision date: 26.06.2024

Product code: 10770

Page 12 of 13

EmS: F-A, S-B

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number or ID number:</b>	UN 1789
<b>14.2. UN proper shipping name:</b>	HYDROCHLORIC ACID
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### SECTION 16: Other information

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,8,9,12.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Multielement-Standardlösung 2 2 Elemente je 1000mg/l in HCl etwa 3 mol/l

Revision date: 26.06.2024

Product code: 10770

Page 13 of 13

#### Abbreviations and acronyms

Ox. Liq: Oxidising liquid  
 Met. Corr: Substance or mixture corrosive to metals  
 Acute Tox: Acute toxicity  
 Skin Corr: Skin corrosion  
 Skin Irrit: Skin irritation  
 Eye Irrit: Eye irritation  
 STOT SE: Specific target organ toxicity - single exposure  
 STOT RE: Specific target organ toxicity - repeated exposure  
 Aquatic Acute: Acute aquatic hazard  
 Aquatic Chronic: Chronic aquatic hazard  
 ADR: Accord européen sur le transport des marchandises dangereuses par Route  
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service  
 LC50: Lethal concentration, 50%  
 LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method

#### Relevant H and EUH statements (number and full text)

H272 May intensify fire; oxidiser.  
 H290 May be corrosive to metals.  
 H301 Toxic if swallowed.  
 H314 Causes severe skin burns and eye damage.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H331 Toxic if inhaled.  
 H335 May cause respiratory irritation.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 EUH071 Corrosive to the respiratory tract.

#### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Provide appropriate information, instructions and training to users

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*