

Pt/Co standard compari	son Color number (Hazen) 100 - EN ISO 6271	Hazen Color Standard according to			
Revision date: 19.03.2025	Product code: 12360	Page 1 of	10		
SECTION 1: Identification of the s	ubstance/mixture and of the comp	any/undertaking			
UFI:	or number (Hazen) 100 - Hazen Color S 1573-01XP-100S-UK0M ubstance or mixture and uses advised				
Use of the substance/mixture Laboratory chemicals Industrial uses: Uses of substar	Laboratory chemicals Industrial uses: Uses of substances as such or in preparations at industrial sites Professional uses: Public domain (administration, education, entertainment, services, craftsmen)				
Do not use for private purposes	(household).				
<u>1.3. Details of the supplier of the safe</u> Company name: Street: Place:	ty data sheet AnalytiChem GmbH ACD Stempelstraße 6 D-47167 Duisburg				
Telephone: E-mail: Contact person: E-mail: Internet: Responsible Department:	0203/5194-0 info@analytichem.de Abteilung Produktsicherheit produktsicherheit@analytichem.de www.analytichem.de Abteilung Produktsicherheit	Telefax: 0203/5194-290 Telephone: 0203/5194-107/117			
<u>1.4. Emergency telephone</u> <u>number:</u> Further Information	For Hazardous Materials [or Dangerou Exposure, or Accident Call CHEMTRE 1-800-424-9300 Outside USA and Ca accepted)	C Day or Night Within USA and Canada:			
	CH Registration Number see section 3.				

# **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Regulation (EC) No 1272/2008 Met. Corr. 1; H290

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

## Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



# Hazard statements

H290

May be corrosive to metals.

#### Precautionary statements P234

Keep only in original packaging.



Pt/Co standard	comparison Color number (Hazen) 100 - Hazen Color Standard accordi EN ISO 6271	ng to
Revision date: 19.03.2025	Product code: 12360	Page 2 of 10
P390 P406	Absorb spillage to prevent material damage. Store in a corrosion-resistant container with a resistant inner liner.	

#### Special labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

No data available

#### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Chemical characterization

Mixtures in aqueous solution

#### **Relevant ingredients**

CAS No	Chemical name		Quantity	
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7647-01-0	Hydrochloric acid		1 - < 5 %	
	231-595-7	017-002-01-X	01-2119484862-27	
	Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, STOT SE 3; H290 H314 H318 H335			

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
7647-01-0	231-595-7	Hydrochloric acid	1 - < 5 %
Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100			

#### **Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### General information

No data available

#### After inhalation

Provide fresh air. Call a doctor if you feel unwell.

#### After contact with skin

Wash immediately with: Water Take off immediately all contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

## After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

#### After ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately.



# Pt/Co standard comparison Color number (Hazen) 100 - Hazen Color Standard according to

Revision date: 19.03.2025

EN ISO 6271..

Product code: 12360

Page 3 of 10

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant Allergic reactions

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

# Unsuitable extinguishing media

no restriction

#### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids Hazardous combustion products In case of fire may be liberated: Hydrochloric gas Metal oxide smoke, toxic

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. Avoid contact with skin, eyes and clothes.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

### For non-emergency personnel

Provide adequate ventilation.

- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

#### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

#### 6.3. Methods and material for containment and cleaning up

#### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

#### Other information

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Wear breathing apparatus if exposed to vapours/dusts/aerosols.



# Pt/Co standard comparison Color number (Hazen) 100 - Hazen Color Standard according to

EN ISO 6271..

Revision date: 19.03.2025

Product code: 12360

Page 4 of 10

# 6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Read label before use. Handle and open container with care. When using do not eat, drink, smoke, sniff. Keep container tightly closed. Use personal protection equipment. Use extractor hood (laboratory). Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Usual measures for fire prevention.

#### Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

#### Further information on handling

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Take off immediately all contaminated clothing and wash it before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

#### Hints on joint storage

national regulations

#### Further information on storage conditions

Unsuitable container/equipment material: Metal

### 7.3. Specific end use(s)

Laboratory chemicals

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### **Occupational exposure limits**

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	



# Pt/Co standard comparison Color number (Hazen) 100 - Hazen Color Standard according to EN ISO 6271..

Revision date: 19.03.2025

Product code: 12360

Page 5 of 10

#### **DNEL/DMEL** values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
7647-01-0 Hydrochloric acid			-	
Worker DNEL, long-term		inhalation	local	8 mg/m³
Worker DNEL, acute		inhalation	local	15 mg/m³
Consumer DNEL, long-term		inhalation	local	8 mg/m³
Consumer DNEL, acute		inhalation	local	15 mg/m³

#### 8.2. Exposure controls

#### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

#### Individual protection measures, such as personal protective equipment

# Eye/face protection

Suitable eye protection: Face protection shield goggles.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

#### Skin protection

Wear suitable protective clothing. Protective clothing acid-resistant

#### **Respiratory protection**

Respiratory protection necessary at: aerosol or mist formation The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are



# Pt/Co standard comparison Color number (Hazen) 100 - Hazen Color Standard according to

Revision date: 19.03.2025

EN ISO 6271.. Product code: 12360

Page 6 of 10

carried out according to the instructions of the producer. These measures have to be properly documented.

### Environmental exposure controls

Do not allow to enter into surface water or drains.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

المتبينية ا	
Liquid	
yellow	
ououness	No data available
	No data available
	not applicable
	No data available
	No data available
	X
	No data available
	No data available
	acidic
	No data available
	No data available
	No data available
	No data available
	No data available
	1,00299 g/cm <sup>3</sup>
	No data available
	No data available
zard classes	not applicable
zard classes	not applicable not applicable
zard classes	
zard classes	not applicable
zard classes	not applicable No data available
zard classes	not applicable No data available No data available
zard classes	not applicable No data available No data available No data available
zard classes	not applicable No data available No data available No data available No data available
zard classes	not applicable No data available No data available No data available No data available No data available
zard classes	not applicable No data available No data available No data available No data available No data available No data available
zard classes	not applicable No data available No data available No data available No data available No data available No data available
zard classes	not applicable No data available No data available No data available No data available No data available No data available No data available
	odourless



# Pt/Co standard comparison Color number (Hazen) 100 - Hazen Color Standard according to

Revision date: 19.03.2025

EN ISO 6271.. Product code: 12360

Page 7 of 10

Corrosive to metals

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Corrosive to metals.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.4. Conditions to avoid

Heat

#### 10.5. Incompatible materials

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

#### Further information

No data available

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

#### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met. slightly irritant but not relevant for classification.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Specific effects in experiment on an animal

There are no data available on the mixture itself.



Pt/	Pt/Co standard comparison Color number (Hazen) 100 - Hazen Color Standard according to EN ISO 6271				
Revision dat	e: 19.03.2025		Product code: 12360		Page 8 of 10
,	Additional information on tests There are no data available on the mixture itself.				
	<b>experience</b> e are no data available o	n the mixture itsel	f.		
11.2. Informa	ation on other hazards				
	Other information There are no data available on the mixture itself.				
Further info					
<b>SECTION 1</b>	2: Ecological inform	ation			
12.1. Toxicity					
Based on available data, the classification criteria are not met.					
CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d] Species	Source	Method

96 h Leuciscus idus

#### 12.2. Persistence and degradability

Hydrochloric acid Acute fish toxicity

There are no data available on the mixture itself.

LC50

#### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

#### 12.4. Mobility in soil

7647-01-0

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

862 mg/l

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

Discharge into the environment must be avoided.

Harmful effect due to pH shift.

Forms corrosive mixtures with water even if diluted.

# Further information

Do not empty into drains.

#### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### **Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Send to a physico-chemical treatment facility under observation of official regulations. Do not empty into drains.

# Contaminated packaging

Handle contaminated packages in the same way as the substance itself. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.



# Pt/Co standard comparison Color number (Hazen) 100 - Hazen Color Standard according to

Revision date: 19.03.2025

EN ISO 6271..

Product code: 12360

Page 9 of 10

# **SECTION 14: Transport information**

Land transport (ADR/RID)	
14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	111
Hazard label:	8
Classification code:	C1
Special Provisions:	520
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C1
Special Provisions:	520
Limited quantity:	5 L
Excepted quantity:	E1
Marine transport (IMDG)	
14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	111
Hazard label:	8
Special Provisions:	223
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L
14.5. Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	No



# Pt/Co standard comparison Color number (Hazen) 100 - Hazen Color Standard according to

Revision date: 19.03.2025

EN ISO 6271.. Product code: 12360

Page 10 of 10

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information	
Restrictions on use (REACH, annex XVII):	
Entry 75	
Information according to Directive 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)
National regulatory information	
Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	non-hazardous to water

# **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 9,12.

#### Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals

Skin Corr: Skin corrosion

Eye Dam: Eye damage

STOT SE: Specific target organ toxicity - single exposure ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50% LD50: Lethal dose, 50%

#### Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data

#### Relevant H and EUH statements (number and full text)

H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.

H335 May cause respiratory irritation.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)