



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891

Revision date: 21.03.2024

Product code: 12501

Page 2 of 10

P406

Store in a corrosion-resistant container with a resistant inner liner.

#### 2.3. Other hazards

No data available

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Mixtures in aqueous solution

##### Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7664-93-9	sulphuric acid			1 - < 5 %
	231-639-5	016-020-00-8	01-2119458838-20	
	Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1; H290 H314 H318			

Full text of H and EUH statements: see section 16.

##### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
7664-93-9	231-639-5	sulphuric acid	1 - < 5 %
	oral: LD50 = 2140 mg/kg Skin Corr. 1A; H314: >= 15 - 100 Skin Irrit. 2; H315: >= 5 - < 15 Eye Irrit. 2; H319: >= 5 - < 15		

##### Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

No data available

##### After inhalation

Provide fresh air.

##### After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

##### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

##### After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritant

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891

Revision date: 21.03.2024

Product code: 12501

Page 3 of 10

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

###### **Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

###### **Unsuitable extinguishing media**

no restriction

##### 5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Sulphur oxides

##### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

###### **Additional information**

Suppress gases/vapours/mists with water spray jet.

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

###### **General advice**

Corrosive to metals.

###### **For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

###### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

##### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

##### 6.3. Methods and material for containment and cleaning up

###### **For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

###### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

###### **Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

##### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891**

Revision date: 21.03.2024

Product code: 12501

Page 4 of 10

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

Read label before use.

**Advice on protection against fire and explosion**

Usual measures for fire prevention.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

**Further information on handling**

Draw up and observe skin protection programme.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Take off immediately all contaminated clothing and wash it before reuse.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Corrosive to metals.  
Unsuitable container/equipment material: Metal, Light metal  
The product develops hydrogen in an aqueous solution in contact with metals.

**Further information on storage conditions**

Keep container tightly closed.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
7664-93-9	Sulphuric acid	-	0.05		TWA (8 h)	

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
7664-93-9	sulphuric acid			
Worker DNEL, long-term		inhalation	local	0,05 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	local	0,1 mg/m <sup>3</sup>

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891

Revision date: 21.03.2024

Product code: 12501

Page 5 of 10

#### PNEC values

CAS No	Substance	Value
Environmental compartment		
7664-93-9	sulphuric acid	
Freshwater		0,003 mg/l
Marine water		0 mg/l
Freshwater sediment		0,002 mg/kg
Marine sediment		0,002 mg/kg
Micro-organisms in sewage treatment plants (STP)		8,8 mg/l

#### 8.2. Exposure controls

##### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

##### Individual protection measures, such as personal protective equipment

##### Eye/face protection

goggles

Wear eye/face protection.

##### Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

##### Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

##### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:

Liquid

Colour:

colourless

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891**

Revision date: 21.03.2024

Product code: 12501

Page 6 of 10

Odour:	odourless	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		<1
Viscosity / kinematic:		No data available
Water solubility:		completely miscible
Solubility in other solvents		No data available
Dissolution rate:		No data available
Partition coefficient n-octanol/water:		No data available
Dispersion stability:		No data available
Vapour pressure:		No data available
Density:		1,0226 g/cm <sup>3</sup>
Relative density:		No data available
Bulk density:		No data available
Relative vapour density:		No data available
Particle characteristics:		No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	No data available
Gas:	No data available
Oxidizing properties	
No data available	

**Other safety characteristics**

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

**Further Information**

Corrosive to metals.

**SECTION 10: Stability and reactivity**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891

Revision date: 21.03.2024

Product code: 12501

Page 7 of 10

#### 10.1. Reactivity

Corrosive to metals.

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.4. Conditions to avoid

No data available

#### 10.5. Incompatible materials

Cellulose

Metal

The product develops hydrogen in an aqueous solution in contact with metals.

#### 10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

#### Further information

No data available

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

##### Acute toxicity

Based on available data, the classification criteria are not met.

##### ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7664-93-9	sulphuric acid				
	oral	LD50 mg/kg	2140	Rat	Am Ind Hyg Assoc J. 1969 Sep-Oct; 30(5): The study was performed as part of a ser

##### Irritation and corrosivity

Based on available data, the classification criteria are not met.

##### Sensitising effects

Based on available data, the classification criteria are not met.

##### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

##### STOT-single exposure

Based on available data, the classification criteria are not met.

##### STOT-repeated exposure

Based on available data, the classification criteria are not met.

##### Aspiration hazard

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891**

Revision date: 21.03.2024

Product code: 12501

Page 8 of 10

**Information on likely routes of exposure**

There are no data available on the preparation/mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the preparation/mixture itself.

**Additional information on tests**

There are no data available on the preparation/mixture itself.

**Practical experience**

There are no data available on the preparation/mixture itself.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

There are no data available on the preparation/mixture itself.

**Other information**

There are no data available on the preparation/mixture itself.

**Further information**

There are no data available on the preparation/mixture itself.

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
7664-93-9	sulphuric acid					
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Desmodesmus subspicatus	Study report (2009) OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2009) OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,025	65 d	Jordanella floridae	Water Research Vol. 11, 612 - 626, 1977 Groups of sexually mature flagfish

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Discharge into the environment must be avoided.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891**

Revision date: 21.03.2024

Product code: 12501

Page 9 of 10

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not empty into drains.

**Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 3264
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 3264
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Classification code:	C1
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 3264
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 3264
<b>14.2. UN proper shipping name:</b>	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (sulphuric acid)
<b>14.3. Transport hazard class(es):</b>	8
<b>14.4. Packing group:</b>	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulfuric acid R1 for determination of silicate with Polymetron Silkostat 8891**

Revision date: 21.03.2024

Product code: 12501

Page 10 of 10

IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,12.

**Abbreviations and acronyms**

Met. Corr: Substance or mixture corrosive to metals

Skin Corr: Skin corrosion

Eye Dam: Eye damage

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data

**Relevant H and EUH statements (number and full text)**

H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*