

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin

Revision date: 21.03.2024

Product code: 12749

Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin

UFI: EK94-W1F3-6009-4CPQ

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

###### Uses advised against

Do not use for private purposes (household).

##### 1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

##### 1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

##### Further Information

This product is a mixture. REACH Registration Number see section 3.

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

##### 2.2. Label elements

###### Regulation (EC) No 1272/2008

###### Hazard components for labelling

White mineral oil, petroleum

Signal word: Danger

###### Pictograms:



###### Hazard statements

H304 May be fatal if swallowed and enters airways.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin

Revision date: 21.03.2024

Product code: 12749

Page 2 of 10

**Precautionary statements**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P405 Store locked up.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
8042-47-5	White mineral oil, petroleum	95 - < 100 %		
	232-455-8			
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
8042-47-5	232-455-8	White mineral oil, petroleum	95 - < 100 %	
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg			

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

No data available

**After inhalation**

Provide fresh air.

**After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water.

**After ingestion**

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Gastrointestinal complaints

Pneumonia

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin

Revision date: 21.03.2024

Product code: 12749

Page 3 of 10

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Foam  
Carbon dioxide (CO<sub>2</sub>)  
Extinguishing powder  
Water

##### **Unsuitable extinguishing media**

no restriction

#### **5.2. Special hazards arising from the substance or mixture**

Combustible liquids  
Hazardous combustion products  
In case of fire may be liberated:  
Carbon dioxide (CO<sub>2</sub>), Carbon monoxide  
In case of warming:  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.

#### **5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

#### **Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Use water spray jet to protect personnel and to cool endangered containers.

## **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

##### **For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Do not breathe dust/fume/gas/mist/vapours/spray.

##### **For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### **6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

#### **6.3. Methods and material for containment and cleaning up**

##### **For containment**

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### **For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

##### **Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin**

Revision date: 21.03.2024

Product code: 12749

Page 4 of 10

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**Advice on safe handling**

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment.
- Do not breathe vapour/aerosol.
- Provide adequate ventilation.

**Advice on protection against fire and explosion**

- Usual measures for fire prevention.
- In case of warming:  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.

**Advice on general occupational hygiene**

- Keep away from food, drink and animal feedingstuffs.

**Further information on handling**

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.

**7.2. Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

- Store in a well-ventilated place.
- Keep container tightly closed.

**Hints on joint storage**

- No data available

**Further information on storage conditions**

- Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

- Laboratory chemicals

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
8042-47-5	White mineral oil, petroleum			
Worker DNEL, long-term		inhalation	systemic	160 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	220 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	35 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	93 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	40 mg/kg bw/day

**8.2. Exposure controls**

**Appropriate engineering controls**

- Technical measures and the application of suitable work processes have priority over personal protection equipment.

- If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin

Revision date: 21.03.2024

Product code: 12749

Page 5 of 10

#### Eye/face protection

goggles  
Face protection umbrella

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®  
Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm  
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 897 Butoject®  
Recommended material: Butyl caoutchouc (butyl rubber) 0,3 mm  
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

#### Skin protection

Take off immediately all contaminated clothing and wash it before reuse.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Draw up and observe skin protection programme.

#### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available
Upper explosion limits:		No data available
Flash point:		No data available
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin**

Revision date: 21.03.2024

Product code: 12749

Page 6 of 10

pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available

**9.2. Other information**

**Information with regard to physical hazard classes**

**Explosive properties**

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

**Other safety characteristics**

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

In case of warming:

Vapours may form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Violent reaction with: Oxidising agent

Explosion hazard with:

Nitrates

Chlorates

Perchlorates

**10.4. Conditions to avoid**

Heat

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin**

Revision date: 21.03.2024

Product code: 12749

Page 7 of 10

**10.5. Incompatible materials**

No data available

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
8042-47-5	White mineral oil, petroleum				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards**

**Other information**

There are no data available on the mixture itself.

**Further information**

Gastrointestinal complaints  
Pneumonia

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin**

Revision date: 21.03.2024

Product code: 12749

Page 8 of 10

Pulmonary oedema

**SECTION 12: Ecological information**

**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
8042-47-5	White mineral oil, petroleum					
	Acute fish toxicity	LC50 mg/l	> 10000	96 h	Lepomis macrochirus	REACH Registration Dossier
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (2008)
						Method: other: procedure as detailed in OECD Guideline 202

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
8042-47-5	White mineral oil, petroleum	> 6

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not allow to enter into surface water or drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information**

**Land transport (ADR/RID)**

**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:**

No dangerous good in sense of this transport regulation.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin**

Revision date: 21.03.2024

Product code: 12749

Page 9 of 10

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Marine transport (IMDG)**

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

No dangerous good in sense of this transport regulation.

**14.7. Maritime transport in bulk according to IMO instruments**

No dangerous good in sense of this transport regulation.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

**SECTION 16: Other information**

**Changes**

This data sheet contains changes from the previous version in section(s): 1,12.

**Abbreviations and acronyms**

Asp. Tox: Aspiration hazard

**Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]**

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

**Relevant H and EUH statements (number and full text)**

H304 May be fatal if swallowed and enters airways.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Sulphur standard solution 500 mg S/kg Dibutyl sulfide in thin paraffin

Revision date: 21.03.2024

Product code: 12749

Page 10 of 10

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*