

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

UFI: F9G5-Q2JC-J00A-9HJF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Repr. 2; H361d
STOT SE 3; H336
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

toluene
propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 2 of 13

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	Index No
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
108-88-3	toluene	50 - < 55 %
	203-625-9	601-021-00-3
		01-2119471310-51
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	45 - < 50 %
	200-661-7	603-117-00-0
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	50 - < 55 %
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 3 of 13

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage, Headache

Dizziness, Dizziness

Vomiting, Inebriation

Spasms, Circulatory collapse

Respiratory complaints, Dyspnoea

Unconsciousness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam.

Extinguishing powder

Carbon dioxide (CO₂)

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Beware of reignition.

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 4 of 13

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 5 of 13

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Draw up and observe skin protection programme.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in a cool, well-ventilated place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	
108-88-3	Toluene	50	192		TWA (8 h)	
		100	384		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
108-88-3	Toluene	Toluene	0.02 mg/L	Blood	Prior to last shift of workweek
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 6 of 13

DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
108-88-3	toluene		
Worker DNEL, long-term	inhalation	systemic	192 mg/m ³
Worker DNEL, acute	inhalation	systemic	384 mg/m ³
Worker DNEL, long-term	inhalation	local	192 mg/m ³
Worker DNEL, acute	inhalation	local	384 mg/m ³
Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m ³
Consumer DNEL, acute	inhalation	systemic	226 mg/m ³
Consumer DNEL, long-term	inhalation	local	56,5 mg/m ³
Consumer DNEL, acute	inhalation	local	226 mg/m ³
Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Worker DNEL, long-term	inhalation	systemic	500 mg/m ³
Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³
Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day

PNEC values

CAS No	Substance	
Environmental compartment	Value	
108-88-3	toluene	
Freshwater	0,68 mg/l	
Freshwater (intermittent releases)	0,68 mg/l	
Marine water	0,68 mg/l	
Freshwater sediment	16,39 mg/kg	
Marine sediment	16,39 mg/kg	
Micro-organisms in sewage treatment plants (STP)	13,61 mg/l	
Soil	2,89 mg/kg	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater	140,9 mg/l	
Freshwater (intermittent releases)	140,9 mg/l	
Marine water	140,9 mg/l	
Freshwater sediment	552 mg/kg	
Marine sediment	552 mg/kg	
Secondary poisoning	160 mg/kg	
Micro-organisms in sewage treatment plants (STP)	2251 mg/l	
Soil	28 mg/kg	

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 7 of 13

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		~ 82 °C
Flammability:		No data available
Lower explosion limits:		No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 8 of 13

Upper explosion limits:	No data available
Flash point:	~ 6 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

Viscosity / dynamic: No data available

Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 9 of 13

Nitric acid
Acetic acid
Strong acid

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Plastic articles
Rubber articles

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 > 5000 mg/kg	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.
Serious eye damage/eye irritation: Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (toluene; propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

There are no data available on the mixture itself.

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 10 of 13

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

Irritant — skin irritation and eye damage, Headache
Dizziness, Dizziness
Vomiting, Inebriation
Spasms, Circulatory collapse
Respiratory complaints, Dyspnoea
Unconsciousness

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 mg/l > 433	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 mg/l 11,5	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC mg/l 1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC mg/l > 400	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC mg/l 0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (other: US EPA 600/4-91-003
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l 10000	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 11 of 13

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol; isopropanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1993
--------------------------------------	---------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 12 of 13

14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol; isopropyl alcohol; isopropanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (toluene, propan-2-ol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 48

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

Information according to Directive 2012/18/EU (SEVESO III):

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D):

3 - highly hazardous to water

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Solvent mixture for pH lubricating oil according to Fuchs Schmierstoffe GmbH

Revision date: 19.03.2024

Product code: 24370

Page 13 of 13

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9,11.

Abbreviations and acronyms

Flam. Liq: Flammable liquid

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Irrit: Eye irritation

Repr: Reproductive toxicity

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Repr. 2; H361d	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)