

according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH

ACD

Street: Stempelstraße 6
Place: D-47167 Duisburg

Telephone: 0203/5194-0 Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,

number: Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Flam. Liq. 3; H226

Acute Tox. 2; H310

Acute Tox. 3; H301

Acute Tox. 3: H331

Skin Corr. 1A; H314

Eye Dam. 1; H318

STOT RE 2; H373

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetic acid

mercury di(acetate)

Signal word: Danger



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 2 of 13

Pictograms:











Hazard statements

H226 Flammable liquid and vapour.
H290 May be corrosive to metals.
H301+H331 Toxic if swallowed or if inhaled.
H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P310 **2.3. Other hazards**

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulati	on (EC) No 1272/2008)	·	
64-19-7	acetic acid			90 - < 95 %
	200-580-7	607-002-00-6	01-2119475328-30	
	Flam. Liq. 3, Skin Corr.	1A; H226 H314		
1600-27-7	mercury di(acetate)			5 - < 10 %
	216-491-1	080-004-00-7		
	Acute Tox. 1, Acute To H330 H300 H373 H400	x. 2, Acute Tox. 2, STOT RE 2, Aquat H410	iic Acute 1, Aquatic Chronic 1; H310	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
64-19-7	200-580-7	acetic acid	90 - < 95 %
	I	50 = 11,4 mg/l (vapours); oral: LD50 = 3310 mg/kg	
1600-27-7	216-491-1	mercury di(acetate)	5 - < 10 %
	I	= 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: ATE : ATE = 5 mg/kg STOT RE 2; H373: >= 0,1 - 100	



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 3 of 13

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider

After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

corrosive

Dyspnoea

Gastrointestinal complaints

Vomiting

Circulatory collapse

Corneal opacity.

Risk of serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

mercury (Hg).

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 4 of 13

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 5 of 13

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place. Keep container tightly closed.

Store in a dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

storage temperature +15°C - +25°C

Store in a place accessible by authorized persons only.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	
		20	50		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Substance				
DNEL type		Exposure route	Effect	Value		
64-19-7	acetic acid					
Worker DNE	L, long-term	inhalation	local	25 mg/m³		
Worker DNEL, acute		inhalation	local	25 mg/m³		
Consumer DNEL, long-term		inhalation	local	25 mg/m³		
Consumer DNEL, acute		inhalation	local	25 mg/m³		



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 6 of 13

PNEC values

CAS No	Substance	
Environmen	tal compartment	Value
64-19-7	acetic acid	
Freshwater		3,058 mg/l
Freshwater	(intermittent releases)	30,58 mg/l
Marine water	r	0,306 mg/l
Freshwater sediment		11,36 mg/kg
Marine sediment		1,136 mg/kg
Micro-organ	isms in sewage treatment plants (STP)	85 mg/l
Soil		0,47 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eve/face protection

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 897 Butoject®

Suitable material: Butyl caoutchouc (butyl rubber) 0,3 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject® Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 90 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 7 of 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: clear
Odour: stinging

Odour threshold: No data available

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

No data available Flammability: Lower explosion limits: No data available Upper explosion limits: No data available ~39 °C Flash point: Auto-ignition temperature: No data available No data available Decomposition temperature: acidic pH-Value: Viscosity / kinematic: No data available Water solubility: No data available

Solubility in other solvents

No data available

Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available Density (at 20 °C): 1,0907 g/cm³ Relative density: No data available No data available Bulk density: No data available Relative vapour density: Particle characteristics: No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available Solvent separation test: No data available Solvent content: No data available Solid content: No data available Sublimation point: No data available Softening point: No data available Pour point: No data available No data available Viscosity / dynamic: No data available No data available Flow time:



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 8 of 13

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming: Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

peroxides, for example hydrogen peroxide

permanganates, e.g. potassium permanganate

Oxidising agent, strong

Metal

iron and steel

7inc

Alkali (lye)

aldehydes

Alcohols

Nitric acid

10.4. Conditions to avoid

storage temperature < 17 °C

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Metal

10.6. Hazardous decomposition products

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Fatal in contact with skin.

Toxic if swallowed.

Toxic if inhaled.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

ATEmix calculated

ATE (oral) 89,90 mg/kg; ATE (dermal) 89,90 mg/kg; ATE (inhalation vapour) 8,990 mg/l; ATE (inhalation dust/mist) 0,8990 mg/l



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 9 of 13

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64-19-7	acetic acid					
	oral	LD50 mg/kg	3310	Rat	J Ind Hyg Toxicol, Vol 23, PP 78-82 (194	The sodium salt of acetic acid was admin
	inhalation (4 h) vapour	LC50	11,4 mg/l	Rat	Study report (1980)	OECD Guideline 403
1600-27-7	mercury di(acetate)					
	oral	ATE	5 mg/kg			
	dermal	ATE	5 mg/kg			
	inhalation vapour	ATE	0,5 mg/l			
	inhalation dust/mist	ATE	0,05 mg/l			

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (mercury di(acetate))

Aspiration hazard

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

Irritant

corrosive

Dyspnoea

Gastrointestinal complaints

Vomiting

Circulatory collapse

Corneal opacity.

Risk of serious damage to eyes.

Further information

kidneys



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 10 of 13

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64-19-7	acetic acid						
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257
	Acute algae toxicity	ErC50 mg/l	> 1000		Skeletonema costatum	Study report (2005)	ISO 10253
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17

BCF

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

There are no data available on the mixture itself.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 11 of 13

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 2927

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (mercury di(acetate),

acetic acid)

6.1

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 6.1+8+3 Classification code: TC1 **Special Provisions:** 274 Limited quantity: 100 mL Excepted quantity: E4 Transport category: 2 Hazard No: 68 Tunnel restriction code: D/F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 2927

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (mercury di(acetate),

acetic acid)

6.1

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 6.1+8+3
Classification code: TC1
Special Provisions: 274 802
Limited quantity: 100 mL
Excepted quantity: E4

Marine transport (IMDG)

14.1. UN number or ID number: UN 2927

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (mercury di(acetate,

acetic acid)

6.1

14.3. Transport hazard class(es):

14.4. Packing group:

Hazard label: 6.1+8+3
Special Provisions: 274
Limited quantity: 100 mL
Excepted quantity: E4
EmS: F-A, S-B

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2927

14.2. UN proper shipping name: TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (mercury di(acetate,

acetic acid)

14.3. Transport hazard class(es): 6.1

14.4. Packing group:

Hazard label: 6.1+8+3
Special Provisions: A4 A137
Limited quantity Passenger: 0.5 L
Passenger LQ: Y640
Excepted quantity: E4

IATA-packing instructions - Passenger: 653
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 660
IATA-max. quantity - Cargo: 30 L



according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsäure

Revision date: 08.03.2024 Product code: 32743 Page 12 of 13

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

Danger releasing substance: mercury di(acetate)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 18, Entry 40

Information according to Directive

H2 ACUTE TOXIC

2012/18/EU (SEVESO III):

Additional information: P5c, E2

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 3 - highly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals

Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Skin Corr: Skin corrosion Eye Dam: Eye damage

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 2; H310	Calculation method
Acute Tox. 3; H301	Calculation method
Acute Tox. 3; H331	Calculation method
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.

H300 Fatal if swallowed. H301 Toxic if swallowed.

H301+H331 Toxic if swallowed or if inhaled.
H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

Print date: 08.03.2024



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Quecksilber(II)-acetat-Lösung 60 g/l zur Analyse in wasserfreier Essigsä	Quecksilber(I)-acetat-Lösund	g 60 g/l zur Anal	vse in wasserfreier Essigsäu
--	---------------	-----------------	-------------------	------------------------------

Revision date: 08.03.2024 Product code: 32743 Page 13 of 13

H330 Fatal if inhaled. H331 Toxic if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)