

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multiement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multiement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

UFI: DYK0-3328-400K-T27W

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	Fa. Bernd Kraft GmbH	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
e-mail:	info@berndkraft.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
e-mail:	produktsicherheit@berndkraft.de	
Internet:	www.berndkraft.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H290 May be corrosive to metals.

Precautionary statements

P234 Keep only in original packaging.
P390 Absorb spillage to prevent material damage.
P406 Store in a corrosion-resistant container with a resistant inner liner.

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 2 of 13

Special labelling of certain mixtures

EUH208 Contains nickel dichloride. May produce an allergic reaction.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7647-01-0	Hydrochloric acid			5 - < 10 %
	231-595-7	017-002-01-X	01-2119484862-27	
	Skin Corr. 1B, STOT SE 3; H314 H335			
1330-43-4	boric acid, disodium salt			< 1 %
	215-540-4	005-011-00-4	01-2119490790-32	
	Repr. 1B, Eye Irrit. 2; H360FD H319			
7718-54-9	nickel dichloride			< 0.1 %
	231-743-0	028-011-00-6		
	Carc. 1A, Muta. 2, Repr. 1B, Acute Tox. 3, Acute Tox. 3, Skin Irrit. 2, Resp. Sens. 1, Skin Sens. 1, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1; H350i H341 H360D H331 H301 H315 H334 H317 H372 H400 H410			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
7647-01-0	231-595-7	Hydrochloric acid	5 - < 10 %
		Skin Corr. 1B; H314: >= 25 - 100 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25 STOT SE 3; H335: >= 10 - 100	
1330-43-4	215-540-4	boric acid, disodium salt	< 1 %
		inhalation: LC50 = > 2,04 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2500 mg/kg	
7718-54-9	231-743-0	nickel dichloride	< 0.1 %
		inhalation: ATE = 3 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); oral: LD50 = 500 mg/kg Skin Irrit. 2; H315: >= 20 - 100 Skin Sens. 1; H317: >= 0,01 - 100 STOT RE 1; H372: >= 1 - 100 STOT RE 2; H373: >= 0,1 - < 1 M acute; H400: M=1 M chron.; H410: M=1	

Further Information

No data available

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 3 of 13

After inhalation

Provide fresh air.
Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant
Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Hydrochloric gas

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Do not breathe dust/fume/gas/mist/vapours/spray.

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 4 of 13

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use.

Handle and open container with care.

When using do not eat, drink, smoke, sniff.

Keep container tightly closed.

Use personal protection equipment.

Provide adequate ventilation.

Do not breathe vapour/aerosol.

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Further information on storage conditions

Unsuitable container/equipment material: Metal

storage temperature: +15°C - +25°C

7.3. Specific end use(s)

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 5 of 13

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
1330-43-4	Borate compounds inorganic: Borate (tetra) sodium anhydrous	-	2		TWA (8 h)	
7647-01-0	Hydrogen chloride	5	8		TWA (8 h)	
		10	15		STEL (15 min)	
-	Nickel, inorganic compounds (as Ni), soluble compounds	-	0.1		TWA (8 h)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7647-01-0	Hydrochloric acid			
	Worker DNEL, long-term	inhalation	local	8 mg/m ³
	Worker DNEL, acute	inhalation	local	15 mg/m ³
	Consumer DNEL, long-term	inhalation	local	8 mg/m ³
	Consumer DNEL, acute	inhalation	local	15 mg/m ³
1330-43-4	boric acid, disodium salt			
	Worker DNEL, long-term	inhalation	systemic	6,7 mg/m ³
	Worker DNEL, long-term	dermal	systemic	316,4 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	3,4 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	159,5 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,79 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	0,79 mg/kg bw/day
7718-54-9	nickel dichloride			
	Worker DNEL, acute	inhalation	local	1,6 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	8,8 mg/m ³
	Consumer DNEL, acute	inhalation	local	0,1 mg/m ³
	Worker DNEL, acute	inhalation	systemic	104 mg/m ³
	Consumer DNEL, long-term	oral	systemic	0,02 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	0,012 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 6 of 13

PNEC values

CAS No	Substance	Value
Environmental compartment		
1330-43-4	boric acid, disodium salt	
Freshwater		2,9 mg/l
Freshwater (intermittent releases)		13,7 mg/l
Marine water		2,9 mg/l
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		5,7 mg/kg
7718-54-9	nickel dichloride	
Freshwater		0,0071 mg/l
Freshwater (intermittent releases)		0 mg/l
Marine water		0,0086 mg/l
Freshwater sediment		109 mg/kg
Marine sediment		109 mg/kg
Secondary poisoning		0,12 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,33 mg/l
Soil		29,9 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:
Face protection shield
goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact
Recommended glove articles: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact
Recommended glove articles: KCL 741 Dermatril® L
Recommended material: NBR (Nitrile rubber) 0,11 mm
Wearing time with occasional contact (splashes): > 480 min

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 7 of 13

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing.
Protective clothing acid-resistant

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	stinging
Odour threshold:	No data available

Changes in the physical state

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Flash point:	X

Flammability

Solid/liquid:	not applicable
Gas:	not applicable

Explosive properties

No data available

Lower explosion limits:	No data available
Upper explosion limits:	No data available
Auto-ignition temperature:	No data available

Self-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: No data available

pH-Value: 0,2

Viscosity / dynamic: No data available

Viscosity / kinematic: No data available

Flow time: No data available

Water solubility: easily soluble

Solubility in other solvents

not determined

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 8 of 13

Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	1,0279 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion:	No data available
Oxidizing properties	
No data available	

Other safety characteristics

Solvent separation test:	No data available
Solvent content:	0
Solid content:	0
Evaporation rate:	No data available

Further Information

Corrosive to metals

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

The product develops hydrogen in an aqueous solution in contact with metals.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 9 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-43-4	boric acid, disodium salt				
	oral	LD50 > 2500 mg/kg	Rat	Study report (1996)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1985)	other: This study was carried out to com
	inhalation (4 h) dust/mist	LC50 > 2,04 mg/l	Rat	Study report (1994)	OECD Guideline 403
7718-54-9	nickel dichloride				
	oral	LD50 500 mg/kg	Rat	Regul Toxicol and Pharmacol (doi.org/10.	OECD Guideline 425
	inhalation vapour	ATE 3 mg/l			
	inhalation dust/mist	ATE 0,5 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met. slightly irritant but not relevant for classification.

Sensitising effects

Contains nickel dichloride. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

Irritant

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 10 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7647-01-0	Hydrochloric acid					
	Acute fish toxicity	LC50	862 mg/l	96 h	Leuciscus idus	
1330-43-4	boric acid, disodium salt					
	Acute fish toxicity	LC50	79,7 mg/l	96 h	Pimephales promelas	Study report (2010) other: ASTM E729-95 Standard Guide for C
	Acute algae toxicity	ErC50	66 mg/l	72 h	Phaeodactylum tricorutum	Study report (2011) ISO 10253
	Acute crustacea toxicity	EC50	102 mg/l	48 h	Ceriodaphnia dubia	Study report (2010) other: ASTM E729-95 Standard Guide for C
	Fish toxicity	NOEC	6,4 mg/l	34 d	Danio rerio	Study report (2000) OECD Guideline 210
	Algae toxicity	NOEC	17,5 mg/l	3 d	Pseudokirchneriella subcapitata	Study report (2000) OECD Guideline 201
	Crustacea toxicity	NOEC	10,8 mg/l	21 d	Daphnia magna	Study report (2000) OECD Guideline 211
	Acute bacteria toxicity	(EC50 mg/l)	> 10000	3 h	activated sludge of a predominantly domestic sewage	Study report (2001) OECD Guideline 209
7718-54-9	nickel dichloride					
	Acute fish toxicity	LC50	15,3 mg/l	96 h	Oncorhynchus mykiss	Aquatic Toxicology 63 (2003) 65-82 (2003) other: not reported
	Acute algae toxicity	ErC50	0,263 mg/l	72 h	Spermatozopsis exsultans	Publication (2009) OECD Guideline 201
	Acute crustacea toxicity	EC50	> 0,2 mg/l	48 h	Ceriodaphnia dubia	Environmental Toxicology and Chemistry. other: comparable to USEPA, Methods for
	Fish toxicity	NOEC	0,04 mg/l	8 d	Danio rerio	Arch. Environ. Contam. Toxicol. 21:126-1 other: Swedish Standard SS 02 81 93
	Algae toxicity	NOEC	0,6 mg/l	14 d	Anabaena cylindrica	Environ. Pollut. (Series A). 25(4):241-2 other: not reported
	Crustacea toxicity	NOEC	0,09 mg/l	21 d	Daphnia magna	Water Res. 23(4):501-510 (1989) other: DIN 38412, Part II
	Acute bacteria toxicity	(EC50	33 mg/l)	0,5 h	Activated sludge	Journal of Hazardous Materials. B139:332 ISO 8192

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1330-43-4	boric acid, disodium salt	-1,53

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 11 of 13

BCF

CAS No	Chemical name	BCF	Species	Source
1330-43-4	boric acid, disodium salt	0,558	Oncorhynchus nerka	Water Research Vol.
7718-54-9	nickel dichloride	39	Chlorella salina	J. Mar. Biol. Ass. U

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substance in the mixture does not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not empty into drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1
Special Provisions:	520
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1789
14.2. UN proper shipping name:	HYDROCHLORIC ACID
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C1

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 12 of 13

Special Provisions: 520
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1789
14.2. UN proper shipping name: HYDROCHLORIC ACID
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8
 Special Provisions: -
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-A, S-B
 Segregation group: 1 - acids

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1789
14.2. UN proper shipping name: HYDROCHLORIC ACID
14.3. Transport hazard class(es): 8
14.4. Packing group: II
 Hazard label: 8
 Special Provisions: A3 A803
 Limited quantity Passenger: 0.5 L
 Passenger LQ: Y840
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 851
 IATA-max. quantity - Passenger: 1 L
 IATA-packing instructions - Cargo: 855
 IATA-max. quantity - Cargo: 30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):
 Substances of very high concern, SVHC (REACH, article 59):
 boric acid, disodium salt

Restrictions on use (REACH, annex XVII):
 Entry 27, Entry 30, Entry 75

Information according to 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
 Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung 6 Elemente je 5 mg/l in HCl 5 % (V/V) + 1 % Soda/Borax (4+1)

Revision date: 17.08.2021

Product code: 33801

Page 13 of 13

IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data

Relevant H and EUH statements (number and full text)

H290	May be corrosive to metals.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350i	May cause cancer by inhalation.
H360D	May damage the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH208	Contains nickel dichloride. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)