

according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

UFI: WAT0-J34M-T006-RACP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH Street: Stempelstraße 6 Place: D-47167 Duisburg Telephone: 0203/5194-0

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone
 number:
 For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire,
 Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada:

1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls

Telefax: 0203/5194-290

accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydrochloric acid

Signal word: Warning

Pictograms:







according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 2 of 13

Hazard statements

H290 May be corrosive to metals.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statements

P280 Wear protective gloves and eye/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses. if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P390 Absorb spillage to prevent material damage.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

| CAS No | Chemical name | | | Quantity |
|-----------|--|--------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (Regulation (EC) No 1272/2008) | | | |
| 7647-01-0 | Hydrochloric acid | | | 10 - < 15 % |
| | 231-595-7 | 017-002-01-X | 01-2119484862-27 | |
| | Skin Corr. 1B, STOT SE 3; H314 F | | | |
| 7697-37-2 | nitric acid | | | < 1 % |
| | 231-714-2 | 007-030-00-3 | 01-2119487297-23 | |
| | Ox. Liq. 3, Met. Corr. 1, Acute Tox. 3, Skin Corr. 1A; H272 H290 H331 H314 EUH071 | | | |
| 7761-88-8 | silver nitrate | | | < 0.01 % |
| | 231-853-9 | 047-001-00-2 | 01-2119513705-43 | |
| | Ox. Sol. 2, Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H272 H290 H314 H318 H400 H410 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits. M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | |
|-----------|----------------|---|-------------|--|
| | Specific Conc. | Limits, M-factors and ATE | | |
| 7647-01-0 | 231-595-7 | Hydrochloric acid | 10 - < 15 % | |
| | · · | H314: >= 25 - 100 | | |
| 7697-37-2 | 231-714-2 | nitric acid | < 1 % | |
| | | inhalation: ATE 2,65 mg/l (vapours) Ox. Liq. 3; H272: >= 65 - 100 Skin Corr. 1A; H314: >= 20 - 100 Skin Corr. 1B; H314: >= 5 - < 20 | | |
| 7761-88-8 | 231-853-9 | silver nitrate | < 0.01 % | |
| | | = > 348 mg/kg; oral: LD50 = > 2000 mg/kg | | |



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 3 of 13

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant — skin irritation and eye damage

Cough

Dyspnoea

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Hydrochloric gas

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 4 of 13

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders: Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment.

Provide adequate ventilation.

Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Take off immediately all contaminated clothing and wash it before reuse.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 5 of 13

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Provide adequate ventilation as well as local exhaustion at critical locations.

Keep in a cool place.

Further information on storage conditions

Unsuitable container/equipment material: Metal, Glass

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

| CAS No | Substance | ppm | mg/m³ | fib/cm³ | Category | Origin |
|-----------|-------------------|-----|-------|---------|---------------|--------|
| 7647-01-0 | Hydrogen chloride | 5 | 8 | | TWA (8 h) | |
| | | 10 | 15 | | STEL (15 min) | |
| 7697-37-2 | Nitric acid | 1 | 2.6 | | STEL (15 min) | |

DNEL/DMEL values

| CAS No | Substance | | | | |
|--------------------------|-------------------|----------------|----------|----------------------|--|
| DNEL type | | Exposure route | Effect | Value | |
| 7647-01-0 | Hydrochloric acid | | | | |
| Worker DNEL, | long-term | inhalation | local | 8 mg/m³ | |
| Worker DNEL, acute | | inhalation | local | 15 mg/m³ | |
| Consumer DNEL, long-term | | inhalation | local | 8 mg/m³ | |
| Consumer DNEL, acute | | inhalation | local | 15 mg/m³ | |
| 7761-88-8 silver nitrate | | | | | |
| Consumer DNEL, long-term | | oral | systemic | 0,02 mg/kg bw/day | |
| Worker DNEL, long-term | | inhalation | systemic | 0,016 mg/m³ | |
| Consumer DNEL, long-term | | inhalation | systemic | 0,006 mg/m³ | |

PNEC values

| CAS No | Substance | | |
|---|---------------------------------|--------------|--|
| Environmental | Environmental compartment Value | | |
| 7761-88-8 | silver nitrate | | |
| Freshwater | | 0,00004 mg/l | |
| Marine water 0,00086 mg | | 0,00086 mg/l | |
| Freshwater sediment 438,13 mg/ | | 438,13 mg/kg | |
| Marine sediment 438,13 | | 438,13 mg/kg | |
| Micro-organisms in sewage treatment plants (STP) 0,025 mg/l | | 0,025 mg/l | |
| Soil 1,41 mg/kg | | 1,41 mg/kg | |

8.2. Exposure controls



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 6 of 13

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Face protection shield goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L Recommended material: NBR (Nitrile rubber) 0,11 mm Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Protective clothing acid-resistant

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: colourless
Odour: stinging

Odour threshold: No data available

Melting point/freezing point:

No data available



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 7 of 13

Boiling point or initial boiling point and

No data available

boiling range:

Flammability: not applicable
Lower explosion limits: No data available
Upper explosion limits: No data available
Flash point: X
Auto-ignition temperature: No data available
Decomposition temperature: No data available

pH-Value (at 20 °C): 0,0
Viscosity / kinematic: No data available
Water solubility: easily soluble

Solubility in other solvents

not determined

Dissolution rate: No data available Partition coefficient n-octanol/water: No data available Dispersion stability: No data available Vapour pressure: No data available Vapour pressure: No data available 1,0538 g/cm³ Density (at 20 °C): No data available Relative density: No data available Bulk density: Relative vapour density: No data available No data available Particle characteristics:

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Sustaining combustion: No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

Solvent separation test:

Solvent content:

Solid content:

No data available

No data available

No data available

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

Flow time:

No data available

No data available

Further Information

Corrosive to metals

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 8 of 13

10.2. Chemical stability

Protect against: Light

10.3. Possibility of hazardous reactions

Exothermic reaction with: Amines, permanganates, e.g. potassium permanganate, aldehydes

Ignition hazard: Carbide, Fluorine

Possibility of hazardous reactions: Aluminium, Formaldehyde, Metal, Alkali (lye)

Danger of explosion: Alkali metals, Sulphuric acid, concentrated

10.4. Conditions to avoid

Heat

Light

10.5. Incompatible materials

Metal. Glass

Keep away from: Metal.

The product develops hydrogen in an aqueous solution in contact with metals.

10.6. Hazardous decomposition products

In case of fire may be liberated: SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

Pulmonary oedema

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

| CAS No | Chemical name | | | | | |
|-----------|-------------------|----------------------|------------|---|--------------------|--|
| | Exposure route | Dose | Species | Source | Method | |
| 7697-37-2 | nitric acid | | | | | |
| | inhalation vapour | ATE 2,65 mg/l | | | | |
| 7761-88-8 | silver nitrate | | | | | |
| | oral | LD50 > 2000 mg/kg | Rat | Study report (1993) | OECD Guideline 401 | |
| | dermal | LD50 > 348 mg/kg | Guinea pig | J. Vet. Med. Sci.73: 1417 - 1423. (2011) | OECD Guideline 434 | |

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 9 of 13

STOT-single exposure

May cause respiratory irritation. (Hydrochloric acid)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the mixture itself.

Other information

There are no data available on the mixture itself.

Further information

Irritant — skin irritation and eye damage

Couah

Dyspnoea

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 10 of 13

| CAS No | Chemical name | | | | | | |
|-----------|--------------------------|--------------------|-----------|--------------------------|--|--|--|
| | Aquatic toxicity Dose | | [h] [d] | [h] [d] Species Source | | Method | |
| 7647-01-0 | Hydrochloric acid | Hydrochloric acid | | | | | |
| | Acute fish toxicity | LC50 | 862 mg/l | 96 h | Leuciscus idus | | |
| 7697-37-2 | nitric acid | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 1559 | 96 h | Topeka shiner | Environmental Toxicology and Chemistry, | other: ASTM E729-26 |
| | Fish toxicity | NOEC | 268 mg/l | 30 d | juvenile Topeka shiner and with juvenile Fathead m | Study report (2009) | Growth tests estimated the test chemical |
| | Algae toxicity | NOEC mg/l | > 419 | 10 d | several benthic diatoms; see results | Marine Biology 43:307-315 (1977) | Ten cultures of benthic diatoms were iso |
| | Acute bacteria toxicity | EC50 mg/l () | > 1000 | 3 h | Activated sludge | Study report (2008) | OECD Guideline 209 |
| 7761-88-8 | silver nitrate | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 0,0012 | 96 h | Pimephales promelas | Environmental Toxicology and Chemistry. | A guideline was not specified. The test |
| | Acute algae toxicity | ErC50 mg/l | 0,0099 | 96 h | Pseudokirchneriella subcapitata | Environmental Science and Technology. 44 | eline: U.S. Environmental Protection Age |
| | Acute crustacea toxicity | EC50 mg/l | 0,00022 | 48 h | Daphnia magna | Environmental Toxicology and Chemistry. | The protective effect of reactive sulphi |
| | Fish toxicity | NOEC 0,00125 mg | > g/l | 73 d | Oncorhynchus mykiss | Environmental Toxicology and Chemistry 2 | other: ASTM 1241-98 |
| | Algae toxicity | NOEC mg/l | 0,0012 | 14 d | Champia parvula | in Bishop WE, Cardwell RD Heidolph BB (E | The toxicity tests lasted 11 days for th |
| | Crustacea toxicity | NOEC mg/l | 0,00031 | 20 d | Isonychia bicolour | Environmental Toxicology and Chemistry. | 20 day sublethal effects on representati |

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

BCF

| CAS No | Chemical name | BCF | Species | Source |
|-----------|----------------|-----|-----------------|---------------------|
| 7761-88-8 | silver nitrate | 70 | Cyprinus carpio | Water, Air and Soil |

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 11 of 13

Discharge into the environment must be avoided.

Further information

Do not empty into drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

| 14.1. | UN number | or ID number: | UN 1789 |
|-------|------------------|---------------|---------|
|-------|------------------|---------------|---------|

14.2. UN proper shipping name: HYDROCHLORIC ACID

14.3. Transport hazard class(es): 14.4. Packing group: Ш Hazard label: 8 Classification code: C1 **Special Provisions:** 520 Limited quantity: 1 I Excepted quantity: F2 Transport category: 2 Hazard No: 80 Tunnel restriction code: F

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1789

14.2. UN proper shipping name: HYDROCHLORIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Classification code:C1Special Provisions:520Limited quantity:1 LExcepted quantity:E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1789

14.2. UN proper shipping name: HYDROCHLORIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:-Limited quantity:1 LExcepted quantity:E2EmS:F-A, S-B

Air transport (ICAO-TI/IATA-DGR)



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 12 of 13

14.1. UN number or ID number: UN 1789

14.2. UN proper shipping name: HYDROCHLORIC ACID

14.3. Transport hazard class(es):814.4. Packing group:IIHazard label:8Special Provisions:A3 A803

Limited quantity Passenger: 0.5 L
Passenger LQ: Y840
Excepted quantity: E2

IATA-packing instructions - Passenger:851IATA-max. quantity - Passenger:1 LIATA-packing instructions - Cargo:855IATA-max. quantity - Cargo:30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive Not subject to 2012/18/EU (SEVESO III)

2012/18/EU (SEVESO III):

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant

disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9,12.



according to Regulation (EC) No 1907/2006

Multielement-Standardlösung "PM Fineness 1" 12 Elemente in Salzsäure 10 % mit Spuren Flusssäure...

Revision date: 09.11.2023 Product code: 33875 Page 13 of 13

Abbreviations and acronyms

Ox. Liq: Oxidising liquid Ox. Sol: Oxidising solid

Met. Corr: Substance or mixture corrosive to metals

Acute Tox: Acute toxicity Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

| Classification | Classification procedure | |
|---------------------|--------------------------|--|
| Met. Corr. 1; H290 | On basis of test data | |
| Skin Irrit. 2; H315 | Calculation method | |
| Eye Irrit. 2; H319 | Calculation method | |
| STOT SE 3; H335 | Calculation method | |

Relevant H and EUH statements (number and full text)

| H272 | May intensity tire; oxidiser. |
|--------|---|
| H290 | May be corrosive to metals. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H331 | Toxic if inhaled. |
| H335 | May cause respiratory irritation. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| EUH071 | Corrosive to the respiratory tract. |

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)