

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2-Propanol LC-MS min. 99.9 %

Substance name: propan-2-ol; isopropyl alcohol; isopropanol
REACH Registration Number: 01-2119457558-25-XXXX
CAS No: 67-63-0
Index No: 603-117-00-0
EC No: 200-661-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals
Industrial uses: Uses of substances as such or in preparations at industrial sites
Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
Telefax: 0203/5194-290
E-mail: info@analytichem.de
Contact person: Abteilung Produktsicherheit
Telephone: 0203/5194-107/117
E-mail: produktsicherheit@analytichem.de
Internet: www.analytichem.de
Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

No data available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 2 of 11

Hazard statements

- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Sum formula: CH₃CH(OH)CH₃
Molecular weight: 60,1 g/mol

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

- Provide fresh air.
- Call a physician immediately.

After contact with skin

- Wash immediately with: Water
- Take off immediately all contaminated clothing and wash it before reuse.

After contact with eyes

- In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
- Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

- Observe risk of aspiration if vomiting occurs.
- Call a physician immediately.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 3 of 11

4.2. Most important symptoms and effects, both acute and delayed

Irritant
Respiratory complaints
Headache
Dizziness
Dizziness
Inebriation
Anaesthetic state
Unconsciousness
Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids
Hazardous combustion products
In case of fire may be liberated: Carbon dioxide (CO₂), Carbon monoxide
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.
Beware of reignition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).
Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 4 of 11

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol. Provide adequate ventilation.

Advice on protection against fire and explosion

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

Wash hands and face before breaks and after work and take a shower if necessary.

When using do not eat or drink.

Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store in a cool dry place.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Further information on storage conditions

Protect from sunlight.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 5 of 11

Protect against: Light
minimum storage temperature +5°C
maximum storage temperature +30°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
67-63-0	Propan-2-ol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-63-0	2-Propanol	Acetone	40 mg/L	Urine	End of shift at end of workweek

DNEL/DMEL values

CAS No	Substance	DNEL type	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	Worker DNEL, long-term		inhalation	systemic	500 mg/m ³
	Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
	Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
	Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
	Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day

PNEC values

CAS No	Substance	Environmental compartment	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
	Freshwater		140,9 mg/l
	Freshwater (intermittent releases)		140,9 mg/l
	Marine water		140,9 mg/l
	Freshwater sediment		552 mg/kg
	Marine sediment		552 mg/kg
	Secondary poisoning		160 mg/kg
	Micro-organisms in sewage treatment plants (STP)		2251 mg/l
	Soil		28 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 6 of 11

Eye/face protection

goggles
Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours
Suitable material: NBR (Nitrile rubber) 0,4 mm
Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation: KCL 720 Camapren®
Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm
Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear fire resistant or flame retardant clothing.
Take off immediately all contaminated clothing and wash it before reuse.
Wear suitable protective clothing. Take off immediately all contaminated clothing.
Wash hands and face before breaks and after work and take a shower if necessary.
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
Filtering device with filter or ventilator filtering device of type: A
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like: Alcohol
Odour threshold:	No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 7 of 11

Melting point/freezing point:	-89,5 °C
Boiling point or initial boiling point and boiling range:	82,5 °C
Flammability:	No data available
Lower explosion limits:	2 vol. %
Upper explosion limits:	13 vol. %
Flash point:	11,7 °C
Auto-ignition temperature:	425 °C
Decomposition temperature:	No data available
pH-Value (at 20 °C):	neutral
Viscosity / kinematic: (at 25 °C)	2,5316 mm ² /s
Water solubility:	easily soluble
Solubility in other solvents	
ethanol; ethyl alcohol, diethyl ether; ether, acetone; propan-2-one; propanone, chloroform; trichloromethane	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	log Pow: 0,05
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	44 hPa
Vapour pressure: (at 50 °C)	76 hPa
Density:	0,786 g/cm ³
Relative density (at 20 °C):	0,8
Bulk density:	No data available
Relative vapour density: (at 20 °C)	2,1
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustaining combustion: Sustaining combustion

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

No data available

Viscosity / dynamic:
(at 20 °C) 2,2 mPa·s

Flow time: No data available

Further Information

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 8 of 11

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

Formation of: Peroxides

10.2. Chemical stability

Protect against:

Light

Air

10.3. Possibility of hazardous reactions

Oxidising agent, Alkali metals, Alkaline earth metal,

, Nitric acid, aldehydes

Amines, Aluminium, Chlorine (Cl₂)

Phosphorus trichloride, Strong acid, Phosgene

Hydrogen peroxide, Nitrogen oxides (NO_x), Iron.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Light

Air

10.5. Incompatible materials

Rubber articles

Plastic articles

10.6. Hazardous decomposition products

Peroxides

In case of fire:

SECTION 5: Firefighting measures

Further information

Peroxides

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 9 of 11

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia
Repeated exposure may cause skin dryness or cracking.

Further information

No data available

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	10000	96 h	Pimephales promelas	Publication (1983) OECD Guideline 203

12.2. Persistence and degradability

95 %; 21 d; aerob
OECD-301E
Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

Avoid release to the environment.

Further information

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 10 of 11

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	-
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1219
14.2. UN proper shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II

Safety Data Sheet

according to Regulation (EC) No 1907/2006

2-Propanol LC-MS min. 99.9 %

Revision date: 05.06.2024

Product code: 34114

Page 11 of 11

Hazard label:	3	
Special Provisions:	A180	
Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

Directive 2010/75/EU on industrial emissions: 100 % (786 g/l)

Directive 2004/42/EC on VOC in paints and varnishes: 100 % (786 g/l)

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,9,12,15.

Abbreviations and acronyms

Flam. Liq: Flammable liquid

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.