

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

UFI: WKM1-C32A-U00P-7PPN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Laboratory chemicals

Industrial uses: Uses of substances as such or in preparations at industrial sites

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name:	AnalytiChem GmbH	
	ACD	
Street:	Stempelstraße 6	
Place:	D-47167 Duisburg	
Telephone:	0203/5194-0	Telefax: 0203/5194-290
E-mail:	info@analytichem.de	
Contact person:	Abteilung Produktsicherheit	Telephone: 0203/5194-107/117
E-mail:	produktsicherheit@analytichem.de	
Internet:	www.analytichem.de	
Responsible Department:	Abteilung Produktsicherheit	

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Met. Corr. 1; H290

Aquatic Acute 1; H400

Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Signal word: Warning

Pictograms:



Hazard statements

H290

May be corrosive to metals.

H410

Very toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 2 of 12

Precautionary statements

- P234 Keep only in original packaging.
- P273 Avoid release to the environment.
- P391 Collect spillage.
- P406 Store in a corrosion-resistant container with a resistant inner liner.
- P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixtures in aqueous solution

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
7761-88-8	silver nitrate			< 1 %
	231-853-9	047-001-00-2	01-2119513705-43	
	Ox. Sol. 2, Met. Corr. 1, Skin Corr. 1B, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H272 H290 H314 H318 H400 H410			
1336-21-6	Ammonia			< 1 %
	215-647-6	007-001-01-2	01-2119488876-14	
	Skin Corr. 1B, Aquatic Acute 1, Aquatic Chronic 2; H314 H400 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
7761-88-8	231-853-9	silver nitrate	< 1 %
	dermal: LD50 = > 348 mg/kg; oral: LD50 = > 2000 mg/kg Aquatic Acute 1; H400: M=1000 Aquatic Chronic 1; H410: M=100		
1336-21-6	215-647-6	Ammonia	< 1 %
	inhalation: LC50 = 4230 mg/l (vapours); oral: LD50 = 350 mg/kg STOT SE 3; H335: >= 5 - 100 Aquatic Acute 1; H400: M=10		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!

After inhalation

- Provide fresh air.
- Call a doctor if you feel unwell.

After contact with skin

- Wash immediately with: Water
- Take off immediately all contaminated clothing and wash it before reuse.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 3 of 12

In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Non-combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Nitrogen oxides (NO_x)

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe vapour/aerosol.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 4 of 12

6.3. Methods and material for containment and cleaning up

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
- Collect in closed and suitable containers for disposal.

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Use personal protection equipment.
- Provide adequate ventilation. Avoid contact with skin, eyes and clothes.
- Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

- Usual measures for fire prevention.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.
- Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Unsuitable container/equipment material: Metal

Further information on storage conditions

- Keep container tightly closed.
- Protect against: Light

7.3. Specific end use(s)

- Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 5 of 12

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
7664-41-7	Ammonia, anhydrous	20	14		TWA (8 h)	
		50	36		STEL (15 min)	

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
7761-88-8	silver nitrate			
	Consumer DNEL, long-term	oral	systemic	0,02 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	0,016 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	0,006 mg/m ³
1336-21-6	Ammonia			
	Worker DNEL, long-term	inhalation	systemic	47,6 mg/m ³
	Worker DNEL, acute	inhalation	systemic	47,6 mg/m ³
	Worker DNEL, long-term	inhalation	local	14 mg/m ³
	Worker DNEL, acute	inhalation	local	36 mg/m ³
	Worker DNEL, long-term	dermal	systemic	6,8 mg/kg bw/day
	Worker DNEL, acute	dermal	systemic	6,8 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	23,8 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	23,8 mg/m ³
	Consumer DNEL, long-term	inhalation	local	2,8 mg/m ³
	Consumer DNEL, acute	inhalation	local	7,2 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	68 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	68 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	6,8 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	6,8 mg/kg bw/day

PNEC values

CAS No	Substance	Value
7761-88-8	silver nitrate	
	Freshwater	0,00004 mg/l
	Marine water	0,00086 mg/l
	Freshwater sediment	438,13 mg/kg
	Marine sediment	438,13 mg/kg
	Micro-organisms in sewage treatment plants (STP)	0,025 mg/l
	Soil	1,41 mg/kg
1336-21-6	Ammonia	
	Freshwater	0,001 mg/l
	Freshwater (intermittent releases)	0,007 mg/l
	Marine water	0,001 mg/l

8.2. Exposure controls

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 6 of 12

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Recommended glove articles: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Recommended glove articles: KCL 741 Dermatril® L

Recommended material: NBR (Nitrile rubber) 0,11mm

Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet (>, <) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		No data available
Flammability:		No data available
Lower explosion limits:		No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 7 of 12

Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	12,6
Viscosity / kinematic:	No data available
Water solubility:	completely miscible
Solubility in other solvents	
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	1,0052 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties	
No data available	
Sustaining combustion:	No data available
Self-ignition temperature	
Solid:	No data available
Gas:	No data available
Oxidizing properties	
No data available	

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	0%
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Corrosive to metals.

10.2. Chemical stability

Protect against: Light

10.3. Possibility of hazardous reactions

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 8 of 12

10.4. Conditions to avoid

Light

10.5. Incompatible materials

Metal

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
7761-88-8	silver nitrate				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1993)	OECD Guideline 401
	dermal	LD50 > 348 mg/kg	Guinea pig	J. Vet. Med. Sci.73: 1417 - 1423. (2011)	OECD Guideline 434
1336-21-6	Ammonia				
	oral	LD50 350 mg/kg	Rat	Journal of Industrial Hygiene and Toxicology	OECD Guideline 401
	inhalation (1 h) vapour	LC50 4230 mg/l	Mouse	Bull. Environm. Contam. Toxicol, 1982, 2	Assessment of acute inhalation toxicity

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 9 of 12

Information on likely routes of exposure

There are no data available on the preparation/mixture itself.

Specific effects in experiment on an animal

There are no data available on the preparation/mixture itself.

Additional information on tests

There are no data available on the preparation/mixture itself.

Practical experience

There are no data available on the preparation/mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

There are no data available on the preparation/mixture itself.

Other information

There are no data available on the preparation/mixture itself.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
7761-88-8	silver nitrate					
	Acute fish toxicity	LC50 mg/l	0,0012	96 h	Pimephales promelas	Environmental Toxicology and Chemistry. A guideline was not specified. The test
	Acute algae toxicity	ErC50 mg/l	0,0099	96 h	Pseudokirchneriella subcapitata	eline: U.S. Environmental Protection Agency. 44
	Acute crustacea toxicity	EC50 mg/l	0,00022	48 h	Daphnia magna	Environmental Toxicology and Chemistry. The protective effect of reactive sulphur
	Fish toxicity	NOEC > 0,00125 mg/l		73 d	Oncorhynchus mykiss	Environmental Toxicology and Chemistry 2 other: ASTM 1241-98
	Algae toxicity	NOEC mg/l	0,0012	14 d	Champia parvula	in Bishop WE, Cardwell RD Heidolph BB (E) The toxicity tests lasted 11 days for th
	Crustacea toxicity	NOEC mg/l	0,00031	20 d	Isonychia bicolor	Environmental Toxicology and Chemistry. 20 day sublethal effects on representati
1336-21-6	Ammonia					
	Acute fish toxicity	LC50 3,4 mg/l	0,75 -	96 h	Pimephales promelas	Trans Amer Fish Soc; 112 (5). 1983. 705- Assessment of acute toxicity in the fath
	Acute crustacea toxicity	EC50	101 mg/l	48 h	Daphnia magna	Environ. Toxicol. Chem. 5: 443-447 (1986) other: ASTM E729-80
	Fish toxicity	NOEC	1,2 mg/l	61 d	Oncorhynchus gorbuscha	Fish. Bull. 78(3): 641-648 (1980) OECD Guideline 210

12.2. Persistence and degradability

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 10 of 12

The methods for determining the biological degradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
1336-21-6	Ammonia	-1,38

BCF

CAS No	Chemical name	BCF	Species	Source
7761-88-8	silver nitrate	70	Cyprinus carpio	Water, Air and Soil

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 3266
14.2. UN proper shipping name:	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (potassium hydroxide)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C5
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 11 of 12

14.1. UN number or ID number:	UN 3266
14.2. UN proper shipping name:	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (potassium hydroxide)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Classification code:	C5
Special Provisions:	274
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

14.1. UN number or ID number:	UN 3266
14.2. UN proper shipping name:	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (potassium hydroxide)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	223, 274
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-A, S-B
Segregation group:	18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 3266
14.2. UN proper shipping name:	CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (potassium hydroxide)
14.3. Transport hazard class(es):	8
14.4. Packing group:	III
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	1 L
Passenger LQ:	Y841
Excepted quantity:	E1
IATA-packing instructions - Passenger:	852
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	856
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	silver nitrate

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

National regulatory information

Water hazard class (D): 3 - highly hazardous to water

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Alkalische Silbernitratlösung zum Versilbern von Lackfolien

Revision date: 24.06.2024

Product code: 34169

Page 12 of 12

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,9,12.

Abbreviations and acronyms

- Ox. Sol: Oxidising solid
- Met. Corr: Substance or mixture corrosive to metals
- Skin Corr: Skin corrosion
- Eye Dam: Eye damage
- Aquatic Acute: Acute aquatic hazard
- Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Met. Corr. 1; H290	On basis of test data
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

Relevant H and EUH statements (number and full text)

- H272 May intensify fire; oxidiser.
- H290 May be corrosive to metals.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material. The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations. Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)