

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

UFI: C1Y3-H3MD-C00C-HTH3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Company name: AnalytiChem GmbH
ACD

Street: Stempelstraße 6

Place: D-47167 Duisburg

Telephone: 0203/5194-0

Telefax: 0203/5194-290

E-mail: info@analytichem.de

Contact person: Abteilung Produktsicherheit

Telephone: 0203/5194-107/117

E-mail: produktsicherheit@analytichem.de

Internet: www.analytichem.de

Responsible Department: Abteilung Produktsicherheit

1.4. Emergency telephone number:

For Hazardous Materials [or Dangerous Goods] Incidents Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Met. Corr. 1; H290

Acute Tox. 4; H332

Acute Tox. 4; H312

Acute Tox. 4; H302

Skin Corr. 1B; H314

Eye Dam. 1; H318

STOT SE 1; H370

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetic acid

methanol

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 2 of 15

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled.
H314	Causes severe skin burns and eye damage.
H370	Causes damage to organs.

Precautionary statements

P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-19-7	acetic acid			60 - < 65 %
	200-580-7	607-002-00-6	01-2119475328-30	
	Flam. Liq. 3, Skin Corr. 1A, Eye Dam. 1; H226 H314 H318			
67-56-1	methanol			20 - < 25 %
	200-659-6	603-001-00-X	01-2119433307-44	
	Flam. Liq. 2, Acute Tox. 3, Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311 H301 H370			
7758-02-3	potassium bromide			1 - < 5 %
	231-830-3		01-2119962195-33	
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 3 of 15

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64-19-7	200-580-7	acetic acid	60 - < 65 %
		oral: LD50 = 3310 mg/kg Skin Corr. 1A; H314: >= 90 - 100 Skin Corr. 1B; H314: >= 25 - < 90 Skin Irrit. 2; H315: >= 10 - < 25 Eye Irrit. 2; H319: >= 10 - < 25	
67-56-1	200-659-6	methanol	20 - < 25 %
		inhalation: LC50 = 128,2 mg/l (vapours); inhalation: ATE = 0,5 mg/l (dusts or mists); dermal: ATE = 300 mg/kg; oral: LD50 = 6000 mg/kg STOT SE 1; H370: >= 10 - 100 STOT SE 2; H371: >= 3 - < 10	
7758-02-3	231-830-3	potassium bromide	1 - < 5 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection!
Call a physician immediately.

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.
Protect uninjured eye.

After ingestion

Rinse mouth immediately and drink plenty of water.
Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

corrosive
Irritant
Cough
Dyspnoea
Respiratory complaints
Dizziness

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 4 of 15

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon monoxide

Carbon dioxide

Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 5 of 15

Other information

Provide adequate ventilation.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use extractor hood (laboratory).
Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Use personal protection equipment.
Provide adequate ventilation. Avoid contact with skin, eyes and clothes.
Do not breathe vapour/aerosol.

Advice on protection against fire and explosion

Usual measures for fire prevention.
In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs. Remove contaminated, saturated clothing immediately.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink. Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

Further information on handling

Draw up and observe skin protection programme.
Wash hands and face before breaks and after work and take a shower if necessary.
Take off immediately all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place. Keep container tightly closed.
Corrosive to metals.

Hints on joint storage

national regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	
		20	50		STEL (15 min)	
67-56-1	Methyl alcohol	200	260		TWA (8 h)	

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 6 of 15

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-56-1	Methanol	Methanol	15 mg/L	Urine	End of shift

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-19-7	acetic acid			
Worker DNEL, long-term		inhalation	local	25 mg/m ³
Worker DNEL, acute		inhalation	local	25 mg/m ³
Consumer DNEL, long-term		inhalation	local	25 mg/m ³
Consumer DNEL, acute		inhalation	local	25 mg/m ³
67-56-1	methanol			
Consumer DNEL, acute		inhalation	systemic	50 mg/m ³
Worker DNEL, long-term		inhalation	systemic	260 mg/m ³
Worker DNEL, acute		inhalation	systemic	260 mg/m ³
Worker DNEL, long-term		inhalation	local	260 mg/m ³
Worker DNEL, acute		inhalation	local	260 mg/m ³
Worker DNEL, long-term		dermal	systemic	40 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	50 mg/m ³
Consumer DNEL, long-term		inhalation	local	50 mg/m ³
Consumer DNEL, acute		inhalation	local	50 mg/m ³
Consumer DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	8 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	8 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	8 mg/kg bw/day
7758-02-3	potassium bromide			
Worker DNEL, long-term		inhalation	systemic	4,75 mg/m ³
Worker DNEL, long-term		dermal	systemic	95 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	95 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1,66 mg/m ³
Consumer DNEL, long-term		dermal	systemic	95 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	95 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,475 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	50 mg/kg bw/day

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 7 of 15

PNEC values

CAS No	Substance	
Environmental compartment		Value
64-19-7	acetic acid	
Freshwater		3,058 mg/l
Freshwater (intermittent releases)		30,58 mg/l
Marine water		0,306 mg/l
Freshwater sediment		11,36 mg/kg
Marine sediment		1,136 mg/kg
Micro-organisms in sewage treatment plants (STP)		85 mg/l
Soil		0,47 mg/kg
67-56-1	methanol	
Freshwater		20,8 mg/l
Freshwater (intermittent releases)		1540 mg/l
Marine water		2,08 mg/l
Freshwater sediment		77 mg/kg
Marine sediment		7,7 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		100 mg/kg
7758-02-3	potassium bromide	
Freshwater		0,52 mg/l
Freshwater (intermittent releases)		109 mg/l
Marine water		41 mg/l
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		3,2 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact:

Trade name/designation: KCL 898 Butoject®

Recommended material: Butyl caoutchouc (butyl rubber) 0,7 mm

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 8 of 15

Wearing time with permanent contact > 480 min

By short-term hand contact

Trade name/designation: KCL 890 Vitoject®

Recommended material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 115 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet <(>, <)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing.

Wash hands before breaks and after work.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	<23 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 9 of 15

Density:	~0,98 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available:

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

Corrosive to metals.

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Corrosive to metals.

10.2. Chemical stability

Protect against:

Heat

10.3. Possibility of hazardous reactions

Ammonia (NH₃), Amines, Nitrogen oxides (NO_x), Alkali (lye), Fluorine, Alkali metals Alkaline earth metal, metals, Powdered metals, Methanol, Light metal, Ketone, Oxidising agent, strong

10.4. Conditions to avoid

Protect against:

Heat

10.5. Incompatible materials

Rubber articles

plastics

Metal

10.6. Hazardous decomposition products

In case of fire may be liberated:

SECTION 5: Firefighting measures

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 10 of 15

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicokinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Harmful if inhaled.

Harmful in contact with skin.

Harmful if swallowed.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

ATEmix calculated

ATE (oral) 480,1 mg/kg; ATE (dermal) 1440 mg/kg; ATE (inhalation vapour) 14,40 mg/l; ATE (inhalation dust/mist) 2,400 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64-19-7	acetic acid				
	oral	LD50 3310 mg/kg	Rat	J Ind Hyg Toxicol, Vol 23, PP 78-82 (194)	The sodium salt of acetic acid was admin
67-56-1	methanol				
	oral	LD50 6000 mg/kg	Monkey	Amer J Ophthalmol 40: 76-83 (cited in DG	Determination of the acute toxicity of t
	dermal	ATE 300 mg/kg			
	inhalation (4 h) vapour	LC50 128,2 mg/l	Rat	Study report (1980)	Study performed according to internal co
	inhalation dust/mist	ATE 0,5 mg/l			
7758-02-3	potassium bromide				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1992)	EPA OPP 81-1
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1988)	other: EPA FIFRA 81-6

Irritation and corrosivity

Skin corrosion/irritation: Causes severe skin burns and eye damage.

Serious eye damage/eye irritation: Causes serious eye damage.

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Causes damage to organs. (methanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 11 of 15

Aspiration hazard

Based on available data, the classification criteria are not met.

Observe risk of aspiration if vomiting occurs. (Pulmonary oedema Pneumonia)

Information on likely routes of exposure

There are no data available on the mixture itself.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

There are no data available on the mixture itself.

Practical experience

There are no data available on the mixture itself.

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

There are no data available on the mixture itself.

Further information

corrosive

Irritant

Cough

Dyspnoea

Respiratory complaints

Dizziness

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 12 of 15

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-19-7	acetic acid					
	Acute fish toxicity	LC50 > 1000 mg/l	96 h	Oncorhynchus mykiss	Study report (2005)	other: SOP E257
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Skeletonema costatum	Study report (2005)	ISO 10253
	Acute crustacea toxicity	EC50 > 1000 mg/l	48 h	Daphnia magna	Study report (1990)	OECD Guideline 202
67-56-1	methanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Fish toxicity	NOEC 446,7 mg/l	28 d	Pimephales promelas	SAR and QSAR in Environmental Research,	Calculation performed with ECOSAR
	Crustacea toxicity	NOEC 208 mg/l	21 d	Daphnia magna	OECD QSAR Toolbox Report (2013)	Toxicity of the target chemical is predi
7758-02-3	potassium bromide					
	Acute fish toxicity	LC50 > 440 mg/l	96 h	Scophthalmus maximus	Study report (2000)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 440 mg/l	72 h	Skeletonema costatum	Study report (2000)	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (1996)	OECD Guideline 202
	Fish toxicity	NOEC 10 mg/l	124 d	Poecilia reticulata	Fd. Chem. Toxic. Vol. 21, No. 4, 369-378	Dutch Standardisation Organisation
	Crustacea toxicity	NOEC 7,5 mg/l	21 d	Daphnia magna	Ecotoxicology and Environmental Safety,	other: OECD
	Acute bacteria toxicity	EC50 > 1000 mg/l ()	3 h	activated sludge of a predominantly domestic sewage	Study report (2007)	OECD Guideline 209

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-19-7	acetic acid	-0,17
67-56-1	methanol	-0,77

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 13 of 15

BCF

CAS No	Chemical name	BCF	Species	Source
64-19-7	acetic acid	3,16	fish	Environ. Toxicol. Ch
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi
7758-02-3	potassium bromide	0,23	Artemia salina	Environmental Toxicol

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Discharge into the environment must be avoided.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
Send to a physico-chemical treatment facility under observation of official regulations.
Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.
Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)".

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (acetic acid, methanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2924
14.2. UN proper shipping name:	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (acetic acid, methanol)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3+8
Classification code:	FC

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 14 of 15

Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (acetic acid, methanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+8
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-C

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 2924
14.2. UN proper shipping name: FLAMMABLE LIQUID, CORROSIVE, N.O.S. (acetic acid, methanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3+8
Special Provisions: A3
Limited quantity Passenger: 0.5 L
Passenger LQ: Y340
Excepted quantity: E2
IATA-packing instructions - Passenger: 352
IATA-max. quantity - Passenger: 1 L
IATA-packing instructions - Cargo: 363
IATA-max. quantity - Cargo: 5 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 69, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): H3 STOT SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE

Additional information: P5c

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

SECTION 16: Other information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Lösemittelgemisch für die coulometrische Bestimmung der Bromzahl 0,14 mol KBr/l in...

Revision date: 10.04.2025

Product code: 35013

Page 15 of 15

Abbreviations and acronyms

Met. Corr: Substance or mixture corrosive to metals
Flam. Liq: Flammable liquid
Acute Tox: Acute toxicity
Skin Corr: Skin corrosion
Eye Dam: Eye damage
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Acute Tox. 4; H332	Calculation method
Acute Tox. 4; H312	Calculation method
Acute Tox. 4; H302	Calculation method
Skin Corr. 1B; H314	Calculation method
Eye Dam. 1; H318	Calculation method
STOT SE 1; H370	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H290 May be corrosive to metals.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H370 Causes damage to organs (eyes, central nervous system).
H370 Causes damage to organs.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)