

Revision: 17.04.2025

**Petroleum ether 60-80 p.**

Product code: AC11.00226

Page 1 of 11

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Petroleum ether 60-80 p.

Substance name: Petroleum benzine  
REACH Registration Number: 01-2119475133-43-XXXX  
CAS No: 64742-49-0  
EC No: 265-151-9

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Reagents and laboratory chemicals  
Only for laboratory and analysis purposes.

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet****Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda  
Street: Rua de Júlio Dinis 676 7º  
Place: N-4050-320 Porto  
Telephone: +351 226002917  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: SDS service department

**Supplier or manufacturer details**

Company name: AnalytiChem Belgium NV  
Street: Industriezone "De Arend" 2  
Place: B-8210 Zedelgem  
Telephone: +32 50 28 83 20  
E-mail: info.be@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Responsible Department: AnalytiChem  
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333

Revision: 17.04.2025

**Petroleum ether 60-80 p.**

Product code: AC11.00226

Page 2 of 11

**1.4. Emergency telephone number:** +44 20 3807 3798 (CHEMTREC)**Further Information**

No data available


**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225  
Repr. 2; H361  
Skin Irrit. 2; H315  
STOT SE 3; H336  
STOT RE 2; H373  
Asp. Tox. 1; H304  
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

Petroleum benzine

**Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

**2.3. Other hazards**

No data available

**SECTION 3: Composition/information on ingredients****3.1. Substances**

## Petroleum ether 60-80 p.

Revision: 17.04.2025

Product code: AC11.00226

Page 3 of 11

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-49-0	Petroleum benzine			100 %
	265-151-9		01-2119475133-43-XXXX	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361 H315 H336 H373 H304 H411			

Full text of H and EUH statements: see section 16.

## Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## SECTION 4: First aid measures

**4.1. Description of first aid measures****General information**

No data available

**After inhalation**

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

**After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant

Vapours may cause drowsiness and dizziness.

Gastrointestinal complaints

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

## SECTION 5: Firefighting measures

**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>)

Foam

Extinguishing powder

Water spray jet

**Petroleum ether 60-80 p.**

Revision: 17.04.2025

Product code: AC11.00226

Page 4 of 11

**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**6.3. Methods and material for containment and cleaning up****For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Petroleum ether 60-80 p.**

Revision: 17.04.2025

Product code: AC11.00226

Page 5 of 11

**Other information**

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Avoid exposure - obtain special instructions before use.  
Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Provide adequate ventilation. Do not breathe vapour.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.  
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in a cool, well-ventilated place.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

National regulations

**Further information on storage conditions**

Keep container tightly closed and dry.  
Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****8.2. Exposure controls****Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment**

**Petroleum ether 60-80 p.**

Revision: 17.04.2025

Product code: AC11.00226

Page 6 of 11

**Eye/face protection**

goggles  
Face protection umbrella

**Hand protection**

Tested protective gloves must be worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

**Skin protection**

Take off immediately all contaminated clothing and wash it before reuse.  
Wear fire resistant or flame retardant clothing.  
Wash hands and face before breaks and after work and take a shower if necessary.  
Draw up and observe skin protection programme.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Thermal hazards**

No data available

**Environmental exposure controls**

Do not allow to enter into surface water or drains.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Danger of explosion

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	like: Gasoline
Odour threshold:	No data available
Melting point/freezing point:	-29 °C
Boiling point or initial boiling point and boiling range:	60-80 °C
Flammability:	No data available
Lower explosion limits:	1 vol. %
Upper explosion limits:	7,5 vol. %
Flash point:	-21 °C
Auto-ignition temperature:	260 °C
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	No data available
No data available	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,68 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available

Revision: 17.04.2025

**Petroleum ether 60-80 p.**

Product code: AC11.00226

Page 7 of 11

Relative vapour density: No data available  
Particle characteristics: No data available

**9.2. Other information****Information with regard to physical hazard classes****Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

**Sustained combustibility:****Sustained combustibility****Self-ignition temperature**

Solid: No data available  
Gas: No data available

**Oxidizing properties**

No data available

**Other safety characteristics**

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

Viscosity / dynamic: No data available

Flow time: No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Vapours may form explosive mixtures with air.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5. Incompatible materials**

Plastic articles

Rubber articles

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information****11.1. Information on hazard classes****Acute toxicity**

Based on available data, the classification criteria are not met.

**Petroleum ether 60-80 p.**

Revision: 17.04.2025

Product code: AC11.00226

Page 8 of 11

**Irritation and corrosivity**

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Suspected of damaging fertility or the unborn child. (Petroleum benzine)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (Petroleum benzine)

Organs affected: central nervous system

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure. (Petroleum benzine)

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Information on likely routes of exposure**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards****Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**Other information**

Avoid exposure - obtain special instructions before use.

**Further information**

Irritant

Vapours may cause drowsiness and dizziness.

Gastrointestinal complaints

**SECTION 12: Ecological information****12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of UK REACH.

**Petroleum ether 60-80 p.**

Revision: 17.04.2025

Product code: AC11.00226

Page 9 of 11

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

Avoid release to the environment.

**Further information**

No data available

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 1268

**14.2. UN proper shipping name:**

PETROLEUM DISTILLATES, N.O.S.

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3

Classification code:

F1

Special Provisions:

640D ADR664

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

33

Tunnel restriction code:

D/E

**Inland waterways transport (ADN)****14.1. UN number or ID number:**

UN 1268

**14.2. UN proper shipping name:**

PETROLEUM DISTILLATES, N.O.S.

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3

Classification code:

F1

Special Provisions:

363 640D

Limited quantity:

1 L

Excepted quantity:

E2

**Marine transport (IMDG)****14.1. UN number or ID number:**

UN 1268

**14.2. UN proper shipping name:**

PETROLEUM DISTILLATES, N.O.S.

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

II

Hazard label:

3

Special Provisions:

-

Limited quantity:

1 L

Excepted quantity:

E2

EmS:

F-E, S-E

Revision: 17.04.2025

## Petroleum ether 60-80 p.

Product code: AC11.00226

Page 10 of 11

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1268
<b>14.2. UN proper shipping name:</b>	PETROLEUM DISTILLATES, N.O.S.
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:	Yes
Danger releasing substance:	Naphtha (petroleum), hydrotreated light

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 29, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): E2 Hazardous to the Aquatic Environment

Additional information: P5c

**National regulatory information****SECTION 16: Other information****Abbreviations and acronyms**

Flam. Liq. 2: Flammable liquids, hazard category 2

Asp. Tox. 1: Aspiration hazard, hazard category 1

Skin Irrit. 2: Skin irritation, hazard category 2

Repr. 2: Reproductive toxicity, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be

**Petroleum ether 60-80 p.**

Revision: 17.04.2025

Product code: AC11.00226

Page 11 of 11

transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users