

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**isopropanol (260-000-202)**

Revision: 26.02.2025

Product code: AC11.00250

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

isopropanol (260-000-202)

REACH Registration Number: 01-2119457558-25-XXXX  
CAS No: 67-63-0  
Index No: 603-117-00-0  
EC No: 200-661-7

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Reagents and laboratory chemicals  
Only for laboratory and analysis purposes.

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet****Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda  
Street: Rua de Júlio Dinis 676 7º  
Place: N-4050-320 Porto  
Telephone: +351 226002917  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: SDS service department

**Supplier or manufacturer details**

Company name: AnalytiChem Belgium NV  
Street: Industriezone "De Arend" 2  
Place: B-8210 Zedelgem  
Telephone: +32 50 28 83 20  
E-mail: info.be@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Responsible Department: AnalytiChem:  
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333  
+353 1 901 4670 (CHEMTREC)

**1.4. Emergency telephone number:**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## isopropanol (260-000-202)

Revision: 26.02.2025

Product code: AC11.00250

Page 2 of 12

## Further Information

No data available

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Flam. Liq. 2; H225

Eye Irrit. 2; H319

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

## Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



## Hazard statements

H225

Highly flammable liquid and vapour.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

## Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240

Ground and bond container and receiving equipment.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233

Store in a well-ventilated place. Keep container tightly closed.

## 2.3. Other hazards

No data available

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

Sum formula: CH<sub>3</sub>CH(OH)CH<sub>3</sub>

Molecular weight: 60,1 g/mol

## Relevant ingredients

| CAS No  | Chemical name                                         |              |                       | Quantity |
|---------|-------------------------------------------------------|--------------|-----------------------|----------|
|         | EC No                                                 | Index No     | REACH No              |          |
|         | Classification (Regulation (EC) No 1272/2008)         |              |                       |          |
| 67-63-0 | "propan-2-ol; isopropyl alcohol; isopropanol"         |              |                       | 100 %    |
|         | 200-661-7                                             | 603-117-00-0 | 01-2119457558-25-XXXX |          |
|         | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 |              |                       |          |

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**isopropanol (260-000-202)**

Revision: 26.02.2025

Product code: AC11.00250

Page 3 of 12

**Further Information**

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

No data available

**After inhalation**

Provide fresh air.

Call a physician immediately.

**After contact with skin**

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

**After contact with eyes**

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

**After ingestion**

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Irritant

Respiratory complaints

Headache

Dizziness

Dizziness

Inebriation

Anaesthetic state

Unconsciousness

Repeated exposure may cause skin dryness or cracking.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

Beware of reignition.

**5.3. Advice for firefighters**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**isopropanol (260-000-202)**

Revision: 26.02.2025

Product code: AC11.00250

Page 4 of 12

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**6.3. Methods and material for containment and cleaning up****For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## isopropanol (260-000-202)

Revision: 26.02.2025

Product code: AC11.00250

Page 5 of 12

**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment. Use extractor hood (laboratory).  
Do not breathe vapour/aerosol. Provide adequate ventilation.

**Advice on protection against fire and explosion**

Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

Keep away from food, drink and animal feedingstuffs.  
Wash hands and face before breaks and after work and take a shower if necessary.  
When using do not eat or drink.  
Avoid: aerosol or mist formation Do not breathe vapour/aerosol.

**Further information on handling**

Take off immediately all contaminated clothing and wash it before reuse.  
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.  
Store in a cool dry place.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

Take national regulations into account.

**Further information on storage conditions**

Protect from sunlight.  
Protect against: Light  
minimum storage temperature +5°C  
maximum storage temperature +30°C

**7.3. Specific end use(s)**

Laboratory chemicals

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

| CAS No  | Substance   | ppm | mg/m <sup>3</sup> | fib/cm <sup>3</sup> | Category      | Origin |
|---------|-------------|-----|-------------------|---------------------|---------------|--------|
| 67-63-0 | Propan-2-ol | 200 | -                 |                     | TWA (8 h)     |        |
|         |             | 400 | -                 |                     | STEL (15 min) |        |

**Biological limit values**

| CAS No  | Substance  | Parameter | Value   | Test material | Sampling time                   |
|---------|------------|-----------|---------|---------------|---------------------------------|
| 67-63-0 | 2-Propanol | Acetone   | 40 mg/L | Urine         | End of shift at end of workweek |

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## isopropanol (260-000-202)

Revision: 26.02.2025

Product code: AC11.00250

Page 6 of 12

## DNEL/DMEL values

| CAS No                   | Substance                                     |                |          |                  |
|--------------------------|-----------------------------------------------|----------------|----------|------------------|
| DNEL type                |                                               | Exposure route | Effect   | Value            |
| 67-63-0                  | "propan-2-ol; isopropyl alcohol; isopropanol" |                |          |                  |
| Worker DNEL, long-term   |                                               | inhalation     | systemic | 500 mg/m³        |
| Worker DNEL, long-term   |                                               | dermal         | systemic | 888 mg/kg bw/day |
| Consumer DNEL, long-term |                                               | inhalation     | systemic | 89 mg/m³         |
| Consumer DNEL, long-term |                                               | dermal         | systemic | 319 mg/kg bw/day |
| Consumer DNEL, long-term |                                               | oral           | systemic | 26 mg/kg bw/day  |

## PNEC values

| CAS No                                          | Substance                                     |  |
|-------------------------------------------------|-----------------------------------------------|--|
| Environmental compartment                       | Value                                         |  |
| 67-63-0                                         | "propan-2-ol; isopropyl alcohol; isopropanol" |  |
| Freshwater                                      | 140,9 mg/l                                    |  |
| Freshwater (intermittent releases)              | 140,9 mg/l                                    |  |
| Marine water                                    | 140,9 mg/l                                    |  |
| Freshwater sediment                             | 552 mg/kg                                     |  |
| Marine sediment                                 | 552 mg/kg                                     |  |
| Secondary poisoning                             | 160 mg/kg                                     |  |
| Microorganisms in sewage treatment plants (STP) | 2251 mg/l                                     |  |
| Soil                                            | 28 mg/kg                                      |  |

## 8.2. Exposure controls

## Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

goggles

Face protection umbrella

## Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

By long-term hand contact

Trade name/designation: KCL 730 Camatril® Velours

Suitable material: NBR (Nitrile rubber) 0,4 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## isopropanol (260-000-202)

Revision: 26.02.2025

Product code: AC11.00250

Page 7 of 12

Trade name/designation: KCL 720 Camapren®  
Suitable material: CR (polychloroprene, chloroprene rubber) 0,65 mm  
Wearing time with occasional contact (splashes): > 120 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet <(>, <)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Wear fire resistant or flame retardant clothing.  
Take off immediately all contaminated clothing and wash it before reuse.  
Wear suitable protective clothing. Take off immediately all contaminated clothing.  
Wash hands and face before breaks and after work and take a shower if necessary.  
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.  
Filtering device with filter or ventilator filtering device of type: A  
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Environmental exposure controls**

Do not allow to enter into surface water or drains.  
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.  
Danger of explosion

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

|                                                           |                   |
|-----------------------------------------------------------|-------------------|
| Physical state:                                           | Liquid            |
| Colour:                                                   | colourless        |
| Odour:                                                    | like: Alcohol     |
| Melting point/freezing point:                             | -89,5 °C          |
| Boiling point or initial boiling point and boiling range: | 82,5 °C           |
| Flammability:                                             | No data available |
| Lower explosion limits:                                   | 2 vol. %          |
| Upper explosion limits:                                   | 13 vol. %         |
| Flash point:                                              | 11,7 °C           |
| Auto-ignition temperature:                                | 425 °C            |
| Decomposition temperature:                                | No data available |
| pH-Value (at 20 °C):                                      | 7                 |
| Viscosity / kinematic:                                    | No data available |
| Water solubility:                                         | easily soluble    |
| Solubility in other solvents                              | No data available |
| Partition coefficient n-octanol/water:                    | log Pow: 0,05     |
| Vapour pressure:                                          | 44 hPa            |
| (at 20 °C)                                                |                   |
| Vapour pressure:                                          | 76 hPa hPa        |
| (at 50 °C)                                                |                   |

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## isopropanol (260-000-202)

Revision: 26.02.2025

Product code: AC11.00250

Page 8 of 12

|                          |                         |
|--------------------------|-------------------------|
| Density:                 | 0,786 g/cm <sup>3</sup> |
| Bulk density:            | No data available       |
| Relative vapour density: | No data available       |

**9.2. Other information****Information with regard to physical hazard classes**

## Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: Sustained combustibility

## Self-ignition temperature

Solid: No data available

Gas: No data available

## Oxidizing properties

No data available

**Other safety characteristics**

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: No data available

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

Viscosity / dynamic:  
(at 20 °C) 2,2 mPa·s

Flow time: No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Vapours may form explosive mixtures with air.

Formation of: Peroxides

**10.2. Chemical stability**

Protect against:

Light

Air

**10.3. Possibility of hazardous reactions**Oxidising agent, Alkali metals, Alkaline earth metal,  
chromium trioxide, Nitric acid, aldehydesAmines, Aluminium, Chlorine (Cl<sub>2</sub>)

Phosphorus trichloride, Strong acid, Phosgene

Hydrogen peroxide, Nitrogen oxides (NO<sub>x</sub>), Iron.**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Light

Air

**10.5. Incompatible materials**

Rubber articles

Plastic articles

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**isopropanol (260-000-202)**

Revision: 26.02.2025

Product code: AC11.00250

Page 9 of 12

various plastics

**10.6. Hazardous decomposition products**

Peroxides

In case of fire:

SECTION 5: Firefighting measures

**Further information**

Peroxides

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Based on available data, the classification criteria are not met.

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

**Irritation and corrosivity**

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. ("propan-2-ol; isopropyl alcohol; isopropanol")

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards****Other information**

Observe risk of aspiration if vomiting occurs. Pulmonary oedema Pneumonia

Repeated exposure may cause skin dryness or cracking.

**Further information**

No data available

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## isopropanol (260-000-202)

Revision: 26.02.2025

Product code: AC11.00250

Page 10 of 12

| CAS No  | Chemical name                                 |              |           |                             |                    |                       |
|---------|-----------------------------------------------|--------------|-----------|-----------------------------|--------------------|-----------------------|
|         | Aquatic toxicity                              | Dose         | [h]   [d] | Species                     | Source             | Method                |
| 67-63-0 | "propan-2-ol; isopropyl alcohol; isopropanol" |              |           |                             |                    |                       |
|         | Acute fish toxicity                           | LC50<br>mg/l | 10000     | 96 h Pimephales<br>promelas | Publication (1983) | OECD Guideline<br>203 |

**12.2. Persistence and degradability**

95 %; 21 d; aerob

OECD-301E

Readily biodegradable (according to OECD criteria).

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

**Partition coefficient n-octanol/water**

| CAS No  | Chemical name                                 | Log Pow |
|---------|-----------------------------------------------|---------|
| 67-63-0 | "propan-2-ol; isopropyl alcohol; isopropanol" | 0,05    |

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**12.7. Other adverse effects**

Avoid release to the environment.

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

The waste code has to be identified in agreement with the disposal company or the competent authority.

**SECTION 14: Transport information****Land transport (ADR/RID)**

|                                          |                                 |
|------------------------------------------|---------------------------------|
| <b>14.1. UN number or ID number:</b>     | UN 1219                         |
| <b>14.2. UN proper shipping name:</b>    | ISOPROPANOL (ISOPROPYL ALCOHOL) |
| <b>14.3. Transport hazard class(es):</b> | 3                               |
| <b>14.4. Packing group:</b>              | II                              |
| Hazard label:                            | 3                               |
| Classification code:                     | F1                              |
| Special Provisions:                      | 601                             |
| Limited quantity:                        | 1 L                             |
| Excepted quantity:                       | E2                              |
| Transport category:                      | 2                               |
| Hazard No:                               | 33                              |

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## isopropanol (260-000-202)

Revision: 26.02.2025

Product code: AC11.00250

Page 11 of 12

Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3  
Classification code: F1  
Special Provisions: 601  
Limited quantity: 1 L  
Excepted quantity: E2

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3  
Special Provisions: -  
Limited quantity: 1 L  
Excepted quantity: E2  
EmS: F-E, S-D

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1219  
**14.2. UN proper shipping name:** ISOPROPANOL (ISOPROPYL ALCOHOL)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** II  
Hazard label: 3  
Special Provisions: A180  
Limited quantity Passenger: 1 L  
Passenger LQ: Y341  
Excepted quantity: E2  
IATA-packing instructions - Passenger: 353  
IATA-max. quantity - Passenger: 5 L  
IATA-packing instructions - Cargo: 364  
IATA-max. quantity - Cargo: 60 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III):

P5c FLAMMABLE LIQUIDS

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

1 - slightly hazardous to water

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**isopropanol (260-000-202)**

Revision: 26.02.2025

Product code: AC11.00250

Page 12 of 12

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,9,13.

**Abbreviations and acronyms**

Flam. Liq. 2: Flammable liquids, hazard category 2

Eye Irrit. 2: Eye irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

**Relevant H and EUH statements (number and full text)**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.