

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Diethylether v.p.

Revision: 03.12.2025

Product code: AC11.00310

Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Diethylether v.p.

REACH Registration Number: 01-2119535785-29-XXXX  
CAS No: 60-29-7  
Index No: 603-022-00-4  
EC No: 200-467-2

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Reagents and laboratory chemicals  
Only for laboratory and analysis purposes.

#### Uses advised against

Do not use for private purposes (household).

### 1.3. Details of the supplier of the safety data sheet

#### Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda  
Street: Rua de Júlio Dinis 676 7º  
Place: N-4050-320 Porto  
Telephone: +351 226002917  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: SDS service department

#### Supplier or manufacturer details

Company name: AnalytiChem Belgium NV  
Street: Industriezone "De Arend" 2  
Place: B-8210 Zedelgem  
Telephone: +32 50 28 83 20  
E-mail: info.be@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Responsible Department: AnalytiChem:  
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333  
+353 1 901 4670 (CHEMTREC)

### 1.4. Emergency telephone number:

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Diethylether v.p.

Revision: 03.12.2025

Product code: AC11.00310

Page 2 of 13

## Further Information

No data available

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

## Regulation (EC) No 1272/2008

Flam. Liq. 1; H224

Acute Tox. 4; H302

STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

## 2.2. Label elements

## Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



## Hazard statements

H224 Extremely flammable liquid and vapour.

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

## Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P403+P235 Store in a well-ventilated place. Keep cool.

## Special labelling of certain mixtures

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

Sum formula: (C<sub>2</sub>H<sub>5</sub>)<sub>2</sub>O

Molecular weight: 74,12 g/mol

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Diethylether v.p.

Revision: 03.12.2025

Product code: AC11.00310

Page 3 of 13

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
60-29-7	diethyl ether			100 %
	200-467-2	603-022-00-4	01-2119535785-29-XXXX	
	Flam. Liq. 1, Acute Tox. 4, STOT SE 3; H224 H302 H336 EUH019 EUH066			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
60-29-7	200-467-2	diethyl ether	100 %
		inhalation: LC50 = 32000 mg/l (vapours); dermal: LD50 = > 20000 mg/kg; oral: LD50 = 1600 mg/kg	

## Further Information

No data available

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

## General information

No data available

## After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

## After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

## After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Remove contact lenses, if present and easy to do. Continue rinsing.

## After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

Irritant

Respiratory complaints

Vapours may cause drowsiness and dizziness.

Unconsciousness

Circulatory collapse

Dizziness

Inebriation

death

## 4.3. Indication of any immediate medical attention and special treatment needed

No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Diethylether v.p.**

Revision: 03.12.2025

Product code: AC11.00310

Page 4 of 13

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>)  
Foam  
Extinguishing powder

**Unsuitable extinguishing media**

no restriction

**5.2. Special hazards arising from the substance or mixture**

Combustible liquid.  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Hazardous combustion products  
In case of fire may be liberated:  
Carbon dioxide (CO<sub>2</sub>) Carbon monoxide  
Beware of reignition.

**5.3. Advice for firefighters**

Remove persons to safety. Do not inhale explosion and combustion gases.  
Avoid contact with skin, eyes and clothes.  
In case of fire: Wear self-contained breathing apparatus.  
Use water spray jet to protect personnel and to cool endangered containers.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.  
Suppress gases/vapours/mists with water spray jet.  
Move undamaged containers from immediate hazard area if it can be done safely.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.  
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).  
Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Consult an expert  
Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.  
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in high concentration.  
Danger of explosion

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Diethylether v.p.**

Revision: 03.12.2025

Product code: AC11.00310

Page 5 of 13

**6.3. Methods and material for containment and cleaning up****For containment**

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

- Clean contaminated articles and floor according to the environmental legislation.

**Other information**

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

**Advice on protection against fire and explosion**

- Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

- Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.
- The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Further information on handling**

- Take off immediately all contaminated clothing and wash it before reuse.
- If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Draw up and observe skin protection programme.
- Wash hands and face before breaks and after work and take a shower if necessary.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

- Keep container tightly closed. Keep container dry.
- Keep in a cool, well-ventilated place.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Protect against: Light

**Hints on joint storage**

- Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.
- national regulations

**Further information on storage conditions**

- Vapours may form explosive mixtures with air.
- storage temperature +2°C - +8°C

**Diethylether v.p.**

Revision: 03.12.2025

Product code: AC11.00310

Page 6 of 13

**7.3. Specific end use(s)**

Laboratory use Laboratory chemical

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fib/cm <sup>3</sup>	Category	Origin
60-29-7	Ethyl ether	100	308		TWA (8 h)	
		200	616		STEL (15 min)	

**DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
60-29-7	diethyl ether			
Worker DNEL, long-term		inhalation	systemic	308 mg/m <sup>3</sup>
Worker DNEL, acute		inhalation	systemic	616 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	44 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	54,5 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	15,6 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	15,6 mg/kg bw/day

**PNEC values**

CAS No	Substance	
Environmental compartment		Value
60-29-7	diethyl ether	
Freshwater		2 mg/l
Freshwater (intermittent releases)		1,65 mg/l
Marine water		0,2 mg/l
Freshwater sediment		9,14 mg/kg
Marine sediment		0,914 mg/kg
Micro-organisms in sewage treatment plants (STP)		4,2 mg/l
Soil		0,66 mg/kg

**8.2. Exposure controls****Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: goggles.

**Hand protection**

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: [vertrieb@kcl.de](mailto:vertrieb@kcl.de) With specification (test according to EN374):

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Diethylether v.p.**

Revision: 03.12.2025

Product code: AC11.00310

Page 7 of 13

By long-term hand contact: No data available

By short-term hand contact

Trade name/designation KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with occasional contact (splashes): > 30 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<)> supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

**Skin protection**

Flame-retardant protective clothing. Wear anti-static footwear and clothing

**Respiratory protection**

In case of inadequate ventilation wear respiratory protection.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Filtering device with filter or ventilator filtering device of type: AX

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

**Environmental exposure controls**

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	-116,3 °C
Boiling point or initial boiling point and boiling range:	34,6 °C
Flammability:	not applicable
Lower explosion limits:	1,7 vol. %
Upper explosion limits:	36 vol. %
Flash point:	-40 °C
Auto-ignition temperature:	180 °C
Decomposition temperature:	not determined
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility: (at 20 °C)	69 g/l
Solubility in other solvents	not determined
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Diethylether v.p.

Revision: 03.12.2025

Product code: AC11.00310

Page 8 of 13

Vapour pressure: (at 20 °C)	716 hPa
Vapour pressure:	No data available
Density:	0,71 g/cm <sup>3</sup>
Bulk density:	No data available
Relative vapour density:	not determined
Particle characteristics:	No data available

#### 9.2. Other information

##### Information with regard to physical hazard classes

###### Explosive properties

Vapours can form explosive mixtures with air.

###### Sustained combustibility:

Sustained combustibility

###### Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

###### Oxidizing properties

Not oxidising.

##### Other safety characteristics

###### Evaporation rate:

not determined

###### Solvent separation test:

No data available

###### Solvent content:

No data available

###### Solid content:

not determined

###### Sublimation point:

No data available

###### Softening point:

No data available

###### Pour point:

No data available

No data available:

###### Viscosity / dynamic:

0,23 mPa·s

(at 20 °C)

###### Flow time:

No data available

##### Further Information

May form explosive peroxides.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable.

Vapours can form explosive mixtures with air.

Protect against: Light

May form explosive peroxides.

### 10.2. Chemical stability

Protect against:

Light

Air

### 10.3. Possibility of hazardous reactions

Peroxides, Oxidizing agent, peroxides, for example hydrogen peroxide, Nitric acid, Oxygen, sulphuric acid Acid halides

(Diethyl ether) Explosive hazard with: azides, halogens, halogen-halogen compounds, non-metals, non-metal oxide halides, strong oxidising agents, chromium(VI) oxide, halogen oxides, peroxide compounds, perchloric acid, perchlorates, nitric acid, nitrous acid, oxygen, ozone, turpentine oils and/or substitutes for turpentine oil, nitrates, metal chlorides; fire hazard or formation of flammable gases or vapours with: chromyl chloride, peroxides.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Diethylether v.p.

Revision: 03.12.2025

Product code: AC11.00310

Page 9 of 13

**10.4. Conditions to avoid**

Light

Air

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

plastic and rubber

**10.6. Hazardous decomposition products**

Peroxides

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide**Further information**

No data available

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

No data available

**Acute toxicity**

Harmful if swallowed.

Resorption (by inhalation)

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
60-29-7	diethyl ether				
	oral	LD50 1600 mg/kg	Rat	Toxicology and applied pharmacology, 197	OECD Guideline 401
	dermal	LD50 > 20000 mg/kg	Rabbit	Am. Ind. Hyg. Assoc. J., 1962, 23, 95-10	OECD Guideline 402
	inhalation (4 h) vapour	LC50 32000 mg/l	Rat	Am. Ind. Hyg. Assoc. J., 1962, 23, 95-10	Test animals are exposed to metered vapo

**Irritation and corrosivity**

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness. (diethyl ether)

**Diethylether v.p.**

Revision: 03.12.2025

Product code: AC11.00310

Page 10 of 13

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

No data available

**Specific effects in experiment on an animal**

No data available

**Additional information on tests**

No data available

**Practical experience**

No data available

**11.2. Information on other hazards****Endocrine disrupting properties**

No data available

**Other information**

The product causes narcotic-like effects.

**Further information**

Irritant

Respiratory complaints

Vapours may cause drowsiness and dizziness.

Unconsciousness

Circulatory collapse

Dizziness

Inebriation

death

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
60-29-7	diethyl ether					
	Acute fish toxicity	LC50 2560 mg/l	96 h	Pimephales promelas	Acute toxicities of organic chemicals to	other: American Society for Testing and
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2010)	OECD Guideline 201
	Crustacea toxicity	NOEC 100 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211
	Acute bacteria toxicity	EC50 26000 mg/l ( )	3 h	activated sludge of a predominantly domestic sewage	Study report (2010)	OECD Guideline 209

**12.2. Persistence and degradability**

Not readily biodegradable (according to OECD criteria)

**12.3. Bioaccumulative potential**

No indication of bioaccumulation potential.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Diethylether v.p.

Revision: 03.12.2025

Product code: AC11.00310

Page 11 of 13

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
60-29-7	diethyl ether	1,05

## BCF

CAS No	Chemical name	BCF	Species	Source
60-29-7	diethyl ether	2	not applicable	Other company data (

**12.4. Mobility in soil**

No information available.

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**12.7. Other adverse effects**

No data available

**Further information**

Avoid release to the environment.

Do not empty into drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains.

Send to a physico-chemical treatment facility under observation of official regulations.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**Contaminated packaging**

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Handle contaminated packages in the same way as the substance itself.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1155
<b>14.2. UN proper shipping name:</b>	DIETHYL ETHER (ETHYL ETHER)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	I
Hazard label:	3
Classification code:	F1
Limited quantity:	0
Excepted quantity:	E3
Transport category:	1
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1155
<b>14.2. UN proper shipping name:</b>	DIETHYL ETHER (ETHYL ETHER)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	I
Hazard label:	3

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Diethylether v.p.

Revision: 03.12.2025

Product code: AC11.00310

Page 12 of 13

Classification code: F1  
Limited quantity: 0  
Excepted quantity: E3

#### Marine transport (IMDG)

**14.1. UN number or ID number:** UN 1155  
**14.2. UN proper shipping name:** DIETHYL ETHER (ETHYL ETHER)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** I  
Hazard label: 3  
Special Provisions: -  
Limited quantity: 0  
Excepted quantity: E3  
EmS: F-E, S-D

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** UN 1155  
**14.2. UN proper shipping name:** DIETHYL ETHER (ETHYL ETHER)  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** I  
Hazard label: 3  
Limited quantity Passenger: Forbidden  
Passenger LQ: Forbidden  
Excepted quantity: E3  
IATA-packing instructions - Passenger: 351  
IATA-max. quantity - Passenger: 1 L  
IATA-packing instructions - Cargo: 361  
IATA-max. quantity - Cargo: 30 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Warning: Combustible liquid.

#### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):  
Entry 3, Entry 40

Information according to Directive 2012/18/EU (SEVESO III): P5a FLAMMABLE LIQUIDS

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Diethylether v.p.**

Revision: 03.12.2025

Product code: AC11.00310

Page 13 of 13

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 1,9.

**Abbreviations and acronyms**

Flam. Liq. 1: Flammable liquids, hazard category 1

Acute Tox. 4: Acute toxicity, hazard category 4

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

**Relevant H and EUH statements (number and full text)**

H224 Extremely flammable liquid and vapour.

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.