

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 1 of 14

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Potassium hydroxide 0.2 mol/l in Ethanol

UFI: HFJJ-9225-VWCC-D7D8

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

**Uses advised against**

Do not use for private purposes (household).

**1.3. Details of the supplier of the safety data sheet****Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda  
Street: Rua de Júlio Dinis 676 7º  
Place: N-4050-320 Porto  
Telephone: +351 226002917  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: SDS service department

**Supplier or manufacturer details**

Company name: AnalytiChem Belgium NV  
Street: Industriezone "De Arend" 2  
Place: B-8210 Zedelgem  
Telephone: +32 50 28 83 20  
E-mail: info.be@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Responsible Department: AnalytiChem  
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333

**1.4. Emergency telephone****number:**

+44 20 3807 3798 (CHEMTREC)

**Further Information**

inapplicable, this product is a mixture REACH registration number see section 3

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 2 of 14

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 2; H225

Met. Corr. 1; H290

Skin Corr. 1; H314

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

**2.2. Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

ethanol

"propan-2-ol; isopropyl alcohol; isopropanol"

potassium hydroxide

**Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.

**Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands and face thoroughly after handling.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures**

## Potassium hydroxide 0.2 mol/l in Ethanol

Revision: 10.12.2025

Product code: AC15.00473

Page 3 of 14

## Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64-17-5	ethanol			95 - < 100 %
	200-578-6	603-002-00-5	01-2119457610-43	
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"			1 - < 5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
1310-58-3	potassium hydroxide			0.5 - < 2 %
	215-181-3	019-002-00-8	01-2119487136-33	
	Met. Corr. 1, Acute Tox. 4, Skin Corr. 1A, Eye Dam. 1; H290 H302 H314 H318			

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64-17-5	200-578-6	ethanol	95 - < 100 %
	inhalation: LC50 = 124,7 mg/l (vapours); oral: LD50 = 10470 mg/kg Eye Irrit. 2; H319: >= 50 - 100		
1310-58-3	215-181-3	potassium hydroxide	0.5 - < 2 %
	oral: LD50 = 333 mg/kg Skin Corr. 1A; H314: >= 5 - 100 Skin Corr. 1B; H314: >= 2 - < 5 Skin Irrit. 2; H315: >= 0,5 - < 2 Eye Irrit. 2; H319: >= 0,5 - < 2		

## Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## SECTION 4: First aid measures

4.1. Description of first aid measures

## General information

Take off immediately all contaminated clothing and wash it before reuse.

## After inhalation

Provide fresh air.

If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

## After contact with skin

Wash immediately with: Water

Take off immediately all contaminated clothing and wash it before reuse.

Call a physician immediately.

## After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

## After ingestion

Rinse mouth immediately and drink plenty of water.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 4 of 14

**4.2. Most important symptoms and effects, both acute and delayed**

No data available

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Water spray jet, Carbon dioxide (CO<sub>2</sub>), Foam, Extinguishing powder.**Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

Combustible liquids Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO<sub>2</sub>) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

Corrosive to metals.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

Danger of explosion

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 5 of 14

**6.3. Methods and material for containment and cleaning up****For containment**

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**For cleaning up**

- Clean contaminated articles and floor according to the environmental legislation.

**Other information**

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**6.4. Reference to other sections**

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

**Advice on protection against fire and explosion**

- Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Advice on general occupational hygiene**

- Keep away from food, drink and animal feedingstuffs.
- The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

**Further information on handling**

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

- Keep in a cool, well-ventilated place.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints on joint storage**

- Take national regulations into account. /National regulations

**Further information on storage conditions**

- Keep cool. Protect from sunlight.

**7.3. Specific end use(s)**

- Laboratory chemicals

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

## Potassium hydroxide 0.2 mol/l in Ethanol

Revision: 10.12.2025

Product code: AC15.00473

Page 6 of 14

## Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
1310-58-3	Potassium hydroxide	-	2		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

## DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64-17-5	ethanol			
	Worker DNEL, long-term	inhalation	systemic	950 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	343 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	114 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	206 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	87 mg/kg bw/day
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"			
	Worker DNEL, long-term	inhalation	systemic	500 mg/m <sup>3</sup>
	Worker DNEL, long-term	dermal	systemic	888 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	89 mg/m <sup>3</sup>
	Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day
1310-58-3	potassium hydroxide			
	Worker DNEL, long-term	inhalation	local	1 mg/m <sup>3</sup>
	Consumer DNEL, long-term	inhalation	local	1 mg/m <sup>3</sup>

## Potassium hydroxide 0.2 mol/l in Ethanol

Revision: 10.12.2025

Product code: AC15.00473

Page 7 of 14

## PNEC values

CAS No	Substance	
		Value
64-17-5	ethanol	
Freshwater		0,96 mg/l
Freshwater (intermittent releases)		2,75 mg/l
Marine water		0,79 mg/l
Freshwater sediment		3,6 mg/kg
Marine sediment		2,9 mg/kg
Secondary poisoning		380 mg/kg
Micro-organisms in sewage treatment plants (STP)		580 mg/l
Soil		0,63 mg/kg
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Secondary poisoning		160 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

## Additional advice on limit values

Observe in addition any national regulations!

**8.2. Exposure controls****Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

goggles

Face protection umbrella

**Hand protection**

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Skin protection**

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

**Respiratory protection**

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 8 of 14

carried out according to the instructions of the producer. These measures have to be properly documented.

**Thermal hazards**

No data available

**Environmental exposure controls**

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour threshold:	No data available
Melting point/freezing point:	~117 °C
Boiling point or initial boiling point and boiling range:	~78 °C
Flammability:	No data available
Lower explosion limits:	not determined
Upper explosion limits:	not determined
Flash point:	12 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	alkaline
Viscosity / kinematic:	No data available
Solubility in other solvents	
not determined	
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,81424 g/cm <sup>3</sup>
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

**9.2. Other information****Information with regard to physical hazard classes****Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

**Other safety characteristics**

Evaporation rate:

not determined

Solvent separation test:

No data available

Solvent content:

No data available

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 9 of 14

Solid content:	0
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
Viscosity / dynamic:	No data available
Flow time:	No data available

**Further Information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

Corrosive to metals. Highly flammable.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Oxidising agent

**10.4. Conditions to avoid**

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

**10.5. Incompatible materials**

various plastics

Metal

**10.6. Hazardous decomposition products**

SECTION 5: Firefighting measures

**Further information**

No data available

**SECTION 11: Toxicological information****11.1. Information on hazard classes****Toxicokinetics, metabolism and distribution**

There are no data available on the mixture itself.

**Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (oral) &gt; 5000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 10 of 14

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
64-17-5	ethanol					
	oral	LD50 mg/kg	10470 Rat	Study report (1976)	OECD Guideline 401	
	inhalation (4 h) vapour	LC50 mg/l	124,7 Rat	Study report (1980)	OECD Guideline 403	
1310-58-3	potassium hydroxide					
	oral	LD50 mg/kg	333 Rat	Fund. Appl. Toxicol., 8, 97-100 (1987)	OECD Guideline 425	

**Irritation and corrosivity**

Skin corrosion/irritation: Causes severe skin burns and eye damage. (On basis of test data)

Serious eye damage/eye irritation: Causes serious eye damage. (On basis of test data)

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Information on likely routes of exposure**

There are no data available on the mixture itself.

**Specific effects in experiment on an animal**

There are no data available on the mixture itself.

**Additional information on tests**

There are no data available on the mixture itself.

**Practical experience**

There are no data available on the mixture itself.

**11.2. Information on other hazards****Endocrine disrupting properties**

There are no data available on the mixture itself.

**Other information**

There are no data available on the mixture itself.

**Further information**

There are no data available on the mixture itself.

**SECTION 12: Ecological information****12.1. Toxicity**

Based on available data, the classification criteria are not met.

## Potassium hydroxide 0.2 mol/l in Ethanol

Revision: 10.12.2025

Product code: AC15.00473

Page 11 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64-17-5	ethanol					
	Acute fish toxicity	LC50 15400 mg/l	96 h	Lepomis macrochirus	Bulletin of Environmental Contamination	other: EPA-660/3-75-00 9, 1975
	Acute algae toxicity	ErC50 ca. 22000 mg/l	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201
	Acute crustacea toxicity	EC50 > 10000 mg/l	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	other: DIN 38412 Teil 11
	Algae toxicity	NOEC 5400 mg/l	5 d	Skeletonema costatum	Environ Toxicol Chem 8(5):451-455. (1989)	Study to determine the sensitivity of a
	Crustacea toxicity	NOEC 2 mg/l	10 d	Ceriodaphnia dubia	Arch Environ Contam Toxicol 20(2):211-21	Follows the basic methodology for the th
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"					
	Acute fish toxicity	LC50 10000 mg/l	96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203

**12.2. Persistence and degradability**

There are no data available on the mixture itself.

**12.3. Bioaccumulative potential**

There are no data available on the mixture itself.

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
64-17-5	ethanol	-0,77
67-63-0	"propan-2-ol; isopropyl alcohol; isopropanol"	0,05

**BCF**

CAS No	Chemical name	BCF	Species	Source
64-17-5	ethanol	1	Cyprinus carpio	Comparative Biochemi

**12.4. Mobility in soil**

There are no data available on the mixture itself.

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 12 of 14

**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.  
Send to a physico-chemical treatment facility under observation of official regulations.  
Do not empty into drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.  
The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	338
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Classification code:	FC
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-E, S-C

**Air transport (ICAO-TI/ATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 2924
<b>14.2. UN proper shipping name:</b>	FLAMMABLE LIQUID, CORROSIVE, N.O.S. (ethanol, potassium hydroxide)
<b>14.3. Transport hazard class(es):</b>	3

**Potassium hydroxide 0.2 mol/l in Ethanol**

Revision: 10.12.2025

Product code: AC15.00473

Page 13 of 14

<b>14.4. Packing group:</b>	II
Hazard label:	3+8
Special Provisions:	A3
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y340
Excepted quantity:	E2
IATA-packing instructions - Passenger:	352
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	363
IATA-max. quantity - Cargo:	5 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**14.6. Special precautions for user**

Warning: Combustible liquid. strongly corrosive.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

**Additional information**

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 2,5,7,8,9,11,15.

## Potassium hydroxide 0.2 mol/l in Ethanol

Revision: 10.12.2025

Product code: AC15.00473

Page 14 of 14

## Abbreviations and acronyms

Met. Corr. 1: Corrosive to metals, hazard category 1  
Flam. Liq. 2: Flammable liquids, hazard category 2  
Acute Tox. 4: Acute toxicity, hazard category 4  
Skin Corr. 1A: Skin corrosion, sub-category 1A  
Skin Corr. 1: Skin corrosion, hazard category 1  
Eye Dam. 1: Serious eye damage, hazard category 1  
Eye Irrit. 2: Eye irritation, hazard category 2  
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3  
ADR: Accord européen sur le transport des marchandises dangereuses par Route  
(European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service  
LC50: Lethal concentration, 50%  
LD50: Lethal dose, 50%

## Classification for mixtures and used evaluation method

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Met. Corr. 1; H290	On basis of test data
Skin Corr. 1; H314	On basis of test data
Eye Dam. 1; H318	On basis of test data

## Relevant H and EUH statements (number and full text)

H225                    Highly flammable liquid and vapour.  
H290                    May be corrosive to metals.  
H302                    Harmful if swallowed.  
H314                    Causes severe skin burns and eye damage.  
H318                    Causes serious eye damage.  
H319                    Causes serious eye irritation.  
H336                    May cause drowsiness or dizziness.

## Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*