

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 1 of 9

1. Identification

Product identifier

CONOSTAN Element Blank Oil, 75 Viscosity

Substance name: White mineral oil, petroleum

CAS No: 8042-47-5

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals

Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda

Street: Rua de Júlio Dinis 676 7º

Place: P-4050-320 Porto

Telephone: +351 226002917

E-mail: info@analytichem.com

Contact person: SDS service department

E-mail: SDS@analytichem.com

Internet: www.analytichem.com

Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Canada Inc.

Québec, CANADA

Street: 21800 Clark Graham Ave

Place: CDN-H9X 4B6 Baie-D'Urfé

Telephone: +1 (800) 361-6820

Telefax: +1 (800) 253-5549

E-mail: info@analytichem.com

Contact person: SDS service department

E-mail: SDS@analytichem.com

Internet: www.analytichem.com

Responsible Department: AnalytiChem:

EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20

EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200

EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848

UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500

USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378

Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701

Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333

Emergency telephone number: +1 703-741-5970 (CHEMTREC)

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 2 of 9

Further Information

No data available

2. Hazard identification

Classification of the substance or mixture

WHMIS 2015

This substance is not classified as hazardous in accordance with WHMIS.

Label elements

Other hazards

No data available

3. Composition/information on ingredients

Substances

Relevant ingredients

CAS No	Chemical name	Quantity
8042-47-5	White mineral oil, petroleum	80 - 100 % (*)

(*) The actual concentration is withheld as a trade secret.

Further Information

No data available

4. First-aid measures

Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water, Soap

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth.

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

Most important symptoms and effects, whether acute or delayed

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 3 of 9

Indication of immediate medical attention and special treatment needed

No data available

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Foam
Carbon dioxide (CO₂)
Extinguishing powder
Water

Unsuitable extinguishing media

no restriction

Specific hazards arising from the hazardous product

Combustible liquids
Hazardous combustion products
In case of fire may be liberated:
Carbon dioxide (CO₂)
Carbon monoxide
In case of warming:
Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Use water spray jet to protect personnel and to cool endangered containers.
Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

In case of warming:
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Take precautionary measures against static discharges.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

Environmental precautions

Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up

For containment

Cover drains.
Prevent spread over a wide area (e.g. by containment or oil barriers).

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 4 of 9

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Collect in closed and suitable containers for disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment. Use extractor hood (laboratory).

Do not breathe vapour/aerosol.

Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

National regulations

Further information on storage conditions

Keep cool. Protect from sunlight.

8. Exposure controls/Personal protection

Control parameters

Safety Data Sheet

according to WHMIS

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 5 of 9

Exposure limits (ACGIH)

CAS No	Chemical name	ppm	mg/m ³	Category	Origin
-	Mineral oil, excluding metal working fluids (inhalable fraction); Pure, highly and severely refined		5	TWA (8 h)	ACGIH-2025

Additional advice on limit values

Observe in addition any national regulations!

Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless, clear
Odour:	like: Hydrocarbons
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	218-800 (424.4-1472°F) °C
Flammability:	No data available
Lower explosive limits:	No data available
Upper explosive limits:	No data available
Flash point:	No data available

Safety Data Sheet

according to WHMIS

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 6 of 9

Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	~75 mm ² /s
Water solubility:	No data available
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

No data available

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

10. Stability and reactivity

Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 7 of 9

Oxidising agent

Conditions to avoid

Heat

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials

No data available

Hazardous decomposition products

in case of fire, see:

SECTION 5: Firefighting measures

Further information

No data available

11. Toxicological information

Information on toxicological effects

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
8042-47-5	White mineral oil, petroleum				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 8 of 9

Practical experience

No data available

Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

12. Ecological information

Persistence and degradability

No data available

Mobility in soil

No data available

Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

14. Transport information

Canadian TDG

Proper shipping name:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

UN number or ID number:

No dangerous good in sense of this transport regulation.

United Nations proper shipping name:

No dangerous good in sense of this transport regulation.

Transport hazard class(es):

No dangerous good in sense of this transport regulation.

Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number:

No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to WHMIS

CONOSTAN Element Blank Oil, 75 Viscosity

Revision: 05.12.2025

Product code: AC18.04861

Page 9 of 9

United Nations proper shipping

No dangerous good in sense of this transport regulation.

name:

Transport hazard class(es):

No dangerous good in sense of this transport regulation.

Packing group:

No dangerous good in sense of this transport regulation.

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

15. Regulatory information

Canadian regulations

16. Other information

Changes

This data sheet contains changes from the previous version in section(s): 9.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users