

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 1 of 13

1. Identification
Product identifier

CONOSTAN® Custom Blend Standard

Relevant identified uses of the substance or mixture and uses advised against
Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

Details of the supplier of the safety data sheet
Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Canada Inc.
Québec, CANADA
Street: 21800 Clark Graham Ave
Place: CDN-H9X 4B6 Baie-D'Urfé
Telephone: +1 (800) 361-6820 Telefax: +1 (800) 253-5549
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
Emergency telephone number: +1 703-741-5970 (CHEMTREC)

Further Information

No data available

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 2 of 13

2. Hazard identification

Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Repr. 2; H361d
Skin Irrit. 2; H315
STOT SE 3; H336
STOT RE 2; H373
Asp. Tox. 1; H304
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling
toluene

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing and eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P403+P235	Store in a well-ventilated place. Keep cool.

Other hazards

No data available

3. Composition/information on ingredients

Mixtures

Chemical characterization

Hydrocarbons, aromatic

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 3 of 13

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
108-88-3	toluene			95 - < 100 %
	203-625-9	601-021-00-3	01-2119471310-51	
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H361d H315 H336 H373 H304 H412			

Full text of H statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
108-88-3	203-625-9	toluene	95 - < 100 %
	inhalation: LC50 = 28,1 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 5580 mg/kg		

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

4. First-aid measures

Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a physician immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.
Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs.
Call a physician immediately.

Most important symptoms and effects, whether acute or delayed

Irritant, Headache
Dizziness, Dizziness
Vomiting, Inebriation
Spasms, Circulatory collapse
Respiratory complaints, Dyspnoea
Unconsciousness

Indication of immediate medical attention and special treatment needed

No data available

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 4 of 13

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Foam.
Extinguishing powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media

no restriction

Specific hazards arising from the hazardous product

Combustible liquids
Beware of reignition.
Hazardous combustion products
In case of fire may be liberated:
Carbon dioxide (CO₂), Carbon monoxide
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Heating causes rise in pressure with risk of bursting.

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.
In case of fire and/or explosion do not breathe fumes.
Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Move undamaged containers from immediate hazard area if it can be done safely.
Use water spray jet to protect personnel and to cool endangered containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Keep away from sources of ignition - No smoking.
This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).
Take action to prevent static discharges.

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Avoid contact with skin, eyes and clothes.
Remove persons to safety.
Emergency procedures
Consult an expert
Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

Environmental precautions

Do not allow to enter into surface water or drains.
The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in high concentration.
Danger of explosion

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 5 of 13

Methods and material for containment and cleaning up

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

- Avoid exposure - obtain special instructions before use.
- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment. Use extractor hood (laboratory).
- Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

- Take action to prevent static discharges. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

- Keep away from food, drink and animal feedingstuffs.
- Draw up and observe skin protection programme.
- The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

- Take off immediately all contaminated clothing and wash it before reuse.
- Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.
- Store in a place accessible by authorized persons only.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep in a cool, well-ventilated place.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.

Hints on joint storage

- Take national regulations into account.

Further information on storage conditions

- Keep cool. Protect from sunlight.

Specific end use(s)

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 6 of 13

Laboratory chemicals
Only for laboratory and analysis purposes.

8. Exposure controls/Personal protection

Control parameters

Exposure limits (ACGIH)

CAS No	Chemical name	ppm	mg/m³	Category	Origin
108-88-3	Toluene	20	-	TWA (8 h)	ACGIH-2025

Biological limit values

CAS No	Chemical name	Parameter	Value	Test material	Sampling time
108-88-3	TOLUENE (ACGIH 2025)	Toluene	0.02 mg/L	blood	Prior to last shift of workweek

DNEL/DMEL values

CAS No	Chemical name	Exposure route	Effect	Value
108-88-3	toluene			
Worker DNEL, long-term	inhalation	systemic	192 mg/m³	
Worker DNEL, acute	inhalation	systemic	384 mg/m³	
Worker DNEL, long-term	inhalation	local	192 mg/m³	
Worker DNEL, acute	inhalation	local	384 mg/m³	
Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day	
Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m³	
Consumer DNEL, acute	inhalation	systemic	226 mg/m³	
Consumer DNEL, long-term	inhalation	local	56,5 mg/m³	
Consumer DNEL, acute	inhalation	local	226 mg/m³	
Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day	
Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day	

PNEC values

CAS No	Chemical name	Value
108-88-3	toluene	
Freshwater		0,68 mg/l
Freshwater (intermittent releases)		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg

Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 7 of 13

equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

Tested protective gloves must be worn. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wear fire resistant or flame retardant clothing.

Wash hands and face before breaks and after work and take a shower if necessary.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Danger of explosion

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	clear
Odour:	like: Hydrocarbons, aromatic
Odour threshold:	No data available
Melting point/freezing point:	-95 °C
Boiling point or initial boiling point and boiling range:	110,6 °C
Flammability:	No data available
Lower explosive limits:	1,1 vol. %
Upper explosive limits:	7,1 vol. %
Flash point:	4,4 °C
Auto-ignition temperature:	480 °C
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic: (at 20 °C)	0,7 mm²/s
Water solubility: (at 20 °C)	0,52 g/l
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	log Pow: 2,65

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 8 of 13

Dispersion stability:	No data available
Vapour pressure:	29,3 hPa
(at 20 °C)	
Vapour pressure:	123 hPa
(at 50 °C)	
Density:	0,87 g/cm³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

Other information

Information with regard to physical hazard classes

Explosive properties

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: Sustained combustibility

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: 100,00 %

Solid content: 0

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

No data available

Viscosity / dynamic: 0,6 mPa·s

(at 20 °C)

Flow time: No data available

Further Information

No data available

10. Stability and reactivity

Reactivity

Vapours may form explosive mixtures with air.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Oxidising agent

Nitric acid

Acetic acid

Strong acid

silver

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 9 of 13

Incompatible materials

Plastic articles

Rubber articles

Hazardous decomposition products

in case of fire, see:

SECTION 5: Firefighting measures

Further information

No data available

11. Toxicological information

Information on toxicological effects

Toxicokinetics, metabolism and distribution

Avoid exposure - obtain special instructions before use.

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation to respiratory tract

Resorption (by inhalation)

Resorption (dermal)

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
108-88-3	toluene				
	oral	LD50 5580 mg/kg	Rat	Toxicology 4, 5-15 (1975)	EU Method B.1
	dermal	LD50 > 5000 mg/kg	Rabbit	American Industrial Hygiene Association	Study investigated mortality in groups o
	inhalation (4 h) vapour	LC50 28,1 mg/l	Rat	Study report (1980)	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (toluene)

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (toluene)

Aspiration hazard

May be fatal if swallowed and enters airways.

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 10 of 13

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Further information

Irritant, Headache
Dizziness, Dizziness
Vomiting, Inebriation
Spasms, Circulatory collapse
Respiratory complaints, Dyspnoea
Unconsciousness

12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-88-3	toluene					
	Acute fish toxicity	LC50 5,5 mg/l	96 h	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Acute algae toxicity	ErC50 mg/l > 433	96 h	Pseudokirchneriella subcapitata	REACH Registration Dossier	Method: other
	Acute crustacea toxicity	EC50 11,5 mg/l	48 h	Daphnia magna	REACH Registration Dossier	Method: other
	Fish toxicity	NOEC mg/l 1,39	40 d	Oncorhynchus kisutch	Transactions A. Fish. Soc. 110, 430-436.	Fry were exposed to toluene in a flow th
	Algae toxicity	NOEC mg/l > 400	7 d	Scenedesmus quadricauda	REACH Registration Dossier	Method: other
	Crustacea toxicity	NOEC mg/l 0,74	7 d	Ceriodaphnia dubia	Ecotoxicol. Environ. Saf. 39, 136-146. (	other: US EPA 600/4-91-003

Persistence and degradability

There are no data available on the mixture itself.

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 11 of 13

Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73

BCF

CAS No	Chemical name	BCF	Species	Source
108-88-3	toluene	90	Leuciscus idus melanotus	Chemosphere 14 (10).

Mobility in soil

There are no data available on the mixture itself.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations .

Do not mix with other wastes.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

Waste codes/waste designations according to EWC/AVV

14. Transport information

Land transport (ADR/RID)

<u>UN number or ID number:</u>	UN 1294
<u>United Nations proper shipping name:</u>	TOLUENE
<u>Transport hazard class(es):</u>	3
<u>Packing group:</u>	II
Hazard label:	3
Classification Code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>UN number or ID number:</u>	UN 1294
--------------------------------	---------

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 12 of 13

United Nations proper shipping name: TOLUENE

Transport hazard class(es): 3

Packing group: II

Hazard label: 3

Classification Code: F1

Limited quantity: 1 L

Excepted quantity: E2

Marine transport (IMDG)

UN number or ID number: UN 1294

United Nations proper shipping name: TOLUENE

Transport hazard class(es): 3

Packing group: II

Hazard label: 3

Special Provisions: -

Limited quantity: 1 L

Excepted quantity: E2

EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1294

United Nations proper shipping name: TOLUENE

Transport hazard class(es): 3

Packing group: II

Hazard label: 3

Limited quantity Passenger: 1 L

Passenger LQ: Y341

Excepted quantity: E2

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 40, Entry 48, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing. Observe employment restrictions for women of child-bearing age.

Water hazard class (D): 3 - highly hazardous to water

16. Other information

CONOSTAN® Custom Blend Standard

Revision: 12.09.2024

Product code: AC18.05570

Page 13 of 13

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids
 Asp. Tox. 1: Aspiration hazard
 Skin Irrit. 2: Skin irritation
 Repr. 2: Reproductive toxicity
 STOT SE 3: Specific target organ toxicity - single exposure
 STOT RE 2: Specific target organ toxicity - repeated exposure
 Aquatic Chronic 3: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Repr. 2; H361d	Calculation method
Skin Irrit. 2; H315	Calculation method
STOT SE 3; H336	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H statements (number and full text)

H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Further Information

Provide appropriate information, instructions and training to users
 The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
 The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.
 The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)