

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 1 of 11

1. Identification

Product identifier

CONOSTAN® Single Element Standard – Nickel (Ni)

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Canada Inc.
Street: Québec, CANADA
Place: 21800 Clark Graham Ave
Telephone: CDN-H9X 4B6 Baie-D'Urfé
Telephone: +1 (800) 361-6820
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
Telefax: +1 (800) 253-5549
+1 703-741-5970 (CHEMTREC)

Emergency telephone number:

Further Information

No data available

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 2 of 11

2. Hazard identification**Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

White mineral oil, petroleum

Signal word: Danger**Pictograms:****Hazard statements**

H304

May be fatal if swallowed and enters airways.

EUH208

Contains nickel. May produce an allergic reaction.

Precautionary statements

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331

Do NOT induce vomiting.

P405

Store locked up.

P501

Dispose of contents/container to an appropriate recycling or disposal facility.

Other hazards

No data available

3. Composition/information on ingredients**Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
8042-47-5	White mineral oil, petroleum			95 - < 100 %
	232-455-8			
	Asp. Tox. 1; H304			
7440-02-0	nickel			< 1 %
	231-111-4	028-002-00-7		
	Flam. Sol. 2, Carc. 2, Skin Sens. 1, STOT RE 1, Aquatic Chronic 3; H228 H351 H317 H372 H412			

Full text of H statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
8042-47-5	232-455-8	White mineral oil, petroleum	95 - < 100 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 3 of 11

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

4. First-aid measures

Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water, Soap

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

Most important symptoms and effects, whether acute or delayed

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Foam

Carbon dioxide (CO₂)

Extinguishing powder

Water

Unsuitable extinguishing media

no restriction

Specific hazards arising from the hazardous product

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO₂)

Carbon monoxide

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 4 of 11

Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Take precautionary measures against static discharges.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

Environmental precautions

Do not allow to enter into surface water or drains.

Methods and material for containment and cleaning up

For containment

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Read label before use. Handle and open container with care.

When using do not eat, drink, smoke, sniff. Keep container tightly closed.

Use personal protection equipment.

Do not breathe vapour/aerosol.

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 5 of 11

Provide adequate ventilation.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedings.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place.

Keep container tightly closed.

Hints on joint storage

TRGS 510

Further information on storage conditions

Keep cool. Protect from sunlight.

Specific end use(s)

Laboratory chemicals

8. Exposure controls/Personal protection

Control parameters

Exposure limits (ACGIH)

CAS No	Chemical name	ppm	mg/m ³	Category	Origin
7440-02-0	Nickel elemental (inhalable fraction)		1.5	TWA (8 h)	ACGIH-2025

Biological limit values

CAS No	Chemical name	Parameter	Value	Test material	Sampling time
7440-02-0	NICKEL (ACGIH 2025)	Nickel	5 µg/L	urine	Post-shift at end of workweek

DNEL/DMEL values

CAS No	Chemical name	Exposure route	Effect	Value
8042-47-5	White mineral oil, petroleum			
Worker DNEL, long-term		inhalation	systemic	160 mg/m ³
Worker DNEL, long-term		dermal	systemic	220 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	35 mg/m ³
Consumer DNEL, long-term		dermal	systemic	93 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	40 mg/kg bw/day

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 6 of 11

Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Face protection umbrella

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Hydrocarbons	
Odour threshold:	No data available	
Melting point/freezing point:		No data available
Boiling point or initial boiling point and boiling range:		>315 °C
Flammability:		No data available
Lower explosive limits:		No data available
Upper explosive limits:		No data available
Flash point:		93-99 °C
Auto-ignition temperature:		No data available
Decomposition temperature:		No data available
pH-Value:		No data available
Viscosity / kinematic:		14,2-17 mm²/s
Water solubility:		No data available
Solubility in other solvents		
No data available		
Dissolution rate:		No data available

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 7 of 11

Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Vapour pressure:	No data available
Density:	0,6-0,9 g/cm³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Solvent separation test:

No data available

Solvent content:

100%

Solid content:

No data available

Sublimation point:

No data available

Softening point:

No data available

Pour point:

No data available

No data available

Viscosity / dynamic:

No data available

Flow time:

No data available

Further Information

No data available

10. Stability and reactivity

Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

Chemical stability

The product is stable under storage at normal ambient temperatures.

Possibility of hazardous reactions

Oxidising agent

Conditions to avoid

Heat

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible materials

No data available

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 8 of 11

Hazardous decomposition products

in case of fire, see:

SECTION 5: Firefighting measures

Further information

No data available

11. Toxicological information

Information on toxicological effects

Toxicokinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Route of exposure	Dose	Species	Source	Method
8042-47-5	White mineral oil, petroleum				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1987)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1987)	OECD Guideline 402

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

slightly irritant but not relevant for classification.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

May cause respiratory irritation.

Sensitizing effects

Based on available data, the classification criteria are not met.

Contains nickel. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 9 of 11

Additional information on tests

No data available

Practical experience

No data available

Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

12. Ecological information

Ecotoxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
8042-47-5	White mineral oil, petroleum					
	Acute fish toxicity	LC50 > 10000 mg/l	96 h	Lepomis macrochirus	REACH Registration Dossier	Method: other: procedure as detailed in
	Acute crustacea toxicity	EC50 > 100 mg/l	48 h	Daphnia magna	Study report (2008)	OECD Guideline 202

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
8042-47-5	White mineral oil, petroleum	> 6

Mobility in soil

No data available

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 10 of 11

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
 Send to a physico-chemical treatment facility under observation of official regulations .
 Do not allow to enter into surface water or drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.
 Waste codes/waste designations according to EWC/AVV

14. Transport information

Land transport (ADR/RID)

<u>UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>United Nations proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>Packing group:</u>	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

<u>UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>United Nations proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>Packing group:</u>	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

<u>UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>United Nations proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>Packing group:</u>	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

<u>UN number or ID number:</u>	No dangerous good in sense of this transport regulation.
<u>United Nations proper shipping name:</u>	No dangerous good in sense of this transport regulation.
<u>Transport hazard class(es):</u>	No dangerous good in sense of this transport regulation.
<u>Packing group:</u>	No dangerous good in sense of this transport regulation.

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

No dangerous good in sense of this transport regulation.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No dangerous good in sense of this transport regulation.

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 3, Entry 27, Entry 75

CONOSTAN® Single Element Standard – Nickel (Ni)

Revision: 18.08.2023

Product code: AC18.05879

Page 11 of 11

Information according to Directive 2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

16. Other information

Changes

This data sheet contains changes from the previous version in section(s): 2, 13.

Abbreviations and acronyms

Flam. Sol. 2: Flammable solids

Asp. Tox. 1: Aspiration hazard

Skin Sens. 1: Skin sensitization

Carc. 2: Carcinogenicity

STOT RE 1: Specific target organ toxicity - repeated exposure

Aquatic Chronic 3: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H statements (number and full text)

H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains nickel. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	PC21	-	-	21	15	-	-	-	
2	PROC15	-	-	-	15	-	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)