

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 1 of 11

### 1. Identification

#### Product identifier

CONOSTAN®Sulfur Standard in Diesel Fuel

#### Relevant identified uses of the substance or mixture and uses advised against

##### Use of the substance/mixture

Reagents and laboratory chemicals  
Only for laboratory and analysis purposes.

##### Uses advised against

Do not use for private purposes (household).

#### Details of the supplier of the safety data sheet

##### Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda  
Street: Rua de Júlio Dinis 676 7º  
Place: P-4050-320 Porto  
Telephone: +351 226002917  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: SDS service department

##### Supplier or manufacturer details

Company name: AnalytiChem Canada Inc.  
Street: Québec, CANADA  
21800 Clark Graham Ave  
Place: CDN-H9X 4B6 Baie-D'Urfé  
Telephone: +1 (800) 361-6820 Telefax: +1 (800) 253-5549  
E-mail: info@analytichem.com  
Contact person: SDS service department  
E-mail: SDS@analytichem.com  
Internet: www.analytichem.com  
Responsible Department: AnalytiChem:  
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20  
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200  
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848  
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500  
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378  
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701  
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333  
+1 703-741-5970 (CHEMTREC)

#### Emergency telephone number:

#### Further Information

No data available

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 2 of 11

## 2. Hazard identification

Classification of the substance or mixture

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

Label elements

Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:

Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P405 Store locked up.  
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Other hazards

No data available

## 3. Composition/information on ingredients

SubstancesRelevant ingredients

| CAS No     | Chemical name                                                          |              |          | Quantity |
|------------|------------------------------------------------------------------------|--------------|----------|----------|
|            | EC No                                                                  | Index No     | REACH No |          |
|            | Classification (Regulation (EC) No 1272/2008)                          |              |          |          |
| 64742-47-8 | "Distillates (petroleum), hydro-treated light; Kerosine - unspecified" |              |          | 100 %    |
|            | 265-149-8                                                              | 649-422-00-2 |          |          |
|            | Asp. Tox. 1; H304                                                      |              |          |          |

Full text of H statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No     | EC No                                                                                            | Chemical name                                                          | Quantity |
|------------|--------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|----------|
|            | Specific Conc. Limits, M-factors and ATE                                                         |                                                                        |          |
| 64742-47-8 | 265-149-8                                                                                        | "Distillates (petroleum), hydro-treated light; Kerosine - unspecified" | 100 %    |
|            | inhalation: LC50 = > 5,28 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg |                                                                        |          |

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

## 4. First-aid measures

**CONOSTAN®Sulfur Standard in Diesel Fuel**

Revision: 23.11.2023

Product code: AC18.06035

Page 3 of 11

**Description of first aid measures**

**General information**

No data available

**After inhalation**

Provide fresh air.

Call a doctor if you feel unwell.

**After contact with skin**

Wash immediately with: Water, Soap

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water.

In case of eye irritation consult an ophthalmologist.

**After ingestion**

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

**Most important symptoms and effects, whether acute or delayed**

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

**Indication of immediate medical attention and special treatment needed**

Treat symptomatically.

**5. Fire-fighting measures**

**Extinguishing media**

**Suitable extinguishing media**

Foam

Carbon dioxide (CO<sub>2</sub>)

Extinguishing powder

Water

**Unsuitable extinguishing media**

no restriction

**Specific hazards arising from the hazardous product**

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO<sub>2</sub>)

Carbon monoxide

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

**Special protective equipment and precautions for fire-fighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Use water spray jet to protect personnel and to cool endangered containers.

Move undamaged containers from immediate hazard area if it can be done safely.

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 4 of 11

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

##### General advice

In case of warming:  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.  
Take precautionary measures against static discharges.

##### For non-emergency personnel

Provide adequate ventilation.  
Use personal protection equipment.  
Avoid contact with skin, eyes and clothes.  
Remove persons to safety.  
Emergency procedures  
Consult an expert  
Do not breathe dust/fume/gas/mist/vapours/spray.

##### For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

#### Environmental precautions

Do not allow to enter into surface water or drains.

#### Methods and material for containment and cleaning up

##### For containment

Cover drains.  
Prevent spread over a wide area (e.g. by containment or oil barriers).  
Collect in closed and suitable containers for disposal.  
Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

##### For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

##### Other information

Provide adequate ventilation.  
Do not breathe dust/fume/gas/mist/vapours/spray.  
Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### Reference to other sections

Safe handling: see section 7  
Personal protection equipment: see section 8  
Disposal: see section 13

### 7. Handling and storage

#### Precautions for safe handling

##### Advice on safe handling

Read label before use. Handle and open container with care.  
When using do not eat, drink, smoke, sniff. Keep container tightly closed.  
Use personal protection equipment.  
Do not breathe vapour/aerosol.  
Provide adequate ventilation.

##### Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Take precautionary measures against static discharges.  
In case of warming:  
Vapours are heavier than air, spread along floors and form explosive mixtures with air.

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 5 of 11

### Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

### Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

### Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Store in a well-ventilated place.

Keep container tightly closed.

#### Hints on joint storage

TRGS 510

#### Further information on storage conditions

Keep cool. Protect from sunlight.

### Specific end use(s)

Laboratory chemicals

## 8. Exposure controls/Personal protection

### Control parameters

### Exposure controls

#### Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

goggles

Face protection umbrella

##### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### Skin protection

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

##### Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

##### Thermal hazards

No data available

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 6 of 11

### 9. Physical and chemical properties

#### Information on basic physical and chemical properties

|                                                           |                    |
|-----------------------------------------------------------|--------------------|
| Physical state:                                           | Liquid             |
| Colour:                                                   | colourless         |
| Odour:                                                    | like: Hydrocarbons |
| Odour threshold:                                          | No data available  |
| Melting point/freezing point:                             | -49 °C             |
| Boiling point or initial boiling point and boiling range: | 222,8-245 °C       |
| Flammability:                                             | No data available  |
| Lower explosive limits:                                   | No data available  |
| Upper explosive limits:                                   | No data available  |
| Flash point:                                              | No data available  |
| Auto-ignition temperature:                                | No data available  |
| Decomposition temperature:                                | No data available  |
| pH-Value:                                                 | No data available  |
| Viscosity / kinematic:                                    | 2 mm²/s            |
| Water solubility:                                         | No data available  |
| Solubility in other solvents                              | No data available  |
| Dissolution rate:                                         | No data available  |
| Partition coefficient n-octanol/water:                    | No data available  |
| Dispersion stability:                                     | No data available  |
| Vapour pressure:                                          | No data available  |
| Density:                                                  | 0,804 g/cm³        |
| Relative density:                                         | No data available  |
| Bulk density:                                             | No data available  |
| Relative vapour density:                                  | No data available  |
| Particle characteristics:                                 | No data available  |

#### Other information

##### Information with regard to physical hazard classes

###### Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

##### Other safety characteristics

|                          |                   |
|--------------------------|-------------------|
| Evaporation rate:        | No data available |
| Solvent separation test: | No data available |
| Solvent content:         | 100%              |
| Solid content:           | No data available |
| Sublimation point:       | No data available |
| Softening point:         | No data available |
| Pour point:              | No data available |

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 7 of 11

Viscosity / dynamic:

No data available

Flow time:

No data available

No data available

### Further Information

No data available

## 10. Stability and reactivity

### Reactivity

In case of warming:

Vapours may form explosive mixtures with air.

### Chemical stability

The product is stable under storage at normal ambient temperatures.

### Possibility of hazardous reactions

Oxidising agent

### Conditions to avoid

Heat

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Incompatible materials

No data available

### Hazardous decomposition products

in case of fire, see:

SECTION 5: Firefighting measures

### Further information

No data available

## 11. Toxicological information

### Information on toxicological effects

#### Toxicokinetics, metabolism and distribution

No data available

#### Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No     | Chemical name                                                          |                   |         |                     |                    |
|------------|------------------------------------------------------------------------|-------------------|---------|---------------------|--------------------|
|            | Route of exposure                                                      | Dose              | Species | Source              | Method             |
| 64742-47-8 | "Distillates (petroleum), hydro-treated light; Kerosine - unspecified" |                   |         |                     |                    |
|            | oral                                                                   | LD50 > 5000 mg/kg | Rat     | Study report (1992) | EPA OTS 798.1175   |
|            | dermal                                                                 | LD50 > 2000 mg/kg | Rabbit  | Study report (1992) | EPA OTS 798.1100   |
|            | inhalation (4 h) vapour                                                | LC50 > 5,28 mg/l  | Rat     | Study report (1987) | OECD Guideline 403 |

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 8 of 11

### Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

slightly irritant but not relevant for classification.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

May cause respiratory irritation.

### Sensitizing effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Information on likely routes of exposure

No data available

### Specific effects in experiment on an animal

No data available

### Additional information on tests

No data available

### Practical experience

No data available

### Information on other hazards

#### Endocrine disrupting properties

No data available

#### Other information

No data available

### Further information

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

## 12. Ecological information

### Ecotoxicity

Based on available data, the classification criteria are not met.



**CONOSTAN®Sulfur Standard in Diesel Fuel**

Revision: 23.11.2023

Product code: AC18.06035

Page 9 of 11

| CAS No     | Chemical name                                                          |                 |           |                          |                     |                    |
|------------|------------------------------------------------------------------------|-----------------|-----------|--------------------------|---------------------|--------------------|
|            | Aquatic toxicity                                                       | Dose            | [h]   [d] | Species                  | Source              | Method             |
| 64742-47-8 | "Distillates (petroleum), hydro-treated light; Kerosine - unspecified" |                 |           |                          |                     |                    |
|            | Acute fish toxicity                                                    | LL50 2 - 5 mg/l | 96 h      | Oncorhynchus mykiss      | Study report (1994) | OECD Guideline 203 |
|            | Acute algae toxicity                                                   | ErC50 8,3 mg/l  | 72 h      | Raphidocelis subcapitata | Study report (1995) | OECD Guideline 201 |
|            | Acute crustacea toxicity                                               | EL50 1,4 mg/l   | 48 h      | Daphnia magna            | Study report (1995) | OECD Guideline 202 |

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**Other adverse effects**

Do not allow to enter into surface water or drains.

**Further information**

Avoid release to the environment.

**13. Disposal considerations**
**Waste treatment methods**
**Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not allow to enter into surface water or drains.

**Contaminated packaging**

Handle contaminated packages in the same way as the substance itself.

Waste codes/waste designations according to EWC/AVV

**14. Transport information**
**Land transport (ADR/RID)**
**UN number or ID number:**

No dangerous good in sense of this transport regulation.

**United Nations proper shipping name:**

No dangerous good in sense of this transport regulation.

**Transport hazard class(es):**

No dangerous good in sense of this transport regulation.

**Packing group:**

No dangerous good in sense of this transport regulation.

**Inland waterways transport (ADN)**
**UN number or ID number:**

No dangerous good in sense of this transport regulation.

**United Nations proper shipping name:**

No dangerous good in sense of this transport regulation.

**Transport hazard class(es):**

No dangerous good in sense of this transport regulation.

**Packing group:**

No dangerous good in sense of this transport regulation.

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 10 of 11

### Marine transport (IMDG)

|                                             |                                                          |
|---------------------------------------------|----------------------------------------------------------|
| <u>UN number or ID number:</u>              | No dangerous good in sense of this transport regulation. |
| <u>United Nations proper shipping name:</u> | No dangerous good in sense of this transport regulation. |
| <u>Transport hazard class(es):</u>          | No dangerous good in sense of this transport regulation. |
| <u>Packing group:</u>                       | No dangerous good in sense of this transport regulation. |

### Air transport (ICAO-TI/IATA-DGR)

|                                             |                                                          |
|---------------------------------------------|----------------------------------------------------------|
| <u>UN number or ID number:</u>              | No dangerous good in sense of this transport regulation. |
| <u>United Nations proper shipping name:</u> | No dangerous good in sense of this transport regulation. |
| <u>Transport hazard class(es):</u>          | No dangerous good in sense of this transport regulation. |
| <u>Packing group:</u>                       | No dangerous good in sense of this transport regulation. |

### Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### Special precautions for user

No dangerous good in sense of this transport regulation.

### Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No dangerous good in sense of this transport regulation.

## 15. Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive 2012/18/EU (SEVESO III): Not subject to 2012/18/EU (SEVESO III)

#### National regulatory information

Water hazard class (D): 3 - highly hazardous to water

## 16. Other information

### Abbreviations and acronyms

Asp. Tox. 1: Aspiration hazard

### Relevant H statements (number and full text)

H304 May be fatal if swallowed and enters airways.

### Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Provide appropriate information, instructions and training to users

## CONOSTAN®Sulfur Standard in Diesel Fuel

Revision: 23.11.2023

Product code: AC18.06035

Page 11 of 11

### Identified uses

| No | Short title | LCS | SU | PC | PROC | ERC | AC | TF | Specification |
|----|-------------|-----|----|----|------|-----|----|----|---------------|
| 1  | PC21        | -   | -  | 21 | 15   | -   | -  | -  |               |
| 2  | PROC15      | -   | -  | -  | 15   | -   | -  | -  |               |

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories