

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Reagents and laboratory chemicals
Only for laboratory and analysis purposes.

Uses advised against

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet

Details of the supplier of the safety data sheet

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem Canada Inc.
Street: Québec, CANADA
Place: 21800 Clark Graham Ave
Telephone: CDN-H9X 4B6 Baie-D'Urfé
Telephone: +1 (800) 361-6820
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

Telefax: +1 (800) 253-5549

1.4. Emergency telephone number:

Further Information

No data available

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 2 of 11

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"

Signal word: Danger

Pictograms:



Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"			100 %
	265-149-8	649-422-00-2		
	Asp. Tox. 1; H304			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-47-8	265-149-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"	100 %
		inhalation: LC50 = > 5,28 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 3 of 11

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No data available

After inhalation

Provide fresh air.

Call a doctor if you feel unwell.

After contact with skin

Wash immediately with: Water, Soap

Take off immediately all contaminated clothing and wash it before reuse.

In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs.

Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Carbon dioxide (CO₂)

Extinguishing powder

Water

Unsuitable extinguishing media

No data available

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated:

Carbon dioxide (CO₂)

Carbon monoxide

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 4 of 11

Additional information

- Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
- Use water spray jet to protect personnel and to cool endangered containers.
- Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- In case of warning:
- Vapours are heavier than air, spread along floors and form explosive mixtures with air.
- Take precautionary measures against static discharges.

For non-emergency personnel

- Provide adequate ventilation.
- Use personal protection equipment.
- Avoid contact with skin, eyes and clothes.
- Remove persons to safety.
- Emergency procedures
- Consult an expert
- Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

- Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

- Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment

- Cover drains.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Collect in closed and suitable containers for disposal.
- Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

- Clean contaminated articles and floor according to the environmental legislation.

Other information

- Provide adequate ventilation.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Read label before use. Handle and open container with care.
- When using do not eat, drink, smoke, sniff. Keep container tightly closed.
- Use personal protection equipment.
- Do not breathe vapour/aerosol.
- Provide adequate ventilation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 5 of 11

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Take precautionary measures against static discharges.

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.

Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Store in a well-ventilated place.

Keep container tightly closed.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep cool. Protect from sunlight.

7.3. Specific end use(s)

Laboratory chemicals

Only for laboratory and analysis purposes.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

Observe in addition any national regulations!

8.2. Exposure controls

Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

goggles

Hand protection

Tested protective gloves must be worn

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Skin protection

Wear suitable protective clothing.

Take off immediately all contaminated clothing and wash it before reuse.

Wash hands and face before breaks and after work and take a shower if necessary.

Draw up and observe skin protection programme.

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 6 of 11

Respiratory protection

Respiratory protection necessary at: aerosol or mist formation

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	colourless, clear
Odour:	like: Hydrocarbons
Odour threshold:	No data available
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	218-800 (424.4-1472 °F) °C
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility:	No data available
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure:	No data available
Density:	No data available
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of warming:

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility:

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 7 of 11

Other safety characteristics

Evaporation rate:	No data available
Solvent separation test:	No data available
Solvent content:	No data available
Solid content:	No data available
Sublimation point:	No data available
Softening point:	No data available
Pour point:	No data available
No data available:	No data available
Viscosity / dynamic:	No data available
Flow time:	No data available

Further Information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

In case of warming:
Vapours may form explosive mixtures with air.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Oxidising agent

10.4. Conditions to avoid

Heat
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

in case of fire, see:
SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicocinetics, metabolism and distribution

No data available

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 8 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1992)	EPA OTS 798.1175
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1992)	EPA OTS 798.1100
	inhalation (4 h) vapour	LC50 > 5,28 mg/l	Rat	Study report (1987)	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

No data available

Further information

Gastrointestinal complaints

Pneumonia

Vapours may cause drowsiness and dizziness.

Dizziness

Depression of central nervous system

Headache

SECTION 12: Ecological information

12.1. Toxicity

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 9 of 11

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
64742-47-8	"Distillates (petroleum), hydro-treated light; Kerosine - unspecified"						
	Acute fish toxicity	LL50 mg/l	2 - 5	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50	8,3 mg/l	72 h	Raphidocelis subcapitata	Study report (1995)	OECD Guideline 201
	Acute crustacea toxicity	EL50	1,4 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of contents/container to hazardous or special waste collection point.
Do not allow to enter into surface water or drains.

Contaminated packaging

This material and its container must be disposed of as hazardous waste.
Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 10 of 11

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

Information according to Directive
2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

SECTION 16: Other information

Abbreviations and acronyms

Asp. Tox. 1: Aspiration hazard, hazard category 1

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CONOSTAN S in Diesel Fuel Std, 40,000ppm (150-410-023)

Revision: 21.01.2026

Product code: AC18.06051

Page 11 of 11

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	PC21	-	-	21	15	-	-	-	
2	PROC15	-	-	-	15	-	-	-	

LCS: Life cycle stages

PC: Product categories

ERC: Environmental release categories

TF: Technical functions

SU: Sectors of use

PROC: Process categories

AC: Article categories

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)