

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### CONOSTAN Very-low Sulfur in Iso UV set

Revision: 09.06.2023

Product code: AC18.10195

Page 1 of 7

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

CONOSTAN Very-low Sulfur in Iso UV set

REACH Registration Number:	01-2119457965-22-XXXX
CAS No:	540-84-1
Index No:	601-009-00-8
EC No:	208-759-1

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Reagents and laboratory chemicals  
 Only for laboratory and analysis purposes.

### 1.3. Details of the supplier of the safety data sheet

#### Details of the supplier of the safety data sheet

Company name:	AnalytiChem Services, Unipessoal, Lda	
Street:	Rua de Júlio Dinis 676 7º	
Place:	P-4050-320 Porto	
Telephone:	+351 226002917	
E-mail:	info@analytichem.com	
Contact person:	SDS service department	
E-mail:	SDS@analytichem.com	
Internet:	www.analytichem.com	
Responsible Department:	SDS service department	

#### Supplier or manufacturer details

Company name:	AnalytiChem Canada Inc.	
	Québec, CANADA	
Street:	21800 Clark Graham Ave	
Place:	CDN-H9X 4B6 Baie-D'Urfé	
Telephone:	+1 (800) 361-6820	Telefax: +1 (800) 253-5549
E-mail:	info@analytichem.com	
Contact person:	SDS service department	
E-mail:	SDS@analytichem.com	
Internet:	www.analytichem.com	
Responsible Department:	AnalytiChem:	
	EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20	
	EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200	
	EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848	
	UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500	
	USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378	
	Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701	
	Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333	
	+353 1 901 4670 (CHEMTREC)	

### 1.4. Emergency telephone number:

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### CONOSTAN Very-low Sulfur in Iso UV set

Revision: 09.06.2023

Product code: AC18.10195

Page 2 of 7

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Regulation (EC) No 1272/2008

Flam. Liq. 2; H225  
 Skin Irrit. 2; H315  
 STOT SE 3; H336  
 Asp. Tox. 1; H304  
 Aquatic Acute 1; H400  
 Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

### 2.2. Label elements

#### Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



#### Hazard statements

H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H304 May be fatal if swallowed and enters airways.  
 H410 Very toxic to aquatic life with long lasting effects.

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P331 Do NOT induce vomiting.  
 P405 Store locked up.  
 P501 Dispose of contents/container to ....

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Sum formula: C8H18  
 Molecular weight: 114,23 g/mol

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**CONOSTAN Very-low Sulfur in Iso UV set**

Revision: 09.06.2023

Product code: AC18.10195

Page 3 of 7

**Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
540-84-1	2,2,4-trimethylpentane			100 %
	208-759-1	601-009-00-8	01-2119457965-22-XXXX	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1; H225 H315 H336 H304 H400 H410			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
540-84-1	208-759-1	2,2,4-trimethylpentane	100 %
	inhalation: LC50 = > 33,52 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**SECTION 5: Firefighting measures**
**5.1. Extinguishing media**
**SECTION 6: Accidental release measures**
**6.1. Personal precautions, protective equipment and emergency procedures**
**General advice**

Keep away from sources of ignition - No smoking.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

Take action to prevent static discharges.

**For non-emergency personnel**

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

**For emergency responders**

Precautionary statements For emergency responders : Personal protection equipment: see section 8

**6.3. Methods and material for containment and cleaning up**
**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**CONOSTAN Very-low Sulfur in Iso UV set**

Revision: 09.06.2023

Product code: AC18.10195

Page 4 of 7

**For cleaning up**

Clean contaminated articles and floor according to the environmental legislation.

**Other information**

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

**SECTION 7: Handling and storage**
**7.1. Precautions for safe handling**
**7.2. Conditions for safe storage, including any incompatibilities**
**SECTION 8: Exposure controls/personal protection**
**8.1. Control parameters**
**DNEL/DMEL values**

CAS No	Substance	Exposure route	Effect	Value
540-84-1	2,2,4-trimethylpentane			
Worker DNEL, long-term		inhalation	systemic	2035 mg/m <sup>3</sup>
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m <sup>3</sup>
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

**8.2. Exposure controls**
**SECTION 9: Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	petrol-like
Melting point/freezing point:	-107 °C °C
Boiling point or initial boiling point and boiling range:	99 °C °C
Lower explosion limits:	1,1 vol. %
Upper explosion limits:	6,0 Vol % vol. %
Flash point:	-12 °C °C
Auto-ignition temperature:	410 °C °C
pH-Value:	neutral
Water solubility:	No
Vapour pressure: (at 20 °C °C)	51 hPa hPa
Density:	0,69 g/cm <sup>3</sup> g/cm <sup>3</sup>

**SECTION 10: Stability and reactivity**
**SECTION 11: Toxicological information**
**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**CONOSTAN Very-low Sulfur in Iso UV set**

Revision: 09.06.2023

Product code: AC18.10195

Page 5 of 7

**Acute toxicity**

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
540-84-1	2,2,4-trimethylpentane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 > 33,52 mg/l	Rat	Study report (1982)	OECD Guideline 403

**SECTION 12: Ecological information**
**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
540-84-1	2,2,4-trimethylpentane					
	Acute fish toxicity	LC50 0,11 mg/l	96 h	Oncorhynchus mykiss	SIDS Initial Assessment Report For SIAM	OECD Guideline 203
	Acute algae toxicity	ErC50 2,943 mg/l	72 h	Pseudokirchneriella subcapitata	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EC50 0,4 mg/l	48 h	Daphnia magna	Publication (1986)	other: As described in: The evaluation o
	Fish toxicity	NOEC 0,82 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC 1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211

**12.3. Bioaccumulative potential**
**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
540-84-1	2,2,4-trimethylpentane	4,08

**BCF**

CAS No	Chemical name	BCF	Species	Source
540-84-1	2,2,4-trimethylpentane	231	calculated	Other company data (

**12.5. Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**12.6. Endocrine disrupting properties**

This substance does not have endocrine disrupting properties with respect to non-target organisms.

**SECTION 13: Disposal considerations**
**13.1. Waste treatment methods**

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**CONOSTAN Very-low Sulfur in Iso UV set**

Revision: 09.06.2023

Product code: AC18.10195

Page 6 of 7

**SECTION 14: Transport information**
**Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1262
<b>14.2. UN proper shipping name:</b>	OCTANE
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1262
<b>14.2. UN proper shipping name:</b>	1262 OCTANE
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Limited quantity:	1L

**Marine transport (IMDG)**

<b>14.1. UN number or ID number:</b>	UN 1262
<b>14.2. UN proper shipping name:</b>	OCTANES, MARINE POLLUTANT
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Marine pollutant:	P
EmS:	F-E,S-E

**Air transport (ICAO-TI/IATA-DGR)**

<b>14.1. UN number or ID number:</b>	UN 1262
<b>14.2. UN proper shipping name:</b>	OCTANES
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: Yes

**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
**EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes: Ja

**National regulatory information**

Water hazard class (D): 2 - obviously hazardous to water

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**CONOSTAN Very-low Sulfur in Iso UV set**

Revision: 09.06.2023

Product code: AC18.10195

Page 7 of 7

**SECTION 16: Other information****Abbreviations and acronyms**

Flam. Liq. 2: Flammable liquids, hazard category 2

Asp. Tox. 1: Aspiration hazard, hazard category 1

Skin Irrit. 2: Skin irritation, hazard category 2

STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3

Aquatic Acute 1: Hazardous to the aquatic environment, hazard category: Acute 1

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard category: Chronic 1

**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.