

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Standard p-xylene 100 µl/l in benzyl alcohol

UFI: JGT4-K37E-400X-8GPW

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**Reagents and laboratory chemicals
Only for laboratory and analysis purposes.**Uses advised against**

Do not use for private purposes (household).

1.3. Details of the supplier of the safety data sheet**Details of the supplier of the safety data sheet**

Company name: AnalytiChem Services, Unipessoal, Lda
Street: Rua de Júlio Dinis 676 7º
Place: P-4050-320 Porto
Telephone: +351 226002917
E-mail: info@analytichem.com
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.com
Responsible Department: SDS service department

Supplier or manufacturer details

Company name: AnalytiChem GmbH
Street: Stempelstraße 6
Place: D-47167 Duisburg
Telephone: 0203/5194-0
E-mail: info@analytichem.de
Contact person: SDS service department
E-mail: SDS@analytichem.com
Internet: www.analytichem.de
Responsible Department: AnalytiChem:
EU-Belgium: AnalytiChem Belgium, Industriezone "De Arend" 2, 8210 Zedelgem, Belgium, +32 50 28 83 20
EU-Germany: AnalytiChem Germany, Stempelstrasse 6, 47167 Duisburg, Germany, +49 203 51 94 – 200
EU-Netherlands: AnalytiChem Netherlands, Communicatieweg 7, 3641 SG Mijdrecht, The Netherlands, +31 297 286848
UK: AnalytiChem UK, Unit 7 Launton Business Center, Murdock Road, Bicester, OX26 4XB, England, +44 1869 355 500
USA: AnalytiChem USA, 227 China Road, Winslow, Maine, 04901, United States, +1 800-244-8378
Canada: AnalytiChem Canada, 21800 Clark Graham Avenue, Baie d'Urfe, H9X 4B6, Canada, +1 514-457-0701
Australia: ORE Research & Exploration Pty Ltd, 37A Hosie Street, Bayswater North, 3153, Australia, +61 3 9729 0333
+353 1 901 4670 (CHEMTREC)

Telefax: 0203/5194-290

1.4. Emergency telephone number:

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 2 of 12

Further Information

This product is a mixture. REACH Registration Number see section 3.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Acute Tox. 4; H332

Acute Tox. 4; H302

Eye Irrit. 2; H319

Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Benzyl alcohol

Signal word: Warning**Pictograms:****Hazard statements**

H302+H332

Harmful if swallowed or if inhaled.

H317

May cause an allergic skin reaction.

H319

Causes serious eye irritation.

Precautionary statements

P261

Avoid breathing dust/fume/gas/mist/vapours/spray.

P280

Wear protective gloves/protective clothing and eye protection/face protection.

P302+P352

IF ON SKIN: Wash with plenty of water.

P333+P313

If skin irritation or rash occurs: Get medical advice/attention.

P362+P364

Take off contaminated clothing and wash it before reuse.

P501

Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
100-51-6	Benzyl alcohol			95 - < 100 %
	202-859-9	603-057-00-5	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2, Skin Sens. 1B; H332 H302 H319 H317			

Full text of H and EUH statements: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
100-51-6	202-859-9	Benzyl alcohol	95 - < 100 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); oral: ATE 1200 mg/kg	

Further Information

This product does not contain substances of very high concern according to Regulation (EC) No 1907/2006 (REACH), Article 57 above the respective regulatory concentration limit of = 0.1 % (w/w).

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

No data available

After inhalation

Provide fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.

After contact with skin

Wash immediately with: Water
Take off immediately all contaminated clothing and wash it before reuse.
Call a doctor if you feel unwell.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth immediately and drink plenty of water.
Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Irritant
Cough
Dyspnoea
Respiratory complaints
Dizziness
Inebriation
Unconsciousness
Vomiting
Gastrointestinal complaints
Headache
Spasms
Agitation
Allergic reactions

4.3. Indication of any immediate medical attention and special treatment needed

Give sodium sulfate as laxative (1 tablespoon in 1 glass of water).

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 4 of 12

Unsuitable extinguishing media

no restriction

5.2. Special hazards arising from the substance or mixture

Combustible liquids

Hazardous combustion products

In case of fire may be liberated: Carbon dioxide (CO₂) Carbon monoxide

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

In case of fire and/or explosion do not breathe fumes.

Avoid contact with skin, eyes and clothes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Move undamaged containers from immediate hazard area if it can be done safely.

Use water spray jet to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Do not breathe vapour/aerosol.

For non-emergency personnel

Provide adequate ventilation.

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

Remove persons to safety.

Emergency procedures

Consult an expert

Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Precautionary statements For emergency responders : Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For containment**

Cover drains.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Collect in closed and suitable containers for disposal.

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

Other information

Provide adequate ventilation.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 5 of 12

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Read label before use. Handle and open container with care.
When using do not eat, drink, smoke, sniff. Keep container tightly closed.
Use personal protection equipment. Use extractor hood (laboratory).
Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation.

Advice on protection against fire and explosion

Usual measures for fire prevention.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.
The choice of body protection depends on the concentration and quantity of hazardous substances. The chemical resistance of protective agents must be clarified with their suppliers.

Further information on handling

Take off immediately all contaminated clothing and wash it before reuse.
Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. If handled uncovered, arrangements with local exhaust ventilation have to be used.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.
Protect against: Light

Hints on joint storage

Take national regulations into account.

Further information on storage conditions

Keep cool. Protect from sunlight.
Protect against: Light
storage temperature < 30°C

7.3. Specific end use(s)

Laboratory chemicals

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 6 of 12

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
100-51-6	Benzyl alcohol			
Worker DNEL, long-term		inhalation	systemic	22 mg/m ³
Worker DNEL, acute		inhalation	systemic	110 mg/m ³
Worker DNEL, long-term		dermal	systemic	8 mg/kg bw/day
Worker DNEL, acute		dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	5,4 mg/m ³
Consumer DNEL, acute		inhalation	systemic	27 mg/m ³
Consumer DNEL, long-term		dermal	systemic	4 mg/kg bw/day
Consumer DNEL, acute		dermal	systemic	20 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4 mg/kg bw/day
Consumer DNEL, acute		oral	systemic	20 mg/kg bw/day

PNEC values

CAS No	Substance	Value
100-51-6	Benzyl alcohol	
Freshwater		1 mg/l
Freshwater (intermittent releases)		2,3 mg/l
Marine water		0,1 mg/l
Freshwater sediment		5,27 mg/kg
Marine sediment		0,527 mg/kg
Micro-organisms in sewage treatment plants (STP)		39 mg/l
Soil		0,456 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Technical measures and the application of suitable work processes have priority over personal protection equipment.

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment**Eye/face protection**

goggles

Face protection umbrella

Hand protection

Protective gloves are recommended Company KCL GmbH, D-36124 Eichenzell, email: vertrieb@kcl.de With specification (test according to EN374):

By long-term hand contact

Trade name/designation KCL 890 Vitoject®

Suitable material: FKM (fluoro rubber) 0,7 mm

Wearing time with permanent contact: > 480 min

By short-term hand contact

Trade name/designation KCL 897 Butoject®

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 7 of 12

Suitable material: FKM (fluoro rubber) 0,7 mm
Wearing time with occasional contact (splashes): > 480 min

The breakthrough times stated above were determined by KCL in laboratory tests acc. to EN374 with samples of the recommended glove types. This recommendation applies only to the product stated in the safety data sheet<(>,<) supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Skin protection

Take off immediately all contaminated clothing and wash it before reuse.
Wash hands and face before breaks and after work and take a shower if necessary.
Draw up and observe skin protection programme.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.
The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
Danger of explosion

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	No data available
Melting point/freezing point:	-15,3 °C
Boiling point or initial boiling point and boiling range:	205 °C
Flammability:	No data available
Lower explosion limits:	1,22 vol. %
Upper explosion limits:	13 vol. %
Flash point:	101 °C
Auto-ignition temperature:	436 °C
Decomposition temperature:	No data available
pH-Value:	No data available
Viscosity / kinematic:	No data available
Water solubility: (at 20 °C)	40 g/l
Solubility in other solvents	No data available
Dissolution rate:	No data available
Partition coefficient n-octanol/water:	No data available
Dispersion stability:	No data available
Vapour pressure: (at 20 °C)	0,07 hPa

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 8 of 12

Vapour pressure: (at 50 °C)	0,07 hPa
Density:	1,04 g/cm ³
Relative density:	No data available
Bulk density:	No data available
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Sustained combustibility: No data available

Self-ignition temperature

Solid: No data available

Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Solvent separation test: No data available

Solvent content: 100,00 %

Solid content: No data available

Sublimation point: No data available

Softening point: No data available

Pour point: No data available

Viscosity / dynamic:
(at 20 °C) 6,57 mPa·s

Flow time: No data available

Further Information

No data available

SECTION 10: Stability and reactivity**10.1. Reactivity**

In case of warming: Vapours may form explosive mixtures with air.

10.2. Chemical stability

Protect against:

Light

Air

10.3. Possibility of hazardous reactions

Oxidising agent

Hydrogen bromide (HBr)

sulphuric acid

Acids

Isocyanates

Iron.

10.4. Conditions to avoid

Protect against: Light

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 9 of 12

10.5. Incompatible materials

plastic

10.6. Hazardous decomposition products

in case of fire, see:

SECTION 5: Firefighting measures

Further information

No data available

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Toxicokinetics, metabolism and distribution**

No data available

Acute toxicity

Harmful if inhaled.

Harmful if swallowed.

ATEmix calculated

ATE (oral) 1200 mg/kg; ATE (dermal) > 2000 mg/kg

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
100-51-6	Benzyl alcohol				
	oral	ATE 1200 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Benzyl alcohol)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

No data available

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience

Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 10 of 12

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other information

Irritant
Cough
Dyspnoea
Respiratory complaints
Dizziness
Inebriation
Unconsciousness
Vomiting
Gastrointestinal complaints
Headache
Spasms
Agitation
Allergic reactions

Further information

Mucous membrane irritation in the mouth, throat, esophagus and gastrointestinal tract.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
100-51-6	Benzyl alcohol					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oryzias latipes	Review article or handbook (2009)	OECD Guideline 203
	Acute algae toxicity	ErC50 770 mg/l	72 h	Pseudokirchneriella subcapitata	Review article or handbook (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 230 mg/l	48 h	Daphnia magna	Review article or handbook (2009)	OECD Guideline 202
	Crustacea toxicity	NOEC 51 mg/l	21 d	Daphnia magna	Review article or handbook (2009)	OECD Guideline 211
	Acute bacteria toxicity	EC50 1385 mg/l ()	3 h	activated sludge, domestic	Study report (1989)	OECD Guideline 209

12.2. Persistence and degradability

92 - 96 %; 14 d; aerob
Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

log Pow: 1 (20 °C)
No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-51-6	Benzyl alcohol	1

12.4. Mobility in soil

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 11 of 12

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Do not allow to enter into surface water or drains.

Avoid release to the environment.

Further information

No data available

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Send to a physico-chemical treatment facility under observation of official regulations.

Do not empty into drains.

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

Waste codes/waste designations according to EWC/AVV

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Marine transport (IMDG)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

No dangerous good in sense of this transport regulation.

14.2. UN proper shipping name:

No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es):

No dangerous good in sense of this transport regulation.

14.4. Packing group:

No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Standard p-xylene 100 µl/l in benzyl alcohol

Revision: 23.02.2026

Product code: AC18.23277

Page 12 of 12

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**EU regulatory information**

Restrictions on use (REACH, annex XVII):
Entry 3, Entry 75

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D): 1 - slightly hazardous to water

SECTION 16: Other information

Abbreviations and acronyms

Acute Tox. 4: Acute toxicity, hazard category 4
Eye Irrit. 2: Eye irritation, hazard category 2
Skin Sens. 1: Skin sensitisation, hazard category 1
Skin Sens. 1B: Skin sensitisation, hazard category 1B

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H332	Calculation method
Acute Tox. 4; H302	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.
H302+H332 Harmful if swallowed or if inhaled.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.

Further Information

Provide appropriate information, instructions and training to users

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)